



**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**SHIFT24/Power Craze 2.0 High Speed Buggy**

**MODEL NUMBER: CT-6176/1422642/VL-6036/VL-6037/VL-6038**

**FCC ID: 2ASK3CT-6176R**

**REPORT NUMBER: 4789461925-6**

**ISSUE DATE: May 22, 2020**

*Prepared for*

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD  
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET  
MONGKOK KOWLOON HONG KONG**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	05/22/2020	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	CFR 47 FCC §15.215 (c) ISED RSS-Gen Clause 6.7	Pass
2	Radiated Emission	CFR 47 FCC §15.249 (a)(d)(e) CFR 47 FCC §15.205 and §15.209	Pass
3	Conducted Emission Test For AC Power Port	FCC Part 15.207	Pass
4	Antenna Requirement	CFR 47 FCC §15.203	Pass

Note 1: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

Note 2: The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C, ISED RSS-210 Issue 10 and ISED RSS-GEN Issue 5 > when <Accuracy Method> decision rule is applied.



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>8</i>
5.2. <i>MAXIMUM FIELD STRENGTH.....</i>	<i>8</i>
5.3. <i>CHANNEL LIST.....</i>	<i>8</i>
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS.....</i>	<i>8</i>
5.5. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>8</i>
5.6. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>9</i>
5.7. <i>TEST ENVIRONMENT .....</i>	<i>9</i>
5.8. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>10</i>
5.9. <i>MEASURING INSTRUMENT AND SOFTWARE USED.....</i>	<i>11</i>
<b>6. ANTENNA PORT TEST RESULTS.....</b>	<b>12</b>
6.1. <i>ON TIME AND DUTY CYCLE.....</i>	<i>12</i>
6.2. <i>20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH .....</i>	<i>14</i>
<b>7. RADIATED TEST RESULTS.....</b>	<b>18</b>
7.1. <i>LIMITS AND PROCEDURE.....</i>	<i>18</i>
7.2. <i>RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS</i> <i>25</i>	
7.3. <i>SPURIOUS EMISSIONS (1~3GHz).....</i>	<i>31</i>
7.4. <i>SPURIOUS EMISSIONS (3~18GHz).....</i>	<i>37</i>
7.5. <i>SPURIOUS EMISSIONS (18~26GHz).....</i>	<i>43</i>
7.6. <i>SPURIOUS EMISSIONS BELOW 30MHz .....</i>	<i>45</i>
7.7. <i>SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz.....</i>	<i>48</i>
<b>8. AC POWER LINE CONDUCTED EMISSIONS.....</b>	<b>50</b>
<b>9. ANTENNA REQUIREMENTS.....</b>	<b>53</b>



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD  
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

## Manufacturer Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD  
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

## EUT Information

EUT Name: SHIFT24/Power Craze 2.0 High Speed Buggy  
Model: CT-6176  
Series Model: 1422642/VL-6036/VL-6037/VL-6038  
Model difference: All the same except for the model name and color.  
Sample Received Date: April 30, 2020  
Sample Status: Normal  
Date of Tested: April 30, 2020~ May 22, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Mick Zhang  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test (include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	5.78dB (1GHz-18GHz)
	5.23dB (18GHz-26GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	SHIFT24/Power Craze 2.0 High Speed Buggy	
EUT Description	The EUT is a wireless remote Car	
Model	CT-6176	
Series Model	1422642/VL-6036/VL-6037/VL-6038	
Model difference	All the same except for the model name and color.	
Product Description	Operation Frequency	2407 MHz ~ 2479 MHz
	Modulation Type	GFSK
Battery	DC 3.7V	

### 5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Channel Number	Max Peak field strength (dB $\mu$ V/m)
2479	3[3]	83.95

### 5.3. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407	3	2467
2	2443	4	2479

### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2407~ 2479	Wire Antenna	0

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

### 5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 1(Low Channel), CH 2(MID Channel), CH 4(High Channel)	2407MHz, 2443MHz, 2479MHz



### 5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2407 MHz ~ 2479 MHz Band				
Test Software Version		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH1	CH2	CH4
GFSK	1	Default	Default	Default

### 5.7. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28°C
Voltage:	VL	/
	VN	DC 3.7V
	VH	/

Note: VL= Lower Extreme Test Voltage  
 VN= Nominal Voltage  
 VH= Upper Extreme Test Voltage  
 TN= Normal Temperature



## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
/	/	/	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB-DC cable	/	/	0.6	/

Note: The USB-DC cable is provided by the customer.


### ACCESSORY

Item	Equipment	Mfr/Brand	Model/Type No.	Specification	Series No.
1	Adapter	SAMSUNG	ETA0U83CBC	5Vdc,1A	DW2G720OS/A

### TEST SETUP

The EUT have the engineer mode inside.

### SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.

**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions						
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date	
EMI Test Receiver	R&S	ESR3	101961	Dec. 5, 2019	Dec. 5, 2020	
Two-Line V-Network	R&S	ENV216	101983	Dec. 5, 2019	Dec. 5, 2020	
Software						
Description			Manufacturer	Name	Version	
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1	
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec. 6, 2019	Dec. 6, 2020
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Sept.17, 2018	Sept.17,2021
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A09099	Dec. 5, 2019	Dec. 5, 2020
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec. 05, 2019	Dec.05, 2020
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept.17,2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00067	Dec. 05, 2019	Dec.05, 2020
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17, 2022
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Dec. 05, 2019	Dec.05, 2020
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11,2018	Aug.11,2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec. 05, 2019	Dec.05, 2020
Software						
Used	Description		Manufacturer	Name	Version	
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Farad	EZ-EMC	Ver. UL-3A1	
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec. 05, 2019	Dec.05, 2020
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec. 05, 2019	Dec.05, 2020

## 6. ANTENNA PORT TEST RESULTS

### 6.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT


Temperature	22.8°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)
GFSK	38.15	100	0.3815	38.15	-8.37


Note: Duty Cycle Correction Factor=20log(x).  
Where: x is Duty Cycle

### ON TIME AND DUTY CYCLE MID CH PLOT



Date: 7.MAY.2020 10:51:02

### ON TIME AND DUTY CYCLE MID CH PLOT-2



Date: 7.MAY.2020 10:50:21

Note: All the modes had been tested, but only the worst duty cycle recorded in the report.

## 6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.249) Subpart C RSS-Gen Issue 5			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.215 (c)	20dB Bandwidth	for reporting purposes only	2400-2483.5
ISED RSS-Gen Clause 6.7 Issue 5	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	22.8°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V



**RESULTS**


Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2407	1.0010	1.0749	PASS

**20 dB BANDWIDTH LOW CH**



Date: 7.MAY.2020 10:34:19

**99% OCCUPIED BANDWIDTH LOW CH**




Date: 7.MAY.2020 10:28:31




Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2443	1.0969	1.0210	PASS

### 20 dB BANDWIDTH MID CH



Date: 7.MAY.2020 10:49:23

### 99% OCCUPIED BANDWIDTH MID CH




Date: 7.MAY.2020 10:44:32






Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2479	1.27	1.5904	PASS

20 dB BANDWIDTH HIG CH



15:50:48 19.05.2020

99% OCCUPIED BANDWIDTH HIG CH



Date: 7.MAY.2020 11:02:37



## 7. RADIATED TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMITS

CFR 47 FCC §15.205 and §15.209

CFR 47 FCC §15.249 (a)(d)(c)(e)

ISED RSS-210 Issue 10 Annex B B.10

RSS-GEN Clause 8.9

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

IC Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands <sup>Note 1</sup>		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.126	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 36.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.




FCC Restricted bands of operation:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.<sup>2</sup>Above 38.6c

**TEST SETUP AND PROCEDURE**

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open field site. Therefore, the sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G



The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured

Above 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter or band reject filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements. Where necessary, average emission are determined by applying the Duty Cycle Correction Factor to the peak measurements. For the Duty Cycle and Correction Factor please refer to clause 6.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


### TEST ENVIRONMENT

Temperature	23.6°C	Relative Humidity	60%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V




## 7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS

### RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2399.870	21.94	32.98	54.92	74.00	-19.08	peak
2	2399.870	13.57	32.98	46.55	54.00	-7.45	AVG
3	2400.000	21.48	32.98	54.46	74.00	-19.54	peak
4	2400.000	13.11	32.98	46.09	54.00	-7.91	AVG
5	2407.020	49.90	33.03	82.93	114.00	-31.07	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2399.760	21.00	32.98	53.98	74.00	-20.02	peak
2	2400.000	19.38	32.98	52.36	74.00	-21.64	peak
3	2407.020	49.00	33.03	82.03	114.00	-31.97	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2443.040	49.70	33.29	82.99	114.00	-31.01	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2442.960	49.69	33.29	82.98	114.00	-31.02	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




**RESTRICTED BANDEGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2478.965	50.35	33.55	83.90	114.00	-30.10	peak
2	2483.500	25.22	33.58	58.80	74.00	-15.20	peak
3	2483.500	16.85	33.58	50.43	54.00	-3.57	AVG
4	2483.515	22.62	33.58	56.20	74.00	-17.80	peak
5	2483.515	14.25	33.58	47.83	54.00	-6.17	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2478.895	50.40	33.55	83.95	114.00	-30.05	peak
2	2483.500	24.87	33.58	58.45	74.00	-15.55	peak
3	2483.500	16.50	33.58	50.08	54.00	-3.92	AVG
4	2483.620	25.06	33.58	58.64	74.00	-15.36	peak
5	2483.620	16.69	33.58	50.27	54.00	-3.73	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### 7.3. SPURIOUS EMISSIONS (1~3GHz)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1548.000	45.88	-11.82	34.06	74.00	-39.94	peak
2	1840.000	45.89	-9.93	35.96	74.00	-38.04	peak
3	2028.000	46.53	-9.64	36.89	74.00	-37.11	peak
4	2352.000	53.81	-8.02	45.79	74.00	-28.21	peak
5	2407.000	47.37	-7.81	39.56	/	/	fundamental
6	2826.000	43.93	-5.92	38.01	74.00	-35.99	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1556.000	45.74	-11.76	33.98	74.00	-40.02	peak
2	1788.000	45.50	-10.04	35.46	74.00	-38.54	peak
3	1858.000	45.83	-9.93	35.90	74.00	-38.10	peak
4	2108.000	45.73	-9.12	36.61	74.00	-37.39	peak
5	2350.000	52.68	-8.02	44.66	74.00	-29.34	peak
6	2407.000	47.22	-7.81	39.41	/	/	fundamental

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.






**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1630.000	45.69	-11.25	34.44	74.00	-39.56	peak
2	2112.000	44.96	-9.10	35.86	74.00	-38.14	peak
3	2338.000	44.73	-8.06	36.67	74.00	-37.33	peak
4	2468.000	44.92	-7.39	37.53	74.00	-36.47	peak
5	2504.000	48.35	-7.19	41.16	74.00	-32.84	peak
6	2912.000	43.85	-5.50	38.35	74.00	-35.65	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1274.000	46.98	-12.43	34.55	74.00	-39.45	peak
2	1744.000	46.13	-10.46	35.67	74.00	-38.33	peak
3	2110.000	45.18	-9.10	36.08	74.00	-37.92	peak
4	2352.000	44.96	-8.02	36.94	74.00	-37.06	peak
5	2443.000	44.92	-7.56	37.36	/	/	fundamental
6	2504.000	48.38	-7.19	41.19	74.00	-32.81	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1778.000	45.83	-10.13	35.70	74.00	-38.30	peak
2	2188.000	44.77	-8.72	36.05	74.00	-37.95	peak
3	2336.000	45.36	-8.07	37.29	74.00	-36.71	peak
4	2479.000	47.26	-7.32	39.94	/	/	fundamental
5	2504.000	47.64	-7.19	40.45	74.00	-33.55	peak
6	2810.000	45.01	-6.00	39.01	74.00	-34.99	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1746.000	45.89	-10.45	35.44	74.00	-38.56	peak
2	1846.000	45.70	-9.93	35.77	74.00	-38.23	peak
3	2479.000	47.14	-7.32	39.82	/	/	fundamental
4	2504.000	48.93	-7.19	41.74	74.00	-32.26	peak
5	2520.000	47.72	-7.27	40.45	74.00	-33.55	peak
6	2908.000	43.41	-5.51	37.90	74.00	-36.10	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

## 7.4. SPURIOUS EMISSIONS (3~18GHz)


### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4814.000	53.42	0.51	53.93	74.00	-20.07	peak
2	7845.000	39.10	7.62	46.72	74.00	-27.28	peak
3	11565.000	35.45	13.26	48.71	74.00	-25.29	peak
4	13800.000	33.34	17.10	50.44	74.00	-23.56	peak
5	17100.000	31.18	20.64	51.82	74.00	-22.18	peak
6	17775.000	29.91	23.09	53.00	74.00	-21.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The High Pass filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4814.000	56.84	0.51	57.35	74.00	-16.65	peak
2	4814.000	48.47	0.51	48.98	54.00	-5.02	AVG
3	7890.000	39.39	7.30	46.69	74.00	-27.31	peak
4	11595.000	35.89	13.19	49.08	74.00	-24.92	peak
5	13905.000	33.56	16.20	49.76	74.00	-24.24	peak
6	15990.000	32.41	17.68	50.09	74.00	-23.91	peak
7	17775.000	29.74	23.09	52.83	74.00	-21.17	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4886.000	57.31	0.81	58.12	74.00	-15.88	peak
2	4886.000	48.94	0.81	49.75	54.00	-4.25	AVG
3	7320.000	40.69	6.14	46.83	74.00	-27.17	peak
4	12570.000	34.96	14.17	49.13	74.00	-24.87	peak
5	13935.000	33.75	16.15	49.90	74.00	-24.10	peak
6	17370.000	31.04	21.52	52.56	74.00	-21.44	peak
7	17805.000	29.49	23.31	52.80	74.00	-21.20	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Cycle Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. The High Pass filter loss factor already add into the correct factor.
  7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4886.000	57.02	0.81	57.83	74.00	-16.17	peak
2	4886.000	48.65	0.81	49.46	54.00	-4.54	AVG
3	7320.000	40.65	6.14	46.79	74.00	-27.21	peak
4	11745.000	36.63	13.05	49.68	74.00	-24.32	peak
5	13920.000	33.99	16.17	50.16	74.00	-23.84	peak
6	16650.000	30.74	19.70	50.44	74.00	-23.56	peak
7	17775.000	29.57	23.09	52.66	74.00	-21.34	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.






**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4958.000	59.24	1.17	60.41	74.00	-13.59	peak
2	4958.000	50.87	1.17	52.04	54.00	-1.96	AVG
3	9060.000	38.33	9.28	47.61	74.00	-26.39	peak
4	13035.000	34.25	15.03	49.28	74.00	-24.72	peak
5	14430.000	33.96	16.35	50.31	74.00	-23.69	peak
6	16005.000	33.74	17.71	51.45	74.00	-22.55	peak
7	17850.000	29.73	23.32	53.05	74.00	-20.95	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Cycle Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. The High Pass filter loss factor already add into the correct factor.
  7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4958.000	59.38	1.17	60.55	74.00	-13.45	peak
2	4958.000	51.01	1.17	52.18	54.00	-1.82	AVG
3	7845.000	39.27	7.62	46.89	74.00	-27.11	peak
4	10590.000	37.69	11.88	49.57	74.00	-24.43	peak
5	13905.000	34.48	16.20	50.68	74.00	-23.32	peak
6	17325.000	30.38	21.67	52.05	74.00	-21.95	peak
7	17970.000	29.46	23.42	52.88	74.00	-21.12	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Cycle Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. The High Pass filter loss factor already add into the correct factor.
  7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 7.5. SPURIOUS EMISSIONS (18~26GHz)

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19024.000	49.99	-4.91	45.08	74.00	-28.92	peak
2	21488.000	50.85	-5.76	45.09	74.00	-28.91	peak
3	22744.000	51.18	-5.74	45.44	74.00	-28.56	peak
4	23536.000	50.96	-4.74	46.22	74.00	-27.78	peak
5	24312.000	50.10	-3.35	46.75	74.00	-27.25	peak
6	25784.000	49.23	-1.49	47.74	74.00	-26.26	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	21248.000	50.98	-5.51	45.47	74.00	-28.53	peak
2	21848.000	51.76	-5.95	45.81	74.00	-28.19	peak
3	22880.000	51.92	-5.67	46.25	74.00	-27.75	peak
4	23544.000	51.13	-4.73	46.40	74.00	-27.60	peak
5	24688.000	48.39	-2.11	46.28	74.00	-27.72	peak
6	25784.000	48.58	-1.49	47.09	74.00	-26.91	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

Note: All test modes had been tested, only the worst data record in the report.

## 7.6. SPURIOUS EMISSIONS BELOW 30MHz

### SPURIOUS EMISSIONS (HIGH CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9kHz~ 150kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	72.72	-101.40	-28.68	47.60	-76.28	peak
2	0.0122	70.50	-101.39	-30.89	45.87	-76.76	peak
3	0.0222	66.86	-101.35	-34.49	40.67	-75.16	peak
4	0.0286	64.46	-101.38	-36.92	38.47	-75.39	peak
5	0.0551	59.95	-101.50	-41.55	32.78	-74.33	peak
6	0.0791	55.71	-101.63	-45.92	29.64	-75.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.


**150kHz ~ 490kHz**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.1607	70.04	-101.65	-31.61	23.48	-55.09	peak
2	0.1811	67.55	-101.68	-34.13	22.45	-56.58	peak
3	0.2298	65.05	-101.77	-36.72	20.37	-57.09	peak
4	0.2782	61.79	-101.83	-40.04	18.71	-58.75	peak
5	0.3190	59.79	-101.88	-42.09	17.53	-59.62	peak
6	0.4132	57.05	-101.98	-44.93	15.28	-60.21	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.  
 3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**490kHz ~ 30MHz**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.7929	59.02	-62.14	-3.12	29.62	-32.74	peak
2	1.3812	55.47	-62.10	-6.63	24.80	-31.43	peak
3	2.7033	52.40	-61.65	-9.25	29.54	-38.79	peak
4	7.5429	50.58	-61.14	-10.56	29.54	-40.10	peak
5	8.9001	50.91	-60.95	-10.04	29.54	-39.58	peak
6	19.7895	50.42	-60.84	-10.42	29.54	-39.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All test modes had been tested, only the worst data record in the report.

## 7.7. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz

### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.8800	37.30	-17.33	19.97	40.00	-20.03	QP
2	176.4700	28.56	-16.77	11.79	43.50	-31.71	QP
3	250.1900	30.34	-16.34	14.00	46.00	-32.00	QP
4	727.4300	26.91	-6.57	20.34	46.00	-25.66	QP
5	900.0900	28.98	-4.25	24.73	46.00	-21.27	QP
6	969.9300	28.69	-3.35	25.34	54.00	-28.66	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.





**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	27.37	-17.56	9.81	40.00	-30.19	QP
2	191.9900	24.70	-16.10	8.60	43.50	-34.90	QP
3	250.1900	29.96	-16.34	13.62	46.00	-32.38	QP
4	299.6600	28.83	-14.39	14.44	46.00	-31.56	QP
5	837.0400	28.01	-4.94	23.07	46.00	-22.93	QP
6	946.6500	29.15	-3.51	25.64	46.00	-20.36	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All test modes had been tested, only the worst data record in the report.


## 8. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


### TEST ENVIRONMENT

Temperature	26°C	Relative Humidity	58%
Atmosphere Pressure	101kPa		



**TEST RESULTS**

Conducted Emissions			
Test Mode:	Charging	Phase:	Line
Test Voltage:	AC 120V_60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1643	26.96	9.61	36.57	65.24	-28.67	QP
2	0.1643	11.90	9.61	21.51	55.24	-33.73	AVG
3	0.1952	26.19	9.60	35.79	63.81	-28.02	QP
4	0.1952	11.53	9.60	21.13	53.81	-32.68	AVG
5	0.2244	24.31	9.60	33.91	62.65	-28.74	QP
6	0.2244	9.23	9.60	18.83	52.65	-33.82	AVG
7	0.5897	19.97	9.60	29.57	56.00	-26.43	QP
8	0.5897	13.11	9.60	22.71	46.00	-23.29	AVG
9	0.6146	21.10	9.60	30.70	56.00	-25.30	QP
10	0.6146	12.12	9.60	21.72	46.00	-24.28	AVG
11	8.2990	10.10	9.72	19.82	60.00	-40.18	QP
12	8.2990	3.53	9.72	13.25	50.00	-36.75	AVG

Note: 1. Result = Reading +Correct (Insertion Loss + Cable Loss + Attenuator Factor)  
2. Margin = Result - Limit



Conducted Emissions			
Test Mode:	Charging	Phase:	Neutral
Test Voltage:	AC 120V_60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1681	28.41	9.60	38.01	65.05	-27.04	QP
2	0.1681	15.70	9.60	25.30	55.05	-29.75	AVG
3	0.1915	24.67	9.60	34.27	63.97	-29.70	QP
4	0.1915	11.83	9.60	21.43	53.97	-32.54	AVG
5	0.5902	28.17	9.60	37.77	56.00	-18.23	QP
6	0.5902	22.49	9.60	32.09	46.00	-13.91	AVG
7	1.1462	20.43	9.61	30.04	56.00	-25.96	QP
8	1.1462	14.70	9.61	24.31	46.00	-21.69	AVG
9	2.0706	20.05	9.63	29.68	56.00	-26.32	QP
10	2.0706	13.25	9.63	22.88	46.00	-23.12	AVG
11	7.7326	17.85	9.72	27.57	60.00	-32.43	QP
12	7.7326	10.31	9.72	20.03	50.00	-29.97	AVG

Note: 1. Result = Reading +Correct (Insertion Loss + Cable Loss + Attenuator Factor)  
2. Margin = Result - Limit



## 9. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

---

**END OF REPORT**