



## **FCC RF EXPOSURE REPORT**

*For*

**FLEX3.0**

**MODEL NUMBER: SC-6141**

**FCC ID: 2ASK3SC-6141R**

**REPORT NUMBER: 4789984716.2-4**

**ISSUE DATE: June 29, 2021**

*Prepared for*

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET  
MONGKOK KOWLOON HONG KONG**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	06/29/2021	Initial Issue	



## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. FACILITIES AND ACCREDITATION .....	5
4. REQUIREMENT .....	6



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
 Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
 TUNG CHOI STREET MONGKOK KOWLOON HONG KONG.

## Manufacturer Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
 Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
 TUNG CHOI STREET MONGKOK KOWLOON HONG KONG.

## EUT Information

EUT Name: FLEX3.0  
 Model: SC-6141  
 Sample ID: 3995365  
 Sample Received Date: June 11, 2021  
 Sample Status: Normal  
 Date of Tested: June 11, 2021 ~ June 24, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	PASS

Prepared By:

\_\_\_\_\_

Denny Huang  
Project Engineer

Checked By:

\_\_\_\_\_

Shawn Wen  
Laboratory Leader

Approved By:

\_\_\_\_\_

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b>          UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b>          UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b>          UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b>          UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.          Facility Name:          Chamber D, the VCCI registration No. is G-20019 and R-20004          Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

## 4. REQUIREMENT

### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

### RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

### CALCULATION METHOD

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

**CALCULATED RESULTS**

WiFi Mode					
Frequency	Output Power	Output Power	Power Density	Power Density Limit	Test Result
MHz	dBm	mW	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	--
2412-2462	16.5	44.67	0.009	1.0	Complies

- Note: 1. Antenna Gain=0 dBi (Numeric 25.12),  $\pi=3.141$ .  
2. The power comes from turn up power which was provided by customer.  
3. The minimum separation distance of the device is greater than 20 cm.  
4. Calculate by WORST-CASE mode.

---

**END OF REPORT**