



**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**FLEX3.0**

**MODEL NUMBER: SC-6141**

**FCC ID: 2ASK3SC-6141T**

**REPORT NUMBER: 4789984716.2-2**

**ISSUE DATE: June 29, 2021**

*Prepared for*

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET  
MONGKOK KOWLOON HONG KONG**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	06/29/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	20dB Bandwidth	CFR 47 FCC §15.215 (c)	Pass
2	Radiated Emission	CFR 47 FCC §15.249 (a)(d)(e) CFR 47 FCC §15.205 and §15.209	Pass
3	Conducted Emission Test For AC Power Port	FCC Part 15.207	Note Applicable (Note 3)
4	Antenna Requirement	CFR 47 FCC §15.203	Pass

Note 1: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

Note 2: The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied.

Note 3: The EUT is power by battery and can't be charged.



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>8</i>
5.2. <i>MAXIMUM FIELD STRENGTH.....</i>	<i>8</i>
5.3. <i>CHANNEL LIST.....</i>	<i>8</i>
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>8</i>
5.5. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.6. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>9</i>
5.7. <i>TEST ENVIRONMENT .....</i>	<i>9</i>
5.8. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>10</i>
5.9. <i>MEASURING INSTRUMENT AND SOFTWARE USED.....</i>	<i>11</i>
<b>6. ANTENNA PORT TEST RESULTS.....</b>	<b>12</b>
6.1. <i>ON TIME AND DUTY CYCLE.....</i>	<i>12</i>
6.2. <i>20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH .....</i>	<i>14</i>
<b>7. RADIATED TEST RESULTS.....</b>	<b>18</b>
7.1. <i>LIMITS AND PROCEDURE .....</i>	<i>18</i>
7.2. <i>RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS</i> <i>24</i>	
7.3. <i>SPURIOUS EMISSIONS (1 ~ 3 GHz).....</i>	<i>30</i>
7.4. <i>SPURIOUS EMISSIONS (3 ~ 18 GHz).....</i>	<i>36</i>
7.5. <i>SPURIOUS EMISSIONS (18 ~ 26 GHz).....</i>	<i>42</i>
7.6. <i>SPURIOUS EMISSIONS BELOW 30 MHz .....</i>	<i>44</i>
7.7. <i>SPURIOUS EMISSIONS BELOW 1 GHz AND ABOVE 30 MHz.....</i>	<i>47</i>
<b>8. ANTENNA REQUIREMENTS.....</b>	<b>49</b>



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG.

## Manufacturer Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD.  
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L  
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG.

## EUT Information

EUT Name: FLEX3.0  
Model: SC-6141  
Sample ID: 3995365  
Sample Received Date: June 11, 2021  
Sample Status: Normal  
Date of Tested: June 11, 2021 ~ June 24, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Checked By:

Denny Huang  
Project Engineer

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

### Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test (include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	5.78dB (1GHz-18GHz)
	5.23dB (18GHz-26GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	FLEX3.0		
Model	SC-6141		
Product Description	Operation Frequency	2451 MHz ~ 2479 MHz	
	Modulation Type	GFSK	
Battery	DC 6.0 V		

### 5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Channel Number	Max Peak field strength (dB $\mu$ V/m)
2463	4[8]	85.90

### 5.3. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2451	3	2459	5	2467	7	2475
2	2455	4	2463	6	2471	8	2479

### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2451 ~ 2479	Wire Antenna	0

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.



**5.5. TEST CHANNEL CONFIGURATION**

Test Mode	Test Channel	Frequency
GFSK	CH 1, CH 4, CH 8	2451 MHz, 2463 MHz, 2479 MHz

**5.6. THE WORSE CASE POWER SETTING PARAMETER**

The Worst Case Power Setting Parameter under 2451 MHz ~ 2479 MHz Band				
Test Software Version		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 1	CH 4	CH 8
GFSK	1	Default	Default	Default

**5.7. TEST ENVIRONMENT**

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65 %	
Atmospheric Pressure:	1025 Pa	
Temperature	TN	22 ~ 28 °C
Voltage:	VL	/
	VN	DC 6.0 V
	VH	/

Note: VL= Lower Extreme Test Voltage  
 VN= Nominal Voltage  
 VH= Upper Extreme Test Voltage  
 TN= Normal Temperature

## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
/	/	/	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
/	/	/	/	/	/

The EUT have the engineer mode inside.

### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

### TEST SETUP

The EUT have the engineer mode inside.

### SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.

**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Nov. 12, 2020	Nov. 11, 2021
Software					
Description		Manufacturer	Name	Version	
Test Software for Radiated Emissions		Farad	EZ-EMC	Ver. UL-3A1	

## 6. ANTENNA PORT TEST RESULTS

### 6.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	24.3 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6.0 V


#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)
GFSK	4.48	100	0.0448	4.48	-26.97

Note: Duty Cycle Correction Factor=20log(x).  
Where: x is Duty Cycle




### ON TIME AND DUTY CYCLE MID CH PLOT



Date: 16 JUN 2021 22:44:07

### ON TIME AND DUTY CYCLE MID CH PLOT-2



Date: 16 JUN 2021 22:44:57

Note: All the modes had been tested, but only the worst duty cycle recorded in the report.

## 6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.249) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.215 (c)	20dB Bandwidth	for reporting purposes only	2400-2483.5
ISED RSS-Gen Clause 6.7 Issue 5	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	24.3 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6.0 V



**RESULTS**


Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2451	0.8072	1.4046	PASS

**20 dB BANDWIDTH LOW CH**



Date: 16 JUN 2021 22:26:43

**99% OCCUPIED BANDWIDTH LOW CH**




Date: 16 JUN 2021 22:25:48




Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2463	0.7892	1.3546	PASS

### 20 dB BANDWIDTH MID CH



Date: 16 JUN 2021 22:43:26

### 99% OCCUPIED BANDWIDTH MID CH




Date: 16 JUN 2021 22:41:09






Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2479	0.8771	1.0789	PASS

### 20 dB BANDWIDTH HIG CH



Date: 16 JUN 2021 23:00:36

### 99% OCCUPIED BANDWIDTH HIG CH



Date: 16 JUN 2021 22:59:49



## 7. RADIATED TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMITS

CFR 47 FCC §15.205 and §15.209

CFR 47 FCC §15.249 (a)(d)(c)(e)

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30




FCC Restricted bands of operation:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.<sup>2</sup>Above 38.6c

**TEST SETUP AND PROCEDURE**

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open field site. Therefore, the sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1 GHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured

Above 1 GHz



The setting of the spectrum analyser. (For Bandedge and Field strength)

RBW	$\geq$ OBW (2 MHz)
VBW	PEAK: $\geq 3 \times$ RBW AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

The setting of the spectrum analyser. (For Spurious emissions)


RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 5
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter or band reject filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 150cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements. Where necessary, average emission are determined by applying the Duty Cycle Correction Factor to the peak measurements. For the Duty Cycle and Correction Factor please refer to clause 6.1. ON TIME AND DUTY CYCLE.

6. For measurements Bandedge above 1 GHz, the resolution bandwidth is set to 2 MHz, then the video bandwidth is set to  $\geq 3 \times \text{RBW}$  for peak measurements. This test results are worse than using 1MHz resolution bandwidth, so if the result is pass, the test is considered to meet the standard requirements.

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


### **TEST ENVIRONMENT**

Temperature	24.3 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6.0 V



## 7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS


### RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400.000	13.83	33.43	47.26	74.00	-26.74	peak
2	2451.085	51.50	33.60	85.10	114.00	-28.90	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400.000	13.32	33.43	46.75	74.00	-27.25	peak
2	2451.085	44.86	33.60	78.46	114.00	-35.54	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.760	52.27	33.63	85.90	114.00	-28.10	peak
2	2483.500	15.09	33.71	48.80	74.00	-25.20	peak
3	2485.800	17.12	33.71	50.83	74.00	-23.17	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.880	43.59	33.63	77.22	114.00	-36.78	peak
2	2483.500	14.48	33.71	48.19	74.00	-25.81	peak
3	2487.640	15.79	33.72	49.51	74.00	-24.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.050	51.36	33.69	85.05	114.00	-28.95	peak
2	2483.500	26.05	33.71	59.76	74.00	-14.24	peak
3	2483.500	-0.92	33.71	32.79	54.00	-21.21	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.050	43.95	33.69	77.64	114.00	-36.36	peak
2	2483.500	19.79	33.71	53.50	74.00	-20.50	peak
3	2483.775	20.26	33.71	53.97	74.00	-20.03	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### 7.3. SPURIOUS EMISSIONS (1 ~ 3 GHz)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	45.95	-13.07	32.88	74.00	-41.12	peak
2	1584.000	45.67	-11.66	34.01	74.00	-39.99	peak
3	1740.000	45.63	-10.51	35.12	74.00	-38.88	peak
4	1906.000	44.80	-10.13	34.67	74.00	-39.33	peak
5	2150.000	45.62	-9.34	36.28	74.00	-37.72	peak
6	2758.000	43.90	-6.82	37.08	74.00	-36.92	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1122.000	45.87	-13.38	32.49	74.00	-41.51	peak
2	1584.000	48.29	-11.66	36.63	74.00	-37.37	peak
3	1802.000	44.88	-10.05	34.83	74.00	-39.17	peak
4	2064.000	44.86	-9.82	35.04	74.00	-38.96	peak
5	2144.000	44.41	-9.37	35.04	74.00	-38.96	peak
6	2760.000	43.83	-6.81	37.02	74.00	-36.98	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1178.000	45.66	-13.10	32.56	74.00	-41.44	peak
2	1290.000	46.01	-12.86	33.15	74.00	-40.85	peak
3	1652.000	45.58	-11.16	34.42	74.00	-39.58	peak
4	1808.000	45.42	-10.05	35.37	74.00	-38.63	peak
5	2463.000	49.38	-8.29	41.09	/	/	fundamental
6	2764.000	43.54	-6.79	36.75	74.00	-37.25	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1190.000	45.64	-13.04	32.60	74.00	-41.40	peak
2	1584.000	48.65	-11.66	36.99	74.00	-37.01	peak
3	1816.000	45.00	-10.06	34.94	74.00	-39.06	peak
4	1998.000	45.20	-10.19	35.01	74.00	-38.99	peak
5	2266.000	44.29	-8.83	35.46	74.00	-38.54	peak
6	2766.000	43.76	-6.77	36.99	74.00	-37.01	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1100.000	46.38	-13.49	32.89	74.00	-41.11	peak
2	1470.000	45.27	-12.37	32.90	74.00	-41.10	peak
3	1816.000	45.41	-10.06	35.35	74.00	-38.65	peak
4	2062.000	45.28	-9.84	35.44	74.00	-38.56	peak
5	2479.000	50.21	-8.26	41.95	/	/	fundamental
6	2684.000	44.70	-7.31	37.39	74.00	-36.61	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1260.000	45.88	-12.90	32.98	74.00	-41.02	peak
2	1584.000	48.40	-11.66	36.74	74.00	-37.26	peak
3	1730.000	45.81	-10.58	35.23	74.00	-38.77	peak
4	2146.000	44.59	-9.36	35.23	74.00	-38.77	peak
5	2479.000	44.94	-8.26	36.68	/	/	fundamental
6	2782.000	43.35	-6.67	36.68	74.00	-37.32	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 7.4. SPURIOUS EMISSIONS (3 ~ 18 GHz)

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4902.000	57.47	1.30	58.77	74.00	-15.23	peak
2	4902.000	30.50	1.30	31.80	54.00	-22.20	AVG
3	7350.000	42.16	7.53	49.69	74.00	-24.31	peak
4	11730.000	35.01	15.32	50.33	74.00	-23.67	peak
5	12285.000	34.85	16.08	50.93	74.00	-23.07	peak
6	13935.000	32.95	17.58	50.53	74.00	-23.47	peak
7	16920.000	30.32	21.51	51.83	74.00	-22.17	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. The High Pass filter loss factor already add into the correct factor.
  5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4902.000	52.77	1.30	54.07	74.00	-19.93	peak
2	4902.000	25.80	1.30	27.10	54.00	-26.90	AVG
3	9315.000	37.21	10.48	47.69	74.00	-26.31	peak
4	11730.000	35.40	15.32	50.72	74.00	-23.28	peak
5	13470.000	33.73	17.15	50.88	74.00	-23.12	peak
6	17025.000	30.09	21.40	51.49	74.00	-22.51	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4926.000	57.68	1.51	59.19	74.00	-14.81	peak
2	4926.000	30.71	1.51	32.22	54.00	-21.78	AVG
3	7380.000	39.08	7.79	46.87	74.00	-27.13	peak
4	7845.000	38.56	9.14	47.70	74.00	-26.30	peak
5	11820.000	35.55	15.29	50.84	74.00	-23.16	peak
6	13965.000	33.03	17.62	50.65	74.00	-23.35	peak
7	17265.000	29.25	22.39	51.64	74.00	-22.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4926.000	56.21	1.51	57.72	74.00	-16.28	peak
2	4926.000	29.24	1.51	30.75	54.00	-23.25	AVG
3	8115.000	37.25	10.13	47.38	74.00	-26.62	peak
4	11730.000	35.50	15.32	50.82	74.00	-23.18	peak
5	14805.000	33.09	18.00	51.09	74.00	-22.91	peak
6	16455.000	31.60	19.68	51.28	74.00	-22.72	peak
7	17625.000	28.46	22.92	51.38	74.00	-22.62	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4958.000	58.19	1.79	59.98	74.00	-14.02	peak
2	4958.000	31.22	1.79	33.01	54.00	-20.99	AVG
3	7440.000	40.99	8.13	49.12	74.00	-24.88	peak
4	7815.000	38.79	9.28	48.07	74.00	-25.93	peak
5	11355.000	36.66	14.34	51.00	74.00	-23.00	peak
6	14820.000	32.93	17.91	50.84	74.00	-23.16	peak
7	16425.000	30.85	19.68	50.53	74.00	-23.47	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4958.000	55.24	1.79	57.03	74.00	-16.97	peak
2	4958.000	28.27	1.79	30.06	54.00	-23.94	AVG
3	7440.000	39.36	8.13	47.49	74.00	-26.51	peak
4	8220.000	38.03	9.79	47.82	74.00	-26.18	peak
5	11730.000	35.53	15.32	50.85	74.00	-23.15	peak
6	14805.000	33.84	18.00	51.84	74.00	-22.16	peak
7	17190.000	29.72	21.98	51.70	74.00	-22.30	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Cycle Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.


## 7.5. SPURIOUS EMISSIONS (18 ~ 26 GHz)

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	50.27	-5.48	44.79	74.00	-29.21	peak
2	20000.000	50.81	-5.45	45.36	74.00	-28.64	peak
3	20560.000	50.23	-5.30	44.93	74.00	-29.07	peak
4	21600.000	50.02	-4.54	45.48	74.00	-28.52	peak
5	23064.000	48.99	-3.42	45.57	74.00	-28.43	peak
6	25616.000	46.18	-1.24	44.94	74.00	-29.06	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18112.000	50.46	-5.47	44.99	74.00	-29.01	peak
2	18528.000	50.61	-5.26	45.35	74.00	-28.65	peak
3	19784.000	50.57	-5.28	45.29	74.00	-28.71	peak
4	21560.000	49.99	-4.60	45.39	74.00	-28.61	peak
5	22792.000	48.61	-3.65	44.96	74.00	-29.04	peak
6	25704.000	47.04	-0.83	46.21	74.00	-27.79	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

Note: All test modes had been tested, only the worst data record in the report.

## 7.6. SPURIOUS EMISSIONS BELOW 30 MHz

### SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz ~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	75.22	-101.40	-26.18	47.60	-73.78	peak
2	0.0187	68.70	-101.35	-32.65	42.16	-74.81	peak
3	0.0206	68.42	-101.35	-32.93	41.32	-74.25	peak
4	0.0279	66.17	-101.38	-35.21	38.69	-73.90	peak
5	0.0316	64.74	-101.40	-36.66	37.61	-74.27	peak
6	0.0432	62.07	-101.45	-39.38	34.89	-74.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**150 kHz ~ 490 kHz**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	75.27	-101.65	-26.38	23.77	-50.15	peak
2	0.1720	71.69	-101.67	-29.98	22.90	-52.88	peak
3	0.2053	66.29	-101.73	-35.44	21.35	-56.79	peak
4	0.2442	65.03	-101.79	-36.76	19.85	-56.61	peak
5	0.3163	62.20	-101.87	-39.67	17.60	-57.27	peak
6	0.3662	59.08	-101.93	-42.85	16.33	-59.18	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

**490 kHz ~ 30 MHz**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	64.44	-62.07	2.37	33.56	-31.19	peak
2	0.8296	63.44	-62.17	1.27	29.23	-27.96	peak
3	1.5564	58.18	-62.02	-3.84	23.76	-27.60	peak
4	5.2705	54.54	-61.45	-6.91	29.54	-36.45	peak
5	10.7299	53.98	-60.83	-6.85	29.54	-36.39	peak
6	16.3959	53.67	-60.96	-7.29	29.54	-36.83	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.


3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All test modes had been tested, only the worst data record in the report.




## 7.7. SPURIOUS EMISSIONS BELOW 1 GHz AND ABOVE 30 MHz

### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	58.1300	36.21	-20.55	15.66	40.00	-24.34	QP
2	71.7100	34.27	-20.70	13.57	40.00	-26.43	QP
3	213.3300	33.79	-17.58	16.21	43.50	-27.29	QP
4	228.8500	35.24	-18.61	16.63	46.00	-29.37	QP
5	247.2800	34.84	-18.99	15.85	46.00	-30.15	QP
6	349.1300	28.75	-14.33	14.42	46.00	-31.58	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	30.92	-18.94	11.98	40.00	-28.02	QP
2	107.6000	32.48	-20.58	11.90	43.50	-31.60	QP
3	213.3300	33.90	-17.58	16.32	43.50	-27.18	QP
4	227.8800	31.90	-18.55	13.35	46.00	-32.65	QP
5	630.4300	26.78	-9.15	17.63	46.00	-28.37	QP
6	953.4400	26.80	-4.45	22.35	46.00	-23.65	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All test modes had been tested, only the worst data record in the report.





## 8. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

---

**END OF REPORT**