

# Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-7426/18-08-04 MPE (FCC)

Certification numbers and labeling requirements	
Kind of test item:	77GHz Radar for Autonomous Drive Applications
Model name:	HiRes 6455
FCC ID	2ASKB-HIRES55

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

## Document authorised:

Alexander Hnatovskiy  
Lab Manager  
Radio Communications & EMC

Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. power [dBm]		Antenna gain max.: [dBi] *	EIRP declared by customer
	conducted	EIRP		
77 GHz Radar	typ. 10.0 max. 15.0	typ. 23.0 max. 30.0	15 dBi	23 to 30 dBm

)\* worst case of all antenna types, channels and modulations (overrated)

**Prediction of MPE limit at given distance - FCC**

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density  
 P = Power input to the antenna  
 G = Antenna gain  
 R = Distance to the center of radiation of the antenna  
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

**Prediction: worst case**

Technologies:	SRR	
Frequency (MHz)	77000	
PG Declared max power (EIRP)	30	dBm
R Distance	20	cm
S MPE limit for uncontrolled exposure	1	mW/cm <sup>2</sup>
<b>Calculated Power density:</b>	0.1990	mW/cm <sup>2</sup>
<b>Calculated percentage of Limit:</b>	19.90%	

**This prediction demonstrates the following:**

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.