

CAUTION



Do not use this product if there is any damage to the unit.

Risk of electric shock.

Do not remove cover or attempt to open the enclosure.

No user serviceable parts inside.

Refer Servicing to qualified service personnel.

WARNING

Risk of explosion.

This equipment has arcing or sparking parts that should not be exposed to flammable vapors.

This equipment should be located at least 460 mm (18 inches) above the floor.

Product: eBox professional

Material number: 10287488

GTIN: 40 62018 00034 8

Serial number: A1234BZ

Charge port number: LP 00000-1

Date of production: 01/21/2019

Electrical phases:

WYE / split phase /

delta center tap

Input voltage: 208/240VAC 60Hz

Output voltage: 208/240VAC 60Hz

Input/output current: up to 50A~

Input/output power: up to 12 kW

Outlet:

type-1/connector

(SAE J1772™, 24.6 ft)

Protection class: class I

Dimensions: 17.7 x 7.1 x 6.7 in.

Operating temperature: -22 - +122°F

Mass: 6 kg

Type: 3S

Impact protection: IK10

Contains FCC ID: UXS-SMR-3X4 and
QIPELS61-US

FCC ID: 2ASKCACCU205



Manufacturer

Broadband TelCom Power, Inc.

1719 S. Grand Ave.

Santa Ana, CA 92705

USA

BTC POWER

For use with electric vehicles.

Ventilation Not Required.

