CAUTION



Do not use this product if there is any damage to the unit

Risk of electric shock. Do not remove cover or attempt to open the enclosure No user serviceable parts inside. Refer Servicing to qualified service

oersonnel. WARNING

Risk of explosion. This equipment has arcing or sparking parts that should not be exposed to

flammable vapors. This equipment should be located at least 460 mm (18 inches) above the

Product: eBox touch

Material number: 10287476 GTIN: 40 62018 00035 5

Serial number: A1234BZ Charge port number: LP 00000-1 Date of production: 01/21/2019

Electrical phases: 3-p WYE / split phase or

delta center tap

Input voltage: 208/240VAC 60Hz Output voltage: 208/240VAC 60Hz Input/output current: up to 50A Input/output power: up to 12 kW

type-1/connector (SAE J1772™,24.6 ft) Protection class: class I Dimensions: 17.7 x 7.1 x 6.7 in.

Outlet:

Operating temperature: -22 - +122°F Mass: 6 kg Type: 3S Impact protection: IK10

Contains FCC ID: UXS-SMR-3X4 and QIPELS61-US

FCC ID: 2ASKCACCU205



Broadband TelCom Power, Inc. 1719 S. Grand Ave

Santa Ana, CA 92705

USA **BTC POWER**

For use with electic vehicles. Ventilation Not Required.

