



Maximum Permissible Exposure Report

1. Product Information

EUT : Dagger QG and Dagger QG Slim
Test Model : 4-8470-10
Additional Model No. : 4-8490-17, 4-8490-10
Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply : Input: DC 12V
DC 3.6V by Battery, 5Ah
Hardware Version : 1.3.0
Software Version : APP: 2.10.53_B4
BLE: 1.0.6_B13
BIN: 5.5.9

Bluetooth :

Frequency Range : 2402MHz ~ 2480MHz
Channel Number : 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing : 2MHz for Bluetooth V5.0 (DTS)
Modulation Type : GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version : V5.0
Antenna Description : Chip Antenna, 3.6dBi(Max.)

LTE Cat M1 :

Support Band : E-UTRA Band 2(U.S.-Band)
E-UTRA Band 4(U.S.-Band)
E-UTRA Band 5(U.S.-Band)
E-UTRA Band 12(U.S.-Band)
E-UTRA Band 13(U.S.-Band)
E-UTRA Band 25(U.S.-Band)
E-UTRA Band 26(U.S.-Band)

LTE Release Version : R14

Type Of Modulation : QPSK/16QAM

Antenna Description : Internal Antenna
3.0dBi (max.) For E-UTRA Band 2
3.0dBi (max.) For E-UTRA Band 4
3.0dBi (max.) For E-UTRA Band 5
3.0dBi (max.) For E-UTRA Band 12
3.0dBi (max.) For E-UTRA Band 13
3.0dBi (max.) For E-UTRA Band 25
3.0dBi (max.) For E-UTRA Band 26



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Power Class : Class 3
GPS function : Support and only RX
Extreme temp. : -30°C to +50°C
Tolerance
Extreme vol. Limits : 3.1VDC to 4.2VDC (nominal: 3.6VDC)
Exposure category : General population/uncontrolled environment
EUT Type : Production Unit
Device Type : Mobile Device





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Chip Antenna	2400 MHz – 2500 MHz	3.6 dBi	BLE ANT
Internal Antenna	600 MHz – 3000 MHz	3.0 dBi	LTE M1 ANT

6. Conducted Power

< BT LE Max Conducted Power >

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
GFSK	0	2402	0.73
	19	2440	0.9
	39	2480	0.41

[LTE M1 Max Average Power]

BAND	Max Average Power (dBm)
LTE Band 2	22.93
LTE Band 4	23.68
LTE Band 5	20.85
LTE Band 12	21.08
LTE Band 13	21.53
LTE Band 25	21.38
LTE Band 26 (814-824MHz)	21.36
LTE Band 26 (824-849MHz)	21.19





7. Manufacturing Tolerance

<BT LE>

GFSK (Peak)

Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance ±(dB)	1.0	1.0	1.0

<LTE Max Average Power>

BAND	Max Average Power (dBm)	Max. Tune Up Power (dBm)
LTE Band 2	22.93	22.0±1.0
LTE Band 4	23.68	23.0±1.0
LTE Band 5	20.85	20.0±1.0
LTE Band 12	21.08	21.0±1.0
LTE Band 13	21.53	21.0±1.0
LTE Band 25	21.38	21.0±1.0
LTE Band 26 (814-824MHz)	21.36	21.0±1.0
LTE Band 26 (824-849MHz)	21.19	21.0±1.0





8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BLE	1	1.26	3.6	2.3	0.0006	1.0
LTE Band 2	23	199.53	3.0	2.0	0.0792	1.0
LTE Band 4	24	251.19	3.0	2.0	0.0997	1.0
LTE Band 5	21	125.89	3.0	2.0	0.0500	0.55
LTE Band 12	22	158.49	3.0	2.0	0.0629	0.47
LTE Band 13	22	158.49	3.0	2.0	0.0629	0.52
LTE Band 25	22	158.49	3.0	2.0	0.0629	1.0
LTE Band 26 (814-824MHz)	22	158.49	3.0	2.0	0.0629	0.54
LTE Band 26 (824-849MHz)	22	158.49	3.0	2.0	0.0629	0.55

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;
3. We choose the lowest frequency operate to calculate MPE limit as higher frequency will have higher MPE limits.
4. $MPE\ values = PG/4\pi R^2$

8.2 Simultaneous Transmission MPE

The sample support one BLE antenna and another one LTE transmit antenna, so need consider simultaneous transmission;
 According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 \sum of MPE ratios ≤ 1.0

Mode	\sum MPE max ratios	Limit	Results
BLE<E	0.1	1.0	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

