



# TEST REPORT



Report No. : KES-RF240184  
Page 1 / 87

**KES Co., Ltd.**  
#3002, #3503, #3701, 40, Simin-daero365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057,  
Republic of Korea  
Tel : +82-31-425-6200, Fax : +82-31-425-6200

## ■ FCC/IC TEST REPORT

### 1. Client

- Name : DeepScent Inc.
- Address : 34134 99, Daehak-ro, Yuseong-gu, Daejeon, Republic of Korea

### 2. Sample Description

- Product item : DEEPSCENT LOUNGE
- Model name : DS08\_019220001
- Manufacturer etc. : DeepScent Inc.

3. Date of test : 2024.03.27 ~ 2024.04.11

4. Location of Test :  Permanent Testing Lab       On Site Testing

- Adress : 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

5. Test method used : Part 15.247 & RSS-247

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This laboratory is not accredited for the test results marked\*.  
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : Bong-Seok Kim                      (Signature)	Name : Yeong-Jun Cho                      (Signature)

2024. 04. 30.

## KES Co., Ltd.

### Accredited by KOLAS, Republic of KOREA



## REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2024.04.30.	KES-RF240184	Initial

*This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.*

### Use of uncertainty of measurement for decisions on conformity (decision rule):

- No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").
- Other (to be specified, for example when required by the standard or client)



## TABLE OF CONTENTS

1.	General information .....	4
1.1.	EUT description .....	4
1.2.	Test configuration.....	5
1.3.	Information about derivative model .....	5
1.4.	Accessory information .....	5
1.5.	Sample calculation .....	5
1.6.	Measurement Uncertainty .....	5
1.7.	Frequency/channel operations .....	6
2.	Summary of tests .....	7
3.	Test results .....	8
3.1.	99% Occupied Bandwidth .....	8
3.2.	6 dB bandwidth .....	14
3.3.	Output power .....	20
3.4.	Power spectral density .....	22
3.5.	Radiated restricted band and emissions .....	28
3.6.	Conducted spurious emissions & band edge .....	70
3.7.	AC conducted emissions .....	82
3.8.	Antenna Requirement.....	86
Appendix A.	Measurement equipment.....	87



## 1. General information

Applicant DeepScent Inc.  
Applicant address 34134 99, Daehak-ro, Yuseong-gu, Daejeon, Republic of Korea  
Test site KES Co., Ltd.  
Test site address  #3002, #3503, #3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea  
 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea  
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148  
Standard(s) Part 15.247  
IC rule part(s): IC : RSS-247  
FCC ID: 2ASKL-DS08  
IC ID: 31697-DSL2401  
Test device serial No.  Production  Pre-production  Engineering

### 1.1. EUT description

Equipment under test DEEPSCENT LOUNGE  
Frequency range 2 402 MHz ~ 2 480 MHz (BDR, EDR)  
**2 402 MHz ~ 2 480 MHz (LE 1 Mbps)**  
**2 412 MHz ~ 2 462 MHz (802.11b,g,n\_HT20)**  
**2 422 MHz ~ 2 452 MHz (802.11n\_HT40)**  
13.562 MHz (NFC)  
Model DS08\_019220001  
Variant Model: -  
Modulation technique **GFSK,  $\pi/4$ DQPSK, 8DPSK, DSSS, OFDM, ASK**  
Number of channels 2 402 MHz ~ 2 480 MHz (BDR, EDR) : 79 ch  
**2 402 MHz ~ 2 480 MHz (LE 1 Mbps) : 40 ch**  
**2 412 MHz ~ 2 462 MHz (802.11b,g,n\_HT20) : 11 ch**  
2 422 MHz ~ 2 452 MHz (802.11n\_HT40) : 7 ch  
13.562 MHz (NFC) : 1 ch  
Antenna specification BDR/EDR : PCB Antenna // Peak gain: 3.40 dBi  
**LE 1 Mbps : PCB Antenna // Peak gain: 3.40 dBi**  
**WLAN 2.4 GHz : PCB Antenna // Peak gain: 3.40 dBi**  
NFC : Loop Antenna  
Power source AC 120 V(Adapter Output DC 5 V)  
H/W Version V2.x  
S/W Version V2.x

**1.2. Test configuration**

The **DeepScent Inc. // DEEPSCENT LOUNGE // DS08\_019220001 // FCC ID: 2ASKL-DS08 // IC ID: 31697-DSL2401** was tested according to the specification of EUT, the EUT must comply with following standards

FCC Part 15.247  
ISED RSS-247 Issue 3 and RSS-Gen Issue 5  
KDB 558074 D01 v05 r02  
ANSI C63.10-2013

**1.3. Information about derivative model**

N/A

**1.4. Accessory information**

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

**1.5. Sample calculation**

Where relevant, the following sample calculation is provided  
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 0.72 + 10 = 10.72 \text{ (dB)} \end{aligned}$$

For Radiation test :

$$\text{Field strength level (dB}\mu\text{V/m)} = \text{Measured level (dB}\mu\text{V)} + \text{Antenna factor (dB)} + \text{Cable loss (dB)} - \text{Amplifier gain (dB)}$$

**1.6. Measurement Uncertainty**

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.22 dB ( SHIELD ROOM #6 )
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1GHz	4.04 dB ( SAC #6 )
	Above 1GHz	5.32 dB ( SAC #5 )
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		



**1.7. Frequency/channel operations**

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
40	2 442	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
78	2 480	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps

Ch.	Frequency (MHz)	Rate(Mbps)
<b>00</b>	<b>2 402</b>	<b>LE 1 Mbps</b>
.	.	.
<b>20</b>	<b>2 442</b>	<b>LE 1 Mbps</b>
.	.	.
<b>39</b>	<b>2 480</b>	<b>LE 1 Mbps</b>

Ch.	Frequency (MHz)	Rate(Mbps)
<b>01</b>	<b>2 402</b>	<b>802.11b(1 Mbps) 802.11g (6 Mbps) 802.11n_HT20(MCS0)</b>
.	.	.
<b>06</b>	<b>2 437</b>	<b>802.11b(1 Mbps) 802.11g (6 Mbps) 802.11n_HT20(MCS0)</b>
.	.	.
<b>11</b>	<b>2 462</b>	<b>802.11b(1 Mbps) 802.11g (6 Mbps) 802.11n_HT20(MCS0)</b>

Ch.	Frequency (MHz)	Rate(Mbps)
03	2 422	802.11n_HT40(MCS0)
.	.	.
06	2 437	802.11n_HT40(MCS0)
.	.	.
09	2 452	802.11n_HT40(MCS0)

Ch.	Frequency (MHz)	Rate(Mbps)
01	13.562	NFC

**2. Summary of tests**

Section in FCC Part 15	Section in RSS-247 & Gen	Test description	Test results
-	RSS-Gen 6.7	99% Occupied bandwidth	Pass
15.247(a)(2)	RSS-247 5.2(a)	6 dB bandwidth	Pass
15.247(b)(3)	RSS-247 5.4(d)	Output power	Pass
15.247(e)	RSS-247 5.2(b)	Power spectral density	Pass
15.205 15.209	RSS-247 5.5 RSS-Gen 8.9,8,10	Radiated restricted band and emission	Pass <sup>note.2</sup>
15.247(d)	RSS-247 5.5	Conducted spurious emission and band edge	Pass
15.207(a)	RSS-Gen 8.8	AC Conducted emissions	Pass <sup>note.2</sup>
15.203	-	Antenna Requirement	Pass <sup>note.1</sup>

**N/T: Not Tested****Note.**

1. Please check the antenna spec. for the Antenna Requirement.
2. Tested each mode and with NFC working simultaneously.
3. Tested is performed with power setting value below :

Mode	Frequency (Mhz)	Setting value
BDR 1 Mbps	2 402 ~ 2 480	8
EDR 2 Mbps		8
EDR 3 Mbps		8
LE 1 Mbps		8
802.11b (1 Mbps)	2 412 ~ 2 462	8
802.11g (6 Mbps)		8
802.11n_HT20 (MCS0)		8
802.11n_HT40 (MCS0)		8
	2 422 ~ 2 452	8




### 3. Test results

#### 3.1. 99% Occupied Bandwidth

##### Test procedure

ANSI C63.10-2013 clause 6.9.2 and 6.9.3

##### Test setup



##### Test setting

1. Span = The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
2. RBW = The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW
3. VBW = shall be approximately three times the RBW
4. Sweep = auto
5. Detector function = Peak
6. Trace = Max hold

##### Limit


None; for reporting purpose only.





**Mode : LE 1Mbps**

Frequency(MHz)	99% occupied bandwidth(MHz)	Limit(MHz)
2 402	1.00	-
2 442	1.00	
2 480	1.01	






Report No. : KES-RF240184

Mode : 802.11b

Frequency(MHz)	99% occupied bandwidth(MHz)	Limit(MHz)
2 412	13.84	-
2 437	13.89	
2 462	13.89	






Report No. : KES-RF240184

Mode : 802.11g

Frequency(MHz)	99% occupied bandwidth(MHz)	Limit(MHz)
2 412	16.90	-
2 437	16.90	
2 462	16.79	






Report No. : KES-RF240184

Mode : 802.11n HT20

Frequency(MHz)	99% occupied bandwidth(MHz)	Limit(MHz)
2 412	17.60	-
2 437	17.54	
2 462	17.48	






Report No. : KES-RF240184

Mode : 802.11n HT40

Frequency(MHz)	99% occupied bandwidth(MHz)	Limit(MHz)
2 422	34.50	-
2 437	34.96	
2 452	34.62	






### 3.2. 6 dB bandwidth

#### Test procedure

ANSI C63.10-2013 - Section 11.8.2

#### Test setup



#### ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

#### FCC Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### IC Limit


According to RSS-247 5.2(a), The minimum 6 dB bandwidth shall be 500 kHz.



Report No. : KES-RF240184

**Test results**  
**Mode : LE 1Mbps**

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 402	0.63	≥ 0.500
2 442	0.64	
2 480	0.64	





Mode : 802.11b

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	9.90	≥ 0.500
2 437	10.01	
2 462	10.01	








Mode : 802.11g


Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	16.51	≥ 0.500
2 437	16.51	
2 462	16.50	





Mode : 802.11n HT20


Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	17.61	≥ 0.500
2 437	17.49	
2 462	17.44	





Mode : 802.11n HT40

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 422	33.57	≥ 0.500
2 437	33.57	
2 452	33.57	






### 3.3. Output power

#### Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

#### Test setup



#### ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

#### ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

#### FCC Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### IC Limit

According to RSS-247 5.4 (d), For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

**Test results**

Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	-1.78	-1.00	0.68	1.36	1.42	1.97

Mode	2 412 MHz		2 437 MHz		2 462 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11b	8.08	11.14	8.95	12.00	9.15	12.14
802.11g	5.95	12.10	7.06	12.93	7.51	13.28
802.11n_HT20	6.13	11.68	7.25	12.56	7.38	12.73

Mode	2 422 MHz		2 437 MHz		2 452 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11n_HT40	6.89	12.44	6.59	12.18	5.92	11.68




### 3.4. Power spectral density

#### Test procedure

ANSI C63.10-2013 - Section 11.10.2

#### Test setup



#### Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- d. Set the VBW  $\geq [3 \times \text{RBW}]$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.
- j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

#### FCCLimit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### IC Limit

According to RSS-247 5.2(b), The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).




Report No. : KES-RF240184

**Results**

**Mode : LE 1 Mbps**


Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 402	-17.15	8
2 442	-15.38	
2 480	-15.46	





**Mode : 802.11b**

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-16.41	8
2 437	-16.49	
2 462	-16.18	








**Mode : 802.11g**

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-21.51	8
2 437	-21.65	
2 462	-21.27	






Report No. : KES-RF240184

**Mode : 802.11n HT20**

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-21.18	8
2 437	-21.26	
2 462	-20.77	






Report No. : KES-RF240184

**Mode : 802.11n HT40**

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 422	-21.97	8
2 437	-22.65	
2 452	-22.64	




Blank




### 3.5. Radiated restricted band and emissions

#### Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.





The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



### Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

#### Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel**.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

#### Test procedure above 30 MHz ~ 1 000 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



**Test procedure above 1 000 MHz**

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  
5. Spectrum analyzer settings for  $f < 1$  GHz:
  - ① Span = wide enough to fully capture the emission being measured
  - ② RBW = 100 kHz
  - ③ VBW  $\geq$  RBW
  - ④ Detector = quasi peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
6. Spectrum analyzer settings for  $f \geq 1$  GHz: Peak
  - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
  - ② RBW = 1 MHz
  - ③ VBW  $\geq$  3 MHz
  - ④ Detector = peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
  - ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for  $f \geq 1$  GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW  $\geq 3 \times$  RBW
- ④ Detector = RMS, if span/(# of points in sweep)  $\leq$  (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is  $10 \log(1/x)$ , where x is the duty cycle.
  - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is  $20 \log(1/x)$ , where x is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq 98$  percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40 \log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20 \log(D_m/D_s)$   
 Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Field strength(dB $\mu$ V/m) = Level(dB $\mu$ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB $\mu$ V/m) - Field strength(dB $\mu$ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

**FCC Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated ( $\mu$ V/m)
0.009 ~ 0.490	300	2 400/F(kHz)
0.490 ~ 1.705	30	24 000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.



**IC Limit**

According to RSS-Gen, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5 – General field strength limits at frequencies above 30 MHz**

Frequency (MHz)	Field strength ( $\mu\text{V}/\text{m}$ at 3 m)
30 ~ 88	100
88 ~ 216	150
216 ~ 960	200
Above 960*	500

**Table 6 – General field strength limits at frequencies below 30 MHz**

Frequency	Magnetic field strength (H-Field) ( $\mu\text{A}/\text{m}$ )	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

**Duty cycle**


Regarding to KDB 558074 D01\_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T <sub>on</sub> time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1Mbps	2.13	2.51	0.85	84.86	0.71
802.11b	100	100	1.00	100	0.00
802.11g	100	100	1.00	100	0.00
802.11n_HT20	100	100	1.00	100	0.00
802.11n_HT40	100	100	1.00	100	0.00

Duty cycle (Linear) = T<sub>on</sub> time/Period


DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)






**Test results (Below 30 MHz)**

Mode: LE 1 Mbps  
 Distance of measurement: 3 meter  
 Channel: 39 (Worst case)






Mode: 802.11g (Worst Case)  
 Distance of measurement: 3 meter  
 Channel: 11 (Worst case)





Test results (Below 1 000 MHz)

Mode: LE 1 Mbps  
 Distance of measurement: 3 meter  
 Channel: 39 (Worst case)




Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB (μV)]	c.f [dB (1/m)]	Result QP [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	41.883	V	41.0	-12.6	28.4	40.0	11.6	100.0	337.3	
2	143.975	H	42.3	-16.1	26.2	43.5	17.3	233.0	226.3	
3	215.876	V	41.3	-12.1	29.2	43.5	14.3	177.0	271.0	
4	218.423	H	49.8	-12.0	37.8	46.0	8.2	274.0	243.2	
5	229.456	V	43.6	-11.7	31.9	46.0	14.1	167.0	242.3	
6	233.700	H	48.7	-11.6	37.1	46.0	8.9	266.0	243.2	
7	244.249	H	46.0	-11.2	34.8	46.0	11.2	271.0	265.3	
8	245.461	V	45.6	-11.2	34.4	46.0	11.6	137.0	359.9	
9	258.071	V	41.0	-10.9	30.1	46.0	15.9	127.0	264.0	
10	275.168	H	43.2	-10.6	32.6	46.0	13.4	208.0	221.4	
11	360.043	H	43.9	-8.1	35.8	46.0	10.2	301.0	198.7	
12	640.009	V	35.9	-3.1	32.8	46.0	13.2	144.0	53.4	



Report No. : KES-RF240184

Mode: 802.11g (Worst Case)  
 Distance of measurement: 3 meter  
 Channel: 11 (Worst case)



Final Result

No.	Frequency [MHz]	Pol	Reading [dB(μV)]	c.f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [deg]	Remark
1	42.368	V	38.7	-12.5	26.2	40.0	13.8	176.0	354.0	
2	211.754	H	45.9	-12.3	33.6	43.5	9.9	233.0	224.3	
3	215.270	V	41.0	-12.2	28.8	43.5	14.7	178.0	164.1	
4	226.789	V	44.0	-11.8	32.2	46.0	13.8	139.0	205.5	
5	227.153	H	49.8	-11.8	38.0	46.0	8.0	233.0	68.7	
6	243.158	V	44.7	-11.3	33.4	46.0	12.6	187.0	0.7	
7	249.463	H	44.1	-11.1	33.0	46.0	13.0	267.0	315.0	
8	258.799	V	41.7	-10.9	30.8	46.0	15.2	187.0	294.0	
9	264.013	H	42.1	-10.8	31.3	46.0	14.7	289.0	269.0	
10	320.030	H	37.8	-9.4	28.4	46.0	17.6	315.0	183.3	
11	360.043	H	42.1	-8.1	34.0	46.0	12.0	331.0	246.0	
12	640.009	V	35.1	-3.1	32.0	46.0	14.0	137.0	27.5	