

RF EXPOSURE REPORT FOR CERTIFICATION
On Behalf of

SP United China

SPC+ CHARGING PAD

Model Number: 52802

Additional Model: 52803, 52804, 52805, 52807, 52808, 52812

FCC ID: 2ASMH-PCB015-PCB018

Applicant:	SP United China
Address:	No. 3 LANE 19 QIAN RD KENGGOU VILLAGE TINGSHAN DIST
	HOUJIE TOWN DONGGUAN CITY GUANGDONG PROVINCE CHINA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808




Report Number:	ESTE-R2209102
Date of Test:	Aug. 08~Sep. 20, 2022
Date of Report:	Sep. 22, 2022

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
TEST REPORT VERIFICATION.....	3
1. SUMMARY OF TEST	4
1.1. Summary of test result.....	4
1.2. Test Mode.....	4
1.3. Test Equipment List	4
1.4. Difference between Model Numbers.....	4
2. MAXIMUM PERMISSIBLE EXPOSURE	5
2.1. Limit	5
2.2. Test Setup A	5
2.3. Test Procedure	6
2.4. Equipment Approval Considerations	7
2.5. Test Result for Test setup A:	8
3. TEST SETUP PHOTO	9



EST Technology Co., Ltd.

Applicant:	SP United China		
Address:	No. 3 LANE 19 QIAN RD KENGGOU VILLAGE TINGSHAN DIST HOUIE TOWN DONGGUAN CITY GUANGDONG PROVINCE CHINA		
Manufacturer:	SP United China		
Address:	No. 3 LANE 19 QIAN RD KENGGOU VILLAGE TINGSHAN DIST HOUIE TOWN DONGGUAN CITY GUANGDONG PROVINCE CHINA		
Factory:	SP United China		
Address:	No. 3 LANE 19 QIAN RD KENGGOU VILLAGE TINGSHAN DIST HOUIE TOWN DONGGUAN CITY GUANGDONG PROVINCE CHINA		
E.U.T:	SPC+ CHARGING PAD		
Model Number:	52802		
Additional Model:	52803, 52804, 52805, 52807, 52808, 52812 Note: They are identical except model name, product name and appearance.		
Power Supply:	DC 12V From Adapter Input AC 100-240V, 50/60Hz		
Trade Name:	-----	Serial No.:	-----
Date of Receipt:	Aug. 08, 2022	Date of Test:	Aug. 08~Sep. 20, 2022
Test Specification:	FCC CFR 47 Part 1.1307(b)&1.1310 KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC CFR 47 Part 1.1307(b)&1.1310 requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
		Date: Sep. 22, 2022	
Prepared by:	Reviewed by:	Approved by:	
			
Emily Cai / Assistant	Seven Wang / Engineer	Iceman Hu / Manager	
Other Aspects:	None.		
<i>Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.</i>			

1. SUMMARY OF TEST

1.1. Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	Maximum Permissible Exposure	Part 1.1307(b)&1.1310	PASS

1.2. Test Mode

Test Item	Test Mode
Maximum Permissible Exposure	Wireless Charging with Empty Load
	Wireless Charging with Half Load
	Wireless Charging with Full Load
Note: The worst Full Load status is recorded in the report	

1.3. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Electric and Magnetic Field Probe-Analyzer	Narda S.T.S./PMM	EHP-200A	EST-E106	June 13,22	1 Year
Simulated load	/	/	EST-306	N/A	N/A
Simulated load	/	/	EST-307	N/A	N/A
Test Software	Narda	EHP200-TS	Rel 1.92	N/A	N/A

1.4. Difference between Model Numbers

Model No.	Product name
52802	SPC+ CHARGING PAD
52803	SPC+ CHARGING OFFICE STAND
52804	SPC+ CHARGING SUCTION MOUNT
52805	SPC+ CHARGING VENT MOUNT
52812	SPC+ CHARGING CLAMP MOUNT
52807	SPC+ CHARGING MODULE
52808	SPC+ CHARGING ANTI VIBRATION MODULE

2. MAXIMUM PERMISSIBLE EXPOSURE

2.1. Limit


Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Note:

- f = frequency in MHz * = Plane-wave equivalent power density.
- For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

2.2. Test Setup A



2.3. Test Procedure

- a. The test was performed on 360 degree turn table in anechoic chamber.
- b. The probe was placed at 15 cm surrounding the device and 20 cm above the top of the charger and the geometric centre of the probe, for test setup A.
- d. The highest emission level was recorded and compared with limit as soon as measurement of each point; A, B, C, D, E were completed.

2.4. Equipment Approval Considerations

Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance.



1	Power transfer frequency is less than 1 MHz
	YES; the device operated in the frequency range from 111-205KHz.
2	Output power from each primary coil is less than or equal to 15 watts.
	YES; the maximum output power of the primary coil is 15W.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
	YES.
4	Client device is placed directly in contact with the transmitter.
	YES; Client device is placed directly in contact with the transmitter.
5	Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
	YES.
6	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
	YES; The EUT field strength levels are 50% x MPE limits.



2.5. Test Result for Test setup A:

E-Field Test Result				
Test Mode	Test distance(cm)	Full Load	Half Load	Empty Load
Frequency range (kHz)	111 to 205 kHz			
Position A(V/m)	15	5.068	4.137	3.523
Position B(V/m)	15	5.129	4.262	3.487
Position C(V/m)	15	5.314	4.154	3.392
Position D(V/m)	15	5.225	4.209	3.368
Position E(V/m)	20	11.698	9.628	7.521
Limits (V/m)	614			
50% Limits(V/m)	307			

H-Field Test Result				
Test Mode	Test distance(cm)	Full Load	Half Load	Empty Load
Frequency range (kHz)	111 to 205 kHz			
Position A(A/m)	15	0.149	0.131	0.122
Position B(A/m)	15	0.152	0.129	0.123
Position C(A/m)	15	0.141	0.133	0.119
Position D(A/m)	15	0.144	0.130	0.121
Position E(A/m)	20	0.408	0.312	0.267
Limits (A/m)	1.630			
50% Limits (A/m)	0.815			

3. TEST SETUP PHOTO







End of Test Report