



CERTIFICATION TEST REPORT

Report Number. : 12743821-E2V2

Applicant : PI INC
1111 BAYHILL DR
SUITE 235
SAN BRUNO, CA 94066, U.S.A.

Model : SOURCE

FCC ID : 2ASP901EH1

EUT Description : WIRELESS CHARGER

Test Standard(s) : FCC 47 CFR PART 1 SUBPART I
FCC 47 CFR PART 2 SUBPART J

Date Of Issue:
May 17, 2019

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	5/13/2019	Initial Issue	--
V2	5/17/2019	Updated report to address TCB's question	Tina Chu

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. EQUIPMENT UNDER TEST	7
4.1. DESCRIPTION OF EUT	7
4.2. KDB 680106 D01 SECTION 5b EQUIPMENT APPROVAL CONSIDERATIONS.....	7
4.3. DESCRIPTION OF TEST SETUP.....	8
5. TEST AND MEASUREMENT EQUIPMENT	12
6. DUTY CYCLE.....	13
7. MAXIMUM PERMISSIBLE RF EXPOSURE	15
7.1. FCC LIMITS AND SUMMARY	15
7.1.1. FCC LIMITS.....	15
7.1.2. FCC SUMMARY OF RESULTS.....	16
7.2. TEST RESULTS	17
7.2.1. FCC RF EXPOSURE.....	17
8. SETUP PHOTO	19

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: PI INC
1111 BAYHILL DR
SUITE 235
SAN BRUNO, CA 94066, U.S.A.

EUT DESCRIPTION: WIRELESS CHARGER

MODEL NUMBER: SOURCE

SERIAL NUMBER: SNEH119030000044

DATE TESTED: APRIL 24 - 29, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



THU CHAN
OPERATIONS LEAD
UL Verification Services Inc.

Prepared By:



TOM CHEN
TEST ENGINEER
UL Verification Services Inc.

Reviewed By:



TINA CHU
SENIOR PROJECT ENGINEER
UL Verification Services Inc. UL Verification

2. TEST METHODOLOGY

All calculations were made in accordance with FCC KDB 447498 D01 and KDB 447498 D03.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd.
☐ Chamber A (ISED:2324B-1)	☐ Chamber D (ISED:22541-1)	☐ Chamber I (ISED: 2324A-5)
☐ Chamber B (ISED:2324B-2)	☐ Chamber E (ISED:22541-2)	☐ Chamber J (ISED: 2324A-6)
☐ Chamber C (ISED:2324B-3)	☐ Chamber F (ISED:22541-3)	☐ Chamber K (ISED: 2324A-1)
☒ EMC conducted room	☐ Chamber G (ISED:22541-4)	☐ Chamber L (ISED: 2324A-3)
	☐ Chamber H (ISED:22541-5)	

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

4. EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF EUT

The EUT is a Qi compatible wireless charger for cellphone. Up to 4 devices can be charged through wireless charging + 2 High Power USB charging ports. Total 8 coils (4 pairs of Tx/Rx). Operating Frequency = 113kHz-230kHz.

4.2. KDB 680106 D01 SECTION 5b EQUIPMENT APPROVAL CONSIDERATIONS

Requirement	Device
1. Power transfer frequency is less than 1 MHz.	Yes. Operating frequency is 113kHz to 230kHz.
2. Output power from each primary coil is less than or equal to 15 watts.	Yes. The system is designed to deliver 5W to each Wireless Power receiver device placed on the charging surface and input power to each coil will not exceed 9W at any time. Four coils can be active at any given time
3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes. Each receiver device is always powered by a single transmitter coil, so there is always a 1:1 relationship between transmitter and receiver. Please refer to the operation manual for further elaboration on this topic, if necessary.
4. Client device is placed directly in contact with the transmitter.	Yes. Client devices are placed in direct contact (placed on top of) the charger.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. This charger is intended for desktop use and therefore is considered to be a mobile device for the purposes of RF exposure evaluation.
6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes. The magnetic field test result is less than 50% of the MPE limit, which is 36.44%.

4.3. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

SUPPORT EQUIPMENT & PERIPHERALS LIST			
Description	Manufacturer	Model	Serial Number
Phone	Apple	IPHONE 8	F4HWRUMYJC6C
Phone	Apple	IPHONE 8	C8PVJXCLJC6D
Phone	Apple	IPHONE XR	G0NXL08ZKXKT
Phone	Apple	IPHONE XS	DNQ94D9KPFR
AC Adapter	DELTA Electronics	ADP-65DWY	6IEW8CS000L-2C-S0

NOTE: Cell Phones were exchanged to ensure the EUT is at the maximum power transfer during testing.

I/O CABLES

N/A

TEST SETUP

The following configurations are tested:


Configuration	Mode	Descriptions
1	Standby	EUT Alone powered by AC/DC adapter
2 1 cellphone WPT (with gap distance and shift)	Operating (power, <10% Power Charging)	EUT and phone powered by AC/DC adapter
	Operating (power, 20~50% Power Charging)	EUT and phone powered by AC/DC adapter
	Operating (power, >90% Power Charging)	EUT and phone powered by AC/DC adapter
3 2 cellphones WPT (with gap distance and shift)	Operating (power, <10% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, 20~50% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, >90% Power Charging)	EUT and phones powered by AC/DC adapter
4 3 cellphones WPT (with gap distance and shift)	Operating (power, <10% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, 20~50% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, >90% Power Charging)	EUT and phones powered by AC/DC adapter
5 4 cellphones WPT (with gap distance and shift)	Operating (power, <10% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, 20~50% Power Charging)	EUT and phones powered by AC/DC adapter
	Operating (power, >90% Power Charging)	EUT and phones powered by AC/DC adapter

MEASUREMENT SETUP


The measurement was taken using a probe placed 15 cm surrounding the device and 20 cm above the top surface of the EUT. Measurements were taken from the top and all sides of the EUT per KDB680106 D01 v03.

The charger is a desktop device, all the phones charged by the WPT must be at upright position (vertical orientation). Worst case RF exposure configuration was investigated among different coil combinations; with/without USB phones loaded; phones were shifted at various positions/fixed position; with/without gap (either a cellphone case at 3 mm or a cellphone pop socket at 6mm was used to represent the cellphone case). The worst case configuration was EUT without USB phones loaded, phones were shifted away from the charging coil with gap distance from the EUT surface after investigation.

CONFIGURATION 1



CONFIGURATIONS 2&3&4&5



5. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was used for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	Local ID T No.)	Cal Date	Cal Due
Electric and Magnetic Field Probe	Narda	EHP-200A	T1085	10/24/2018	10/24/2019

6. DUTY CYCLE

LIMITS



None; for reporting purposes only.

PROCEDURE

Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
Standby	710.00	2000.00	0.36	35.50%	4.50
Operating	100.00	100.00	1.00	100.00%	0.00



7. MAXIMUM PERMISSIBLE RF EXPOSURE

7.1. FCC LIMITS AND SUMMARY

7.1.1. FCC LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

7.1.2. FCC SUMMARY OF RESULTS

RESULTS

ID:	29435	Date:	4/30/19
------------	-------	--------------	---------

Note: Both magnetic and electric field strengths have been investigated from 9 kHz to 30 MHz at 15cm to find that the EUT operation frequency is at 113 kHz to 230kHz.

FCC RF Exposure Summary of Results

Electric Field Limit			Magnetic Field Limit		
FCC	Maximum RMS (V/m)	Percentage (%)	FCC	Maximum RMS (A/m)	Percentage (%)
614	12.247	1.99%	1.63	0.594	36.44%

7.2. TEST RESULTS

7.2.1. FCC RF EXPOSURE

E- FIELD AND H- FIELD MEASUREMENTS

Note: Peak measurements were performed.

Configuration	Test Mode	Measuring Distance (cm)	Electric Field Limit	Electric Field Reading		Magnetic Field Limit	Magnetic Field	
			(V/m) FCC	Location	Peak	(A/m) FCC	Location	Peak
(1)	Standby	15 cm surrounding the device (S1-S4) and 20 cm above the top surface of the EUT	614	S1	0.855	1.63	S1	0.486
				S2	1.185		S2	0.251
				S3	0.693		S3	0.133
				S4	0.914		S4	0.114
				Top	0.362		Top	0.234
				Max	1.455		Max	0.486
(2) 1 cellphone WPT (with gap distance and shift)	Operating (power < 10% charging)			S1	1.880		S1	0.186
				S2	1.710		S2	0.287
				S3	1.098		S3	0.153
				S4	1.935		S4	0.256
				Top	3.131		Top	0.109
				Max	3.131		Max	0.361
	Operating (power 20%~50% charging)			S1	2.970		S1	0.303
				S2	2.914		S2	0.461
				S3	1.123		S3	0.203
				S4	1.295		S4	0.249
				Top	2.628		Top	0.232
				Max	2.970		Max	0.461
Operating (power > 90% charging)	S1	1.467	S1	0.206				
	S2	1.269	S2	0.219				
	S3	1.284	S3	0.261				
	S4	1.607	S4	0.495				
	Top	1.063	Top	0.165				
	Max	1.955	Max	0.495				
(3) 2 cellphones WPT (with gap distance and shift)	Operating (power < 10% charging)	S1	2.099	S1	0.098			
		S2	2.228	S2	0.314			
		S3	0.639	S3	0.148			
		S4	0.858	S4	0.349			
		Top	1.382	Top	0.138			
		Max	3.492	Max	0.510			
	Operating (power 20%~50% charging)	S1	11.127	S1	0.239			
		S2	5.240	S2	0.445			
		S3	0.974	S3	0.157			
		S4	2.720	S4	0.394			
		Top	10.659	Top	0.155			
		Max	11.127	Max	0.445			
Operating (power > 90% charging)	S1	2.778	S1	0.208				
	S2	2.014	S2	0.455				
	S3	1.272	S3	0.280				
	S4	2.505	S4	0.448				
	Top	2.154	Top	0.198				
	Max	4.027	Max	0.455				
(4) 3 cellphones WPT (with gap distance and shift)	Operating (power < 10% charging)	S1	2.018	S1	0.168			
		S2	1.933	S2	0.321			
		S3	1.984	S3	0.185			
		S4	3.362	S4	0.504			
		Top	1.638	Top	0.215			
		Max	2.069	Max	0.504			
	Operating (power 20%~50% charging)	S1	1.164	S1	0.260			
		S2	2.085	S2	0.391			
		S3	4.639	S3	0.476			
		S4	3.145	S4	0.574			
		Top	2.684	Top	0.149			
		Max	7.612	Max	0.476			
Operating (power > 90% charging)	S1	2.458	S1	0.224				
	S2	2.015	S2	0.411				
	S3	1.676	S3	0.270				
	S4	2.558	S4	0.507				
	Top	2.042	Top	0.156				
	Max	2.558	Max	0.507				
(5) 4 cellphones WPT (with gap distance and shift)	Operating (power < 10% charging)	S1	2.760	S1	0.250			
		S2	2.539	S2	0.380			
		S3	2.387	S3	0.205			
		S4	2.778	S4	0.594			
		Top	3.735	Top	0.178			
		Max	3.735	Max	0.594			
	Operating (power 20%~50% charging)	S1	2.438	S1	0.174			
		S2	4.195	S2	0.549			
		S3	12.247	S3	0.248			
		S4	4.149	S4	0.456			
		Top	2.014	Top	0.361			
		Max	12.247	Max	0.549			
Operating (power > 90% charging)	S1	2.997	S1	0.169				
	S2	2.365	S2	0.446				
	S3	1.959	S3	0.155				
	S4	1.631	S4	0.260				
	Top	1.945	Top	0.138				
	Max	2.997	Max	0.484				