

RF EXPOSURE REPORT

FOR

| | | |
|-----------------------------|---|---|
| Applicant | : | PRAISE PERFECTION LIMITED |
| Address | : | FLAT/RM 4, 7F SHING YIP INDUSTRIAL BUILDING, 19-21 SHING YIP STREET, KWUN TONG, KL., HONG KONG. |
| Equipment under Test | : | Portable Projector Entertainment System |
| Model No. | : | MET1473, RPJ060, RPJ060XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), 10XXXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), PL-1473 |
| Trade Mark | : | MET, RCA, ONN, PPL |
| FCC ID | : | 2ASQA6961473 |
| Manufacturer | : | PRAISE PERFECTION LIMITED |
| Address | : | FLAT/RM 4, 7F SHING YIP INDUSTRIAL BUILDING, 19-21 SHING YIP STREET, KWUN TONG, KL., HONG KONG. |

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

- Test report declares.....3
- 1. General Information 5
 - 1.1. Description of equipment 5
 - 1.2. Assess laboratory 5
- 2. RF Exposure Evaluation 5
 - 2.1. Requirement..... 5
 - 2.2. Calculation method..... 6
 - 2.3. Estimation result..... 6

Test Report Declare

| | | |
|-----------------------------|---|---|
| Applicant | : | PRAISE PERFECTION LIMITED |
| Address | : | FLAT/RM 4, 7F SHING YIP INDUSTRIAL BUILDING, 19-21 SHING YIP STREET, KWUN TONG, KL., HONG KONG. |
| Equipment under Test | : | Portable Projector Entertainment System |
| Model No. | : | MET1473, RPJ060, RPJ060XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), 10XXXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), PL-1473 |
| Trade mark | : | MET, RCA, ONN, PPL |
| Manufacturer | : | PRAISE PERFECTION LIMITED |
| Address | : | FLAT/RM 4, 7F SHING YIP INDUSTRIAL BUILDING, 19-21 SHING YIP STREET, KWUN TONG, KL., HONG KONG. |

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.


| | | | |
|-------------------------|-------------------|----------------------|------------------------------|
| Report No: | DDT-R20051203-1E3 | | |
| Date of Receipt: | May 22, 2020 | Date of Test: | May 22, 2020 ~ Jul. 15, 2020 |

Prepared By:

Sam Li

Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

| Rev. | Revisions | Issue Date | Revised By |
|------|---------------|---------------|------------|
| --- | Initial issue | Jul. 15, 2020 | |
| | | | |

1. General Information

1.1. Description of equipment

| | |
|--------------------------|---|
| EUT* Name | : Portable Projector Entertainment System |
| Model Number | : MET1473, RPJ060, RPJ060XXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), 10XXXXXX (where XXXXX denote any printable characters in the ASCII Standard Character Table to represent variances in cosmetics or buyers), PL-1473 |
| Model differences | : Only the color and appearance are different, there is no other difference. |
| EUT Function Description | : Please reference user manual of this device |
| Power Supply | : DC 13 V is powered by external adapter or 11.1 V built-in battery |
| Radio Specification | : Bluetooth V5.0 |
| Operation Frequency | : 2402 MHz - 2480 MHz |
| Modulation | : GFSK, $\pi/4$ -DQPSK |
| Data Rate | : 1 Mbps, 2 Mbps |
| Antenna Type | : Integral PCB antenna, maximum PK gain: -0.58 dBi |
| Sample Type | : Series production |

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

- E** = Electric field (V/m)
- P** = Peak RF output power (mW)
- G** = EUT Antenna numeric gain (numeric)=
- d** = Separation distance between radiator and human body (m)
- The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

| Mode | PK Output power (dBm) | Output power (mW) | Antenna Gain (dBi) | Antenna Gain (linear) | MPE Values (mW/cm ²) | MPE Limit (mW/cm ²) |
|---------------------|-----------------------|-------------------|--------------------|-----------------------|----------------------------------|---------------------------------|
| Bluetooth Max power | -0.19 | 0.96 | -0.58 | 0.87 | 0.000166 | 1 |

Note: The estimation distance is 20 cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT