

Radio frequency radiation exposure evaluation: portable devices

RESULT :

Pass

Test Specification

Test item	:	Golf GPS Rangefinder
Identification / Type No.	:	Phantom 3
FCC ID	:	2ASQI-36240
IC	:	24886-36240
Test standard	:	CFR47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 D01 General RF Exposure Guidance v06 RSS-102 Issue 5

FCC Measurement Record:

Test Mode	Conducted Power (dBm)	Conducted Power (mW)	Minimum Separation Distances (mm)	Limit (mW)
BLE	5.91	3.899	5	9.7

ISED Measurement Record:

Test Mode	Conducted Power (dBm)	Conducted Power (dBm)	Minimum Separation Distances (mm)	Limit (mW)
BLE	5.91	3.899	5	4

For ISED, output power level shall be the higher of the maximum conducted or effective isotropic radiated power (e.i.r.p.) source-based, time-averaged output power.

Hence the EUT is excluded from SAR evaluation if the distance between the antenna and the human body is equal or above one of the minimum distances depicted in the tables above, depending on the wireless protocol in use, in accordance with FCC KDB Publication 447498 D01 General RF Exposure Guidance v06 and RSS-102 Issue 5.