

# FCC Test Report

Report No.: AGC00184190601FE04

**FCC ID** : 2ASQI-3880

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Top Dogg Ground Swat Grey Camo 360 Degree Sound

**BRAND NAME** : Primos

**MODEL NAME** : 3880, 3870

**APPLICANT** : Bushnell Holdings Inc.

**DATE OF ISSUE** : Nov. 15, 2019

**STANDARD(S)** : FCC Part 15.247

**REPORT VERSION** : V1.0

## Attestation of Global Compliance (Shenzhen) Co., Ltd

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

#### REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date   | Valid Version | Notes           |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0           | /           | Nov. 15, 2019 | Valid         | Initial Release |



## TABLE OF CONTENTS

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>1. VERIFICATION OF COMPLIANCE .....</b>                       | <b>5</b>  |
| <b>2. GENERAL INFORMATION .....</b>                              | <b>6</b>  |
| 2.1 PRODUCT DESCRIPTION .....                                    | 6         |
| 2.2. TABLE OF CARRIER FREQUENCIES .....                          | 6         |
| 2.3 RELATED SUBMITTAL(S)/GRANT(S) .....                          | 7         |
| 2.4 TEST METHODOLOGY .....                                       | 7         |
| 2.5 SPECIAL ACCESSORIES .....                                    | 7         |
| 2.6 EQUIPMENT MODIFICATIONS .....                                | 7         |
| <b>3. MEASUREMENT UNCERTAINTY .....</b>                          | <b>8</b>  |
| <b>4. DESCRIPTION OF TEST MODES .....</b>                        | <b>9</b>  |
| <b>5. SYSTEM TEST CONFIGURATION .....</b>                        | <b>10</b> |
| 5.1 CONFIGURATION OF TESTED SYSTEM .....                         | 10        |
| 5.2 EQUIPMENT USED IN TESTED SYSTEM .....                        | 10        |
| 5.3. SUMMARY OF TEST RESULTS .....                               | 10        |
| <b>6. TEST FACILITY .....</b>                                    | <b>11</b> |
| <b>7. PEAK OUTPUT POWER .....</b>                                | <b>12</b> |
| 7.1. MEASUREMENT PROCEDURE .....                                 | 12        |
| 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....          | 12        |
| 7.3. LIMITS AND MEASUREMENT RESULT .....                         | 13        |
| <b>8. 6 DB BANDWIDTH .....</b>                                   | <b>14</b> |
| 8.1. MEASUREMENT PROCEDURE .....                                 | 14        |
| 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....          | 14        |
| 8.3. LIMITS AND MEASUREMENT RESULTS .....                        | 14        |
| <b>9. CONDUCTED SPURIOUS EMISSION .....</b>                      | <b>15</b> |
| 9.1. MEASUREMENT PROCEDURE .....                                 | 15        |
| 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....          | 15        |
| 9.3. MEASUREMENT EQUIPMENT USED .....                            | 15        |
| 9.4. LIMITS AND MEASUREMENT RESULT .....                         | 15        |
| <b>10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b> | <b>18</b> |

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| 10.1 MEASUREMENT PROCEDURE .....                                  | 18        |
| 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....           | 18        |
| 10.3 MEASUREMENT EQUIPMENT USED .....                             | 18        |
| 10.4 LIMITS AND MEASUREMENT RESULT .....                          | 18        |
| <b>11. RADIATED EMISSION .....</b>                                | <b>19</b> |
| 11.1. MEASUREMENT PROCEDURE .....                                 | 19        |
| 11.2. TEST SETUP .....                                            | 20        |
| 11.3. LIMITS AND MEASUREMENT RESULT .....                         | 21        |
| 11.4. TEST RESULT .....                                           | 21        |
| <b>12. FCC LINE CONDUCTED EMISSION TEST .....</b>                 | <b>25</b> |
| 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....                | 25        |
| 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST .....         | 25        |
| 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST ..... | 26        |
| 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST .....       | 26        |
| 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST .....           | 27        |
| <b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>                | <b>29</b> |
| <b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>                       | <b>31</b> |

## 1. VERIFICATION OF COMPLIANCE

|                                 |                                                                                                                                                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>                | Bushnell Holdings Inc.                                                                                                                                                                                                                                             |
| <b>Address</b>                  | 9200 Cody, Overland Park, KS 66214 USA                                                                                                                                                                                                                             |
| <b>Manufacturer</b>             | Wata Electronics Co., Ltd.                                                                                                                                                                                                                                         |
| <b>Address</b>                  | No 142, South Tanshen Road, Tanzhou Town, Zhongshan City, Guangdong, China                                                                                                                                                                                         |
| <b>Factory</b>                  | Wata Electronics Co., Ltd.                                                                                                                                                                                                                                         |
| <b>Address</b>                  | No 142, South Tanshen Road, Tanzhou Town, Zhongshan City, Guangdong, China                                                                                                                                                                                         |
| <b>Product Designation</b>      | Top Dogg Ground Swat Grey Camo 360 Degree Sound                                                                                                                                                                                                                    |
| <b>Brand Name</b>               | Primos                                                                                                                                                                                                                                                             |
| <b>Test Model</b>               | 3880                                                                                                                                                                                                                                                               |
| <b>Series Model</b>             | 3870                                                                                                                                                                                                                                                               |
| <b>Difference description</b>   | All the same except for the model name and battery. The 3880 will be marketed with Li-on battery and adapter. The 3870 will be marketed with dry battery and without adapter. Both of them had been tested, the 3880 is the worst case and recorded in the report. |
| <b>Date of test</b>             | Nov. 05, 2019 to Nov. 14, 2019                                                                                                                                                                                                                                     |
| <b>Deviation</b>                | No any deviation from the test method                                                                                                                                                                                                                              |
| <b>Condition of Test Sample</b> | Normal                                                                                                                                                                                                                                                             |
| <b>Test Result</b>              | Pass                                                                                                                                                                                                                                                               |
| <b>Report Template</b>          | AGCRT-US-BLE/RF                                                                                                                                                                                                                                                    |

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By

*NiNi*

NiNi Guo  
(Project Engineer)

Nov. 14, 2019

Reviewed By

*Max Zhang*

Max Zhang  
(Reviewer)

Nov. 15, 2019

Approved By

*Forrest Lei*

Forrest Lei  
(Authorized Officer)

Nov. 15, 2019

## 2.GENERAL INFORMATION

### 2.1PRODUCT DESCRIPTION

The EUT is designed as a “Top Dogg Ground Swat Grey Camo 360 Degree Sound”. It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

|                            |                                                               |
|----------------------------|---------------------------------------------------------------|
| <b>Operation Frequency</b> | 915MHz                                                        |
| <b>RF Output Power</b>     | 11.011dBm(Average)                                            |
| <b>Modulation</b>          | GFSK                                                          |
| <b>Number of channels</b>  | 1 Channel                                                     |
| <b>Antenna Designation</b> | PIFA Antenna(Comply with requirements of the FCC part 15.203) |
| <b>Antenna Gain</b>        | 0dBi                                                          |
| <b>Hardware Version</b>    | V2.41                                                         |
| <b>Software Version</b>    | V1.0                                                          |
| <b>Power Supply</b>        | DC 14.8V by battery                                           |

### 2.2. TABLE OF CARRIER FREQUENCIES

| Frequency Band | Frequency |
|----------------|-----------|
| 902-928MHz     | 915MHz    |

### 2.3 RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2ASQI-3880** filing to comply with the FCC Part 15.247 requirements.

### 2.4 TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

### 2.5 SPECIAL ACCESSORIES

Refer to section 2.2.

### 2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission,  $U_c = \pm 3.2$  dB
- Uncertainty of Radiated Emission below 1GHz,  $U_c = \pm 3.9$  dB
- Uncertainty of Radiated Emission above 1GHz,  $U_c = \pm 4.8$  dB
- Uncertainty of total RF power, conducted,  $U_c = \pm 0.8$  dB
- Uncertainty of RF power density, conducted,  $U_c = \pm 2.6$  dB
- Uncertainty of spurious emissions, conducted,  $U_c = \pm 2.7$  dB
- Uncertainty of Occupied Channel Bandwidth:  $U_c = \pm 2$  %



#### 4. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|-----|-----------------------|
| 1   | Transmitting mode     |


Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



## 5. SYSTEM TEST CONFIGURATION

### 5.1 CONFIGURATION OF TESTED SYSTEM



### 5.2 EQUIPMENT USED IN TESTED SYSTEM

| Item | Equipment                                       | Model No.      | ID or Specification                                                       | Remark |
|------|-------------------------------------------------|----------------|---------------------------------------------------------------------------|--------|
| 1    | Top Dogg Ground Swat Grey Camo 360 Degree Sound | 3880           | 2ASQI-3880                                                                | EUT    |
| 2    | Adapter                                         | GQ24-190100-AU | Input: AC 100-240V, 50/60Hz,<br>1.0A max<br>Output: DC 19V $\approx$ 1.0A | Supprt |

### 5.3. SUMMARY OF TEST RESULTS

| FCC RULES     | DESCRIPTION OF TEST                    | RESULT    |
|---------------|----------------------------------------|-----------|
| 15.247 (b)(3) | Peak Output Power                      | Compliant |
| 15.247 (a)(2) | 6 dB Bandwidth                         | Compliant |
| 15.247 (d)    | Conducted Spurious Emission            | Compliant |
| 15.247 (e)    | Maximum Conducted Output Power Density | Compliant |
| 15.209        | Radiated Emission                      | Compliant |
| 15.207        | Conducted Emission                     | Compliant |

## 6. TEST FACILITY

|                                          |                                                                                                                                          |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Site</b>                         | Attestation of Global Compliance (Shenzhen) Co., Ltd                                                                                     |
| <b>Location</b>                          | 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| <b>Designation Number</b>                | CN1259                                                                                                                                   |
| <b>FCC Test Firm Registration Number</b> | 975832                                                                                                                                   |
| <b>A2LA Cert. No.</b>                    | 5054.02                                                                                                                                  |
| <b>Description</b>                       | Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA                                                                |

### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

| Equipment     | Manufacturer | Model                | S/N    | Cal. Date     | Cal. Due      |
|---------------|--------------|----------------------|--------|---------------|---------------|
| TEST RECEIVER | R&S          | ESCI                 | 10096  | Jun. 12, 2019 | Jun. 11, 2020 |
| LISN          | R&S          | ESH2-Z5              | 100086 | Aug. 26, 2019 | Aug. 25, 2020 |
| Test software | R&S          | ES-K1<br>(Ver V1.71) | N/A    | N/A           | N/A           |

### TEST EQUIPMENT OF RADIATED EMISSION TEST

| Equipment                         | Manufacturer   | Model                | S/N        | Cal. Date     | Cal. Due      |
|-----------------------------------|----------------|----------------------|------------|---------------|---------------|
| TEST RECEIVER                     | R&S            | ESCI                 | 10096      | Jun. 12, 2019 | Jun. 11, 2020 |
| EXA Signal Analyzer               | Aglient        | N9010A               | MY53470504 | Dec. 20, 2018 | Dec. 19, 2019 |
| 2.4GHz Fliter                     | EM Electronics | 2400-2500MHz         | N/A        | Feb. 27, 2019 | Feb. 26, 2020 |
| Attenuator                        | ZHINAN         | E-002                | N/A        | Sep. 09, 2019 | Sep. 08, 2020 |
| Horn antenna                      | SCHWARZBECK    | BBHA 9170            | #768       | Sep.21, 2019  | Sep. 20, 2021 |
| Active loop antenna<br>(9K-30MHz) | ZHINAN         | ZN30900C             | 18051      | Jun. 13, 2018 | Jun. 12, 2020 |
| Double-Ridged Waveguide Horn      | ETS LINDGREN   | 3117                 | 00034609   | May. 17, 2018 | May. 16, 2020 |
| Broadband Preamplifier            | ETS LINDGREN   | 3117PA               | 00225134   | Oct. 15, 2019 | Oct. 16, 2020 |
| ANTENNA                           | SCHWARZBECK    | VULB9168             | 494        | Sep. 20, 2019 | Sep. 19, 2021 |
| Test software                     | Tonscend       | JS32-RE<br>(Ver.2.5) | N/A        | N/A           | N/A           |

## 7. PEAK OUTPUT POWER

### 7.1. MEASUREMENT PROCEDURE

For peak power test:


1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2.  $RBW \geq DTS$  bandwidth
3.  $VBW \geq 3 \times RBW$ .
4.  $SPAN \geq VBW$ .
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.


For average power test:

Connect EUT RF output port to the average power sensor.

### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP




### AVERAGE POWER SETUP



### 7.3. LIMITS AND MEASUREMENT RESULT

| PEAK OUTPUT POWER MEASUREMENT RESULT<br>FOR GFSK MOUDULATION |                     |                        |                               |              |
|--------------------------------------------------------------|---------------------|------------------------|-------------------------------|--------------|
| Frequency<br>(GHz)                                           | Peak Power<br>(dBm) | Average power<br>(dBm) | Applicable<br>Limits<br>(dBm) | Pass or Fail |
| 0.915                                                        | 19.679              | 11.011                 | 30                            | Pass         |



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

## 8. 6 DB BANDWIDTH

### 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW $\geq 3 \times$  RBW.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.


### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

### 8.3. LIMITS AND MEASUREMENT RESULTS

| LIMITS AND MEASUREMENT RESULT |                   |       |          |
|-------------------------------|-------------------|-------|----------|
| Applicable Limits             | Applicable Limits |       |          |
|                               | Test Data (kHz)   |       | Criteria |
| >500KHZ                       | operate Channel   | 643.5 | PASS     |

TEST PLOT OF BANDWIDTH



## 9. CONDUCTED SPURIOUS EMISSION

### 9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

### 9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.

### 9.4. LIMITS AND MEASUREMENT RESULT

| LIMITS AND MEASUREMENT RESULT                                                                                                                                                                                                                                                                                          |                                          |              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|--------------|
| Applicable Limits                                                                                                                                                                                                                                                                                                      | Measurement Result                       |              |
|                                                                                                                                                                                                                                                                                                                        | Test Data                                | Criteria     |
| In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. | At least -20dBc than the reference level | PASS<br>PASS |




### TEST RESULT FOR ENTIRE FREQUENCY RANGE



Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit.

### TEST RESULT FOR BAND EDGE



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

## 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

### 10.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

### 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 7.2.


### 10.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

### 10.4 LIMITS AND MEASUREMENT RESULT

| Channel No.     | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | Result |
|-----------------|-------------------|---------------------|--------|
| operate Channel | 2.009             | 8                   | Pass   |

TEST PLOT OF SPECTRAL DENSITY




## 11. RADIATED EMISSION

### 11.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



### 11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.

### 11.4. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

### RADIATED EMISSION BELOW 1GHZ


|             |                                                    |                   |                |
|-------------|----------------------------------------------------|-------------------|----------------|
| EUT         | Top Dogg Ground Swat Grey<br>Camo 360 Degree Sound | Model Name        | 3880           |
| Temperature | 25° C                                              | Relative Humidity | 55.4%          |
| Pressure    | 960hPa                                             | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1                                             | Antenna           | Horizontal     |



| NO. | Freq.<br>[MHz] | Level<br>[dBμV/m] | Factor<br>[dB] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Polarity   |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1   | 36.7900        | 28.06             | 14.16          | 40.00             | 11.94          | 100            | 339          | Horizontal |
| 2   | 66.8600        | 28.64             | 12.76          | 40.00             | 11.36          | 150            | 160          | Horizontal |
| 3   | 143.490        | 37.69             | 14.88          | 43.50             | 5.81           | 150            | 213          | Horizontal |
| 4   | 207.510        | 36.51             | 12.52          | 43.50             | 6.99           | 150            | 3            | Horizontal |
| 5   | 416.060        | 35.63             | 20.14          | 46.00             | 10.37          | 100            | 297          | Horizontal |
| 6   | 688.630        | 37.58             | 25.80          | 46.00             | 8.42           | 100            | 323          | Horizontal |

RESULT: PASS

|             |                                                    |                   |                |
|-------------|----------------------------------------------------|-------------------|----------------|
| EUT         | Top Dogg Ground Swat Grey<br>Camo 360 Degree Sound | Model Name        | 3880           |
| Temperature | 25° C                                              | Relative Humidity | 55.4%          |
| Pressure    | 960hPa                                             | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1                                             | Antenna           | Vertical       |



| NO. | Freq.<br>[MHz] | Level<br>[dBμV/m] | Factor<br>[dB] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1   | 36.7900        | 28.68             | 14.16          | 40.00             | 11.32          | 100            | 313          | Vertical |
| 2   | 52.3100        | 34.46             | 14.49          | 40.00             | 5.54           | 100            | 245          | Vertical |
| 3   | 143.490        | 27.05             | 14.88          | 43.50             | 16.45          | 100            | 113          | Vertical |
| 4   | 289.960        | 27.68             | 16.11          | 46.00             | 18.32          | 100            | 344          | Vertical |
| 5   | 546.040        | 34.21             | 23.18          | 46.00             | 11.79          | 100            | 171          | Vertical |
| 6   | 774.960        | 38.84             | 27.80          | 46.00             | 7.16           | 100            | 261          | Vertical |

## RESULT: PASS

### Note:

- Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- The emission above the limit is the fundamental wave, and there is a filter used for it .

### RADIATED EMISSION ABOVE 1GHZ

|                    |                                                    |                          |                |
|--------------------|----------------------------------------------------|--------------------------|----------------|
| <b>EUT</b>         | Top Dogg Ground Swat Grey<br>Camo 360 Degree Sound | <b>Model Name</b>        | 3880           |
| <b>Temperature</b> | 25° C                                              | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa                                             | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1                                             | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz) | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 1830.014           | 50.14                   | -1.25          | 48.89                      | 74.00              | -25.11         | peak       |
| 1830.014           | 48.98                   | -1.25          | 47.73                      | 54.00              | -6.27          | AVG        |
| 2745.026           | 42.46                   | 0.13           | 42.59                      | 74.00              | -31.41         | peak       |
| 2745.026           | 39.26                   | 0.13           | 39.39                      | 54.00              | -14.61         | AVG        |
|                    |                         |                |                            |                    |                |            |
|                    |                         |                |                            |                    |                |            |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

|                    |                                                    |                          |                |
|--------------------|----------------------------------------------------|--------------------------|----------------|
| <b>EUT</b>         | Top Dogg Ground Swat Grey<br>Camo 360 Degree Sound | <b>Model Name</b>        | 3880           |
| <b>Temperature</b> | 25° C                                              | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa                                             | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1                                             | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz) | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 1830.014           | 50.28                   | -1.25          | 49.03                      | 74.00              | -24.97         | peak       |
| 1830.014           | 46.77                   | -1.25          | 45.52                      | 54.00              | -8.48          | AVG        |
| 2745.026           | 44.89                   | 0.13           | 45.02                      | 74.00              | -28.98         | peak       |
| 2745.026           | 42.64                   | 0.13           | 42.77                      | 54.00              | -11.23         | AVG        |
|                    |                         |                |                            |                    |                |            |
|                    |                         |                |                            |                    |                |            |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

#### Note:

Other emissions from 1G to 9.2GHz are considered as ambient noise. No recording in the test report.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

## 12. FCC LINE CONDUCTED EMISSION TEST


### 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency     | Maximum RF Line Voltage |                |
|---------------|-------------------------|----------------|
|               | Q.P.( dBuV)             | Average( dBuV) |
| 150kHz~500kHz | 66-56                   | 56-46          |
| 500kHz~5MHz   | 56                      | 46             |
| 5MHz~30MHz    | 60                      | 50             |

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter which received AC120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

## 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



### MEASUREMENT RESULT: "agc\_fin"

2019/11/08 16:56

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 63.30         | 10.6         | 66            | 2.7          | QP       | L1   | FLO |
| 0.186000         | 58.20         | 10.8         | 64            | 6.0          | QP       | L1   | FLO |
| 0.198000         | 57.00         | 10.8         | 64            | 6.7          | QP       | L1   | FLO |
| 0.206000         | 51.90         | 10.8         | 63            | 11.5         | QP       | L1   | FLO |
| 0.214000         | 53.90         | 10.8         | 63            | 9.1          | QP       | L1   | FLO |
| 0.226000         | 53.50         | 10.8         | 63            | 9.1          | QP       | L1   | FLO |

### MEASUREMENT RESULT: "agc\_fin2"

2019/11/08 16:56

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 47.10         | 10.6         | 56            | 8.9          | AV       | L1   | FLO |
| 0.186000         | 41.30         | 10.8         | 54            | 12.9         | AV       | L1   | FLO |
| 0.194000         | 40.10         | 10.8         | 54            | 13.8         | AV       | L1   | FLO |
| 0.198000         | 38.80         | 10.8         | 54            | 14.9         | AV       | L1   | FLO |
| 0.206000         | 30.00         | 10.8         | 53            | 23.4         | AV       | L1   | FLO |
| 0.214000         | 33.10         | 10.8         | 53            | 19.9         | AV       | L1   | FLO |
| 0.270000         | 32.70         | 10.8         | 51            | 18.4         | AV       | L1   | FLO |



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

### Line Conducted Emission Test Line 2-N



#### MEASUREMENT RESULT: "agc\_fin"

2019/11/08 16:53

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 64.60         | 10.6         | 66            | 1.4          | QP       | N    | FLO |
| 0.158000         | 63.60         | 10.7         | 66            | 2.0          | QP       | N    | FLO |
| 0.194000         | 58.70         | 10.8         | 64            | 5.2          | QP       | N    | FLO |
| 0.214000         | 55.40         | 10.8         | 63            | 7.6          | QP       | N    | FLO |
| 0.222000         | 55.20         | 10.8         | 63            | 7.5          | QP       | N    | FLO |
| 0.246000         | 50.60         | 10.8         | 62            | 11.3         | QP       | N    | FLO |

#### MEASUREMENT RESULT: "agc\_fin2"

2019/11/08 16:53

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 48.20         | 10.6         | 56            | 7.8          | AV       | N    | FLO |
| 0.158000         | 45.30         | 10.7         | 56            | 10.3         | AV       | N    | FLO |
| 0.190000         | 42.00         | 10.8         | 54            | 12.0         | AV       | N    | FLO |
| 0.222000         | 38.20         | 10.8         | 53            | 14.5         | AV       | N    | FLO |
| 0.254000         | 34.20         | 10.8         | 52            | 17.4         | AV       | N    | FLO |
| 0.266000         | 33.90         | 10.8         | 51            | 17.3         | AV       | N    | FLO |

#### RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### RADIATED EMISSION TEST SETUP BELOW 1GHZ



### RADIATED EMISSION TEST SETUP ABOVE 1GHZ



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

**CONDUCTED EMISSION TEST SETUP**

## APPENDIX B: PHOTOGRAPHS OF EUT

### ALL VIEW OF EUT



**Attestation of Global Compliance**

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


TOP VIEW OF EUT




BOTTOM VIEW OF EUT




FRONT VIEW OF EUT




BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (PORT)




OPEN VIEW-1 OF EUT



OPEN VIEW OF EUT-2




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



VIEW OF BATTERY



----END OF REPORT----