

English

01. Package Contents

3

2



1









THE STATE OF THE S


4



8 Paper Output

(5)

Cover Release Button (6) Ų



03. Note
 ① Please use a 5V = 2A adapter to charge the printer. You may use a phone adapter to charge the printer. ② Connect the USB cable to a power adapter to charge the printer. When charging, gently inso or remove the power cord to prevent damaging the terminals. ③ Please remove the power cable after charging. ④ To prevent any dangerous situations, please do not use or charge the printer in environmer that are too hot, too wet, or contain a lot of smoke and dust. Do not use them in bathrooms, saunas, open flame, etc. ⑤ Charging inappropriately might damage the printer head. ⑤ Do not touch the printer head as it might burn. ⑦ The paper cutter blade is very sharp. Please be careful when handling it. ⑧ If the printer malfunctions, gently poke the reset hole to restart the printer.

- * Do not disassemble, crush, break, or toss the batteries into fire.

 * Please do not reuse when the battery is swollen.

 * Please do not use if the battery is exposed to water and high temperature.

 * Using the wrong battery may cause an explosion. Please dispose of used batteries according to the Instruction Manual.


 * If the user widese the user and the last of the last of
- If the user wishes to use an adapter, please purchase and use adapters that have CCC certificates or fulfill relevant safety standards.
- 04. How to Download the App
- Mobile Download Please search for "Phomemo" on your device's app market and download the software.

- Phomemo

printer.

Method 1:

05. How to Connect to the App



Method 2: Press the Power Button twice to print out a QR code. Use your Phomemo App to scan the QR code.

1. For your first use, please charge the printer fully. Press and hold the Power Button for around 3 seconds to start the

Turn on the Bluetooth function on yo phone. Connect after searching for M02 on your Phomemo App.

2. Connecting to the Printer.

. Open the printer's cover. Take out



the paper holder.

Maintenance person:

Delivery date:

Delivery date:

- 09. Warranty Card Return Exchange Repair Name Gender: Phone:
 - Failure condition: Handling situation: Maintenance ticket number

Product order number:

User Info

Product Info

Address Purchase date:

11. Basic Functions 10.1 Print images Steps: 1.Choose the "Print Images" function in the Phomemo App 2.Add the photos you wish to print. 3.Adjust the setting of the image in the workspace. 4.Choose the printing intensity.

5.Press the "Print" button on the lower right corner to print. 10.2 Graphic Function The Graphics library contains various materials drawn by artists. You can modify and lize the materials us personalize the materials using the following steps. Step 1: Select the "Graphic" function in the Phomemo App. Step 2: Select the Graphic Tunction in the Frion

Reason Problem Only half the paper is printed The printer head did not connect properly

1. Unable to charge

The charger is overheating 3. Unable to switch on printer

2. System Bug

3. System Bug

 The paper holder is not installed correctly 2. The paper is wrinkled or deformed

The printer's cover is not closed properly

4. The printer's power is too low

The paper is exposed to the air for a long time

Improper storage

the paper

Unable to print

App shows that the printer has run out of paper

Missing prints

The text on the paper is faint

There's a black line on

4. The Indicator light is flashing

Your phone's Bluetooth is deactivated

12. Frequently Asked Questions

Function

Table

Image

Emoji

QR Code

einstall the paper. The paper is not pulled to the utput slot. Pull a segment of paper out of the aper output slot. Remove the paper holder, manually pull the paper roll tight, and reinstall the paper holder. Or use the paper roll directly. The paper roll has ecome loose and causes Paper jammed in the printer 2. There's a foreign object in the printer Open the printer's paper compartment and use rubbing alcohol to clean the interior of the printer

After printing, do not store the paper with the printing surface touching another printing surface or plastic surface. Please choose self-adhesive thermal paper. Some alkaline-based adhesive will cause the print to fade faster. 13. FCC Warning This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception. equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following Reorient or relocate the receiving antenna. Increase the separation between the equip e the se quip nd racai Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.
 The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction. 14. ISED Warning

- 3. Load the printing paper 2. Remove the adjuster on Install the adjuster on the right side the right side (O) 5. Put in the paper holder and close the printer's cover *Tips: How to differentiate the front and back parts of the Thermal Paper? ① Use your nail to scratch the surface of the Thermal Paper. Install the thermal paper with the side that shows color facing up. ② Make sure the glossy side is facing upward. 07. Warranty Thank you for choosing our product.
 * We provide "Exchange/Refund" services for customers within one year upon the purchase of the product. 08. After-sales services pp : +86 13928088284 / +86 15338193665 Phomemo Team-Jessie / Phomemo Team-Helen (US only) Office Hours: Monday to Friday from 9 a.m. to 5 p.m. EST www.phomemo.com யிம் Please search for "Phomemo" to find more guides on how to operate the printer.
 - Product Serial Number: Reason description:
 - 10. Official Thermal Paper Type ① Waterproof, oilproof, PVC thermal paper: Does tant. Can retain the printed image for 7-10 years. er: Does not contain Bisphenol-A. Scratch-resis-② Color thermal paper: Does not contain Bisphenol-A. Includes colors such as yellow, pink. blue, etc. Can retain the printed image for up to 5 years.

 ③ Self-adhesive thermal paper: Does not contain Bisphenol-A. The thermal pap Seri-adriesive tierman paper, Does into Comian Bispinerors. The tierman paper has adhesive side that can stick to objects. Can retain the printed image for up to 10 years.
 Semi-transparent thermal paper: Does not contain Bisphenol-A. Waterproof, oilproof, and scratch-resistant. Excellent retention of the printed image for up to 15 years.
 "The above-mentioned are official Phomemo thermal papers.
 "We are not responsible for any damage caused to the printer if unofficial thermal papers
 - Step 3: You can create personalized edits by adding text, table, image, stickers, QR codes on the edit screen. Any content edited is previewed on the edit screen.

Description

Selecting "Text" will insert a text box for editing. You can edit the content's font, alignment, etc.

Selecting "Emoji" will insert an Emoji for editing or printing.

Selecting "QR Code" will bring you to a screen where you can insert any text or numbers to generate a QR Code.

Selecting "Table" will insert a table for editing.

Step 4: Press the $\ \, \boxminus \,$ button on the upper right corner to print.

Select the "Print Web" function in the Phomemo App and enter the URL to access the webpage. Press the "Print" button to print the content of the webpage.

Common problems and solutions

adapter

Solution Reinstall the paper holder according to the paper adapter.

Reinstall the paper holder according to the paper

Connect the printer. You can check the remaining power of the printer at the Bluetooth connection indicator in the upper right corner.

Use a SV = 2A charger. Under normal circumstances, the printer will be fully charged in 2-5 hours.

Do not leave the printer uncharged for more than 3 months or so. The battery power might run out completely and fail to activate or charge.

Activate your phone's Bluetooth. (Bluetooth function does not activate automatically. You have to activate it manually)

10.3 Printing Windows Application Files

Selecting "Image" will insert an image for editing or printing.

The printer is not turned on. Turn on the print Press the Power Button of the printer twice to print the QR Code. Scan the QR Code to connect to the printer. 2. The App cannot dete nnot connecthe Printer' Bluetooth Disconnect your printer from other existing phones You may only connect the printer to one phone at a Connecting to multiple devices u cannot connect to the printer while conne your Bluetooth earphones. Disconnect from her devices before connecting to the printer. The phone's location has not been turned on The paper is installed the other way round. The printing surface should be installed facing up. Paper comes out without prints

Restart your pho

The paper is stuck, pull out some paper

e's no power. Charge for half an hour

Reinstall the paper. The paper is not extended toward the paper output slot.

Reinstall the paper holder according to the paper adapter.

Take out the paper and cut off the deformed area Reinstall and continue to print.

Close the printer's cover properly using your palm.

Store unused paper in a sealed bag or contain Thermal paper should not be glued together. Record your edits before you print. After printing, avoid using permanent markers or rollerball pens

Environmental temperature, humidity, alcohol, sanitizers, sweat, or hand soap can cause the text to fade.

Store the printing papers away from sunlight in a dry environment.

he sensor has malfunction oclean the sensor.

Uninstall and reinstall the App

No power. Charge before printing. Set the printing intensity to the highest The paper will expire even if placed inside the machine when exposed to humidity and the air for a long time.

on the pap

IC Warning statement:

2.This device must accept any interference, including interference that may cause

comply RSS(s).

- This device contains licence-exempt transmitter(s)/receiver(s) that comp Innovation, Science and Economic Development Canada's licence-exempt Operation is subject to the following two conditions: 1.This device may not cause interference.
- L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: 1.L' appareil ne doit pas produire de brouillage;

The device has been evaluated to meet general IC RF exposure requirement. The device can be used in portable exposure condition without restriction.

IC Déclaration d'exposition aux RF: L'appareil a été évalué pour répondre aux exigences générales d'exposition aux RF d'IC. L'appareil peut être utilisé dans des conditions d'exposition portable sans restriction.

undesired operation of the device.

 $2.L'\ appareil\ doit\ accepter\ tout\ brouillage\ radio\'electrique\ subi,\ m\^eme\ si\ le\ brouillage\ est\ susceptible\ d'\ en\ compromettre\ le\ fonctionnement.$ RF exposure statement