

Report No.: SHEM190301151102

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: SHEM1903011511CR FCC ID: 2ASRJHS-AT2301

Applicant: Zhejiang Hanshow Technology Co.,Ltd

Address of Applicant: Bld.33, Zhifu Center, Jiaxing, Zhejiang, P.R. China Manufacturer: Suzhou Caina Electronics Technology Co., Ltd

Address of Manufacturer: No.588 San Xing Rd, Wujiang District, Suzhou, Jiangsu Province, P.R.

China

Factory: Suzhou Caina Electronics Technology Co., Ltd

Address of Factory: No.588 San Xing Rd, Wujiang District, Suzhou, Jiangsu Province, P.R.

China

Equipment Under Test (EUT):

EUT Name: DIGITAL SIGNAGE 23.1INCH

Model No.: HS-AT2301
Trade mark: Hanshow

Standard(s): FCC Rules 47 CFR §2.1091

KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2019-03-13

Date of Test: 2019-03-20 to 2019-03-21

Date of Issue: 2019-03-26

Test Result: Pass*

Parlam Zhan

Parlam ∠nan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



DPTOVAIS IN Writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction susses defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document ose not exoneate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone (86-755) 83071443,

| NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 (186-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn 中国・上海・松江区金都西路588号 邮编: 201612 (186-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM190301151102

Page: 2 of 7

Revision Record						
Version	Description	Date	Remark			
00	Original	2019-03-26	/			

Authorized for issue by:		
	Bril Wu	
	Bill Wu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM190301151102

Page: 3 of 7

2 Contents

		Pa	age
1	C	OVER PAGE	1
2	C	ONTENTS	3
3	G	ENERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T	4
	3.2	TEST LOCATION	5
	3.3	TEST FACILITY	5
4	T	EST STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	M	IEASUREMENT AND CALCULATION	6
	5.1	MAXIMUM TRANSMIT POWER	6
	5.2	MPE CALCULATION	7



Report No.: SHEM190301151102

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

Power supply: DC 12V 3A By adapter

Test voltage: AC 120V/60Hz Cable: AC Cable 1.5m

DC Cable 1.2m

Antenna Type PCB Antenna

Channel Spacing 5MHz

Modulation Type 802.11b: DSSS (CCK, DQPSK, DBPSK)

802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Number of Channels 802.11b/g/n(HT20):11

Operation Frequency 802.11b/g/n(HT20): 2412MHz to 2462MHz

Antenna Gain -0.63dBi



Report No.: SHEM190301151102

Page: 5 of 7

3.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC –Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB identifier: CN0020.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM190301151102

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM190301151101

The Fower Data is based on the IXI Test Keport Shill in 190501151101					
Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]	
11B	2412	Ant1	13.06	20.23	
11B	2437	Ant1	13.25	21.13	
11B	2462	Ant1	13.15	20.65	
11G	2412	Ant1	12.62	18.28	
11G	2437	Ant1	12.94	19.68	
11G	2462	Ant1	12.80	19.05	
11N20SISO	2412	Ant1	12.23	16.71	
11N20SISO	2437	Ant1	12.58	18.11	
11N20SISO	2462	Ant1	12.35	17.18	



Report No.: SHEM190301151102

Page: 7 of 7

5.2 MPE Calculation

The max conducted output power is 21.13mW;

For FCC:

According to the formula $S = \frac{P}{4R^2\pi}$, we can calculate S which is MPE.

Note:

- 1) P (Watts)
- 2) G (Antenna gain in numeric)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{P}{4R^2\pi} = 0.004 \text{ mW/cm}^2 < 1 \text{mW/cm}^2$$

So the device is exclusion from SAR test.

-- End of the Report--