

Maximum Permissible Exposure Evaluation

FCC ID: 2ASRQ-CP-2105

1. Client Information

Applicant	:	Shenzhen Zhongben Security electronic Co., Ltd
Address	:	4F, Block 10th, Rundongsheng Industrial Zone, Xixiang, Bao'an District, Shenzhen, China
Manufacturer	:	Shenzhen Zhongben Security electronic Co., Ltd
Address	:	4F, Block 10th, Rundongsheng Industrial Zone, Xixiang, Bao'an District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Smart Pet Feeder
Models No.	:	CP-2105, CP-P201, CP-2102, CP-2103, CP-2106
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only different is appearance.
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	RF Output Power:	802.11b: 16.83dBm 802.11g: 15.62dBm 802.11n (HT20): 15.54dBm 802.11n (HT40): 14.36dBm
	Antenna Gain:	2dBi Internal Antenna
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK, QPSK, 16QAM, 64QAM)
Power Supply	:	DC Voltage by AC/DC Adapter supplied(LY012SPS-050200UH)
Power Rating	:	Input: DC 5V 2A
Connecting I/O Port(S)	:	Please refer to the User's Manual

TB-RF-075-1.0

MPE Calculations for WIFI

1. Antenna Gain:

Internal Antenna: 2dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11b	16.83	16±1	17	2	20	0.01580
802.11g	15.62	15±1	16	2	20	0.01255
802.11n (HT20)	15.54	15±1	16	2	20	0.01255
802.11n (HT40)	14.36	14±1	15	2	20	0.00997

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.01580 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----