

Antenna specification

Antenna Sample Confirmation From

Name of supplier	ShenZhen Aihui Technology Co. , Ltd				
Customer name	Ke Jing Ming				
Sample name	NPX122				
model	Tablets				
Sample size	Wire length 200mm 1.13 wire diameter 1 generation terminal				
Inspection item	Performance test	Visual inspection	Structure	In the news	Test results
Notes					
Quality Audit		Project Audit		Business confirmation	
The following is to be completed by the client					

Shenzhen Aihui Technology Co. , Ltd.

Customer feedback	
Customer signature/seal	date:

Antenna Test Report

Test Unit: Shenzhen Aihui Technology Co. , Ltd.			
Materials	FPC		
Antenna form	PIFA	Polarization mode	Linear
Application scenario	Wifi /BT		
Working band	2400Mhz-2500Mhz 5100Mhz-5850Mhz	VSWR	≤2

Address: 402TEL: 0755-23203435fax: 0755-23203435, Block C, Juxin Science and
Technology Industrial Park, Nanchang community, xixiang, Baoan District, Shenzhen

Shenzhen Aihui Technology Co. , Ltd.

Power	Max: 2W	Impedance	50Ω
dBi	≥		
Test Equipment	HPE5071C、Shielding Room、3D automatic turntable		
<p>Antenna Description::</p> <p>1. Grounding processing and picture description: no</p> <p>2. Need to change the motherboard to match: no</p> <ul style="list-style-type: none">● Test voltage: 3.6V, check the antenna contact is good before testing.● The RF cable of the integrated tester is kept in a natural state and can not be curled. <p>Specification:test the specified power level, all indicators must conform to the specifications.</p>			

1. Project Image

2. Test Fixture

3. Antenna matching circuit

4. S11 test

5. Antenna passive efficiency and gain

6. Darkroom test equipment and data

7. Schematic diagram of antenna assembly

8. Antenna environment handling

9. Antenna mass production index

10. Structural drawing


1. Project Image

The final verification antenna performance prototype in our company for at least one year, easy to analyze and solve the problem of antenna mass production, to ensure the quality of antenna shipment

2. Test Fixture

Objective: to test the passive parameters of antenna as accurately as possible. Making Method: the handset is made of a 50 ohm coaxial cable, one end of which is connected to the test point of the back end of the matching circuit of the handset motherboard (front end of the RF test hole) , and the other end is connected to the SMA joint. The diagram is as follows:

3. Antenna matching circuit




Modify

E01	E02	E03
No	No	No


Note: The match is unmodified.

4.S11 test

4.0 4.0s11 test method description of test equipment: Network Analyzer (E5071C) test method: a 50 ohm CABLE is used to export from the instrument test port. The SMA connector for connecting the handset is calibrated using a calibration piece, record the echo loss and standing wave ratio corresponding to the relevant frequency points. The test schematic is as follows:



5. Darkroom test equipment and data



6. Test Equipment

Test system: shielded darkroom

The temperature was $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and the humidity was $50\% \pm 15\%$

Test equipment: when testing passive data, use the Network analyzer AGILENTE5071C to test active data, use the omnibus CMW500



nce and
Shenzhen




7.Active antenna test data


Frequency Band	2.4G-WIFI B模			2.4G-WIFI G模		
channel	L	M	H	L	M	H
TRP	16.38	16.75	17.12	14.65	14.86	15.14
TIS			-78.36			-67.17
Frequency Band	2.4G-WIFI N模			5.8G-WIFI A模		
channel	L	M	H	L	M	H
TRP	14.36	14.41	15.24	14.65	14.31	13.1
TIS			-67.05			-70.35

测试数据:		
WIFI 2.4G		
Freq(MHz)	Efficiency (%)	Gain (dBi)
2400	58.64	1.25
2410	59.32	1.66
2420	54.21	1.73
2430	54.85	1.55
2440	56.32	1.25
2450	57.44	1.30
2460	58.65	1.29
2470	59.35	1.41
2480	54.21	1.54



测试数据:		
WIFI 5.8G		
Freq(MHz)	Efficiency (%)	Gain (dBi)
5150	55.23	1.85
5200	56.32	1.44
5250	54.58	1.51
5300	52.65	1.54
5350	57.54	1.62
5400	58.65	1.55
5450	58.51	2.10
5500	51.44	1.35
5550	52.33	1.54
5600	54.25	1.66
5650	51.98	1.58
5700	52.64	1.47
5750	53.47	1.30
5800	58.62	1.47
5850	57.63	1.25

2.4G





5.8G



6.The panel matches the change schematic

7.Antenna environment handling



The original environment, we do not do processing

8.Antenna mass production index


When the antenna is mass-produced, the standing wave ratio is taken as the mass-produced test standard.

Based on the differences of the project itself, the following criteria are given:

Frequency	Standard for volume production
2400 MHZ -2500MHZ	VSWR (Mass Production performance) & LT; VSWR(recognition performance) 0.5
5100 MHZ -5800MHZ	VSWR (Mass Production performance) & LT; VSWR(recognition performance) 0.5

9.Structural drawings

Shenzhen Aihui Technology Co. , Ltd.



Address: 402TEL: 0755-23203435fax: 0755-23203435, Block C, Juxin Science and Technology Industrial Park, Nanchang community, xixiang, Baoan District, Shenzhen