

**Maximum Permissible Exposure Report****1. Product Information**

EUT	:	Multi-function projector
Test Model	:	NeoPix 130
Additional Model No.	:	NeoPix 130C, NeoPix 130W, NeoPix 130 Smart, NeoPix 130C Smart, NeoPix 130W Smart
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	:	Input:100V-240V~, 50/60Hz, 50W
Hardware Version	:	V2.0
Software Version	:	v10
<b>Bluetooth</b>		
Frequency Range	:	2402MHz ~ 2480MHz
Channel Number	:	79 Channels for Bluetooth V5.0(DSS) 40 channels for Bluetooth V5.0(DTS)
Channel Spacing	:	1MHz for Bluetooth V5.0(DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	:	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0(DSS) GFSK for Bluetooth V5.0(DTS)
Bluetooth Version	:	V5.0
Antenna Description	:	Antenna1: FPC Antenna, 2.0dBi(Max.)
<b>WIFI(2.4G Band)</b>		
Frequency Range	:	2412MHz~2462MHz
Channel Number	:	11 Channels for 20MHz bandwidth(2412~2462MHz) 7 Channels for 40MHz bandwidth(2422~2452MHz)
Channel Spacing	:	5MHz
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna1: FPC Antenna, 2.0dBi(Max.) Antenna2: FPC Antenna, 2.0dBi(Max.)
<b>WIFI(5.2G Band)</b>		
Frequency Range	:	5180MHz~5240MHz
Channel Number	:	4 channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	:	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna1: FPC Antenna, 2.0dBi(Max.) Antenna2: FPC Antenna, 2.0dBi (Max.)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



WIFI(5.8G Band)	
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna1: FPC Antenna, 2.0dBi(Max.) Antenna2: FPC Antenna, 2.0dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 3. Limit

### 3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.





### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance  
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

- Where: S=power density
- P=power input to antenna
- G=power gain of the antenna in the direction of interest relative to an isotropic radiator
- R=distance to the center of radiation of the antenna

### 5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna 1	FPC Antenna	2400-2500 MHz	2.0 dBi	Bluetooth/2.4G WIFI/5.2GWIFI/5.8GWIFI Antenna
		5180~5240 MHz	2.0 dBi	
		5745~5825 MHz	2.0 dBi	
Antenna 2	FPC Antenna	2400-2500 MHz	-5.68 dBi	2.4G WIFI /5.2GWIFI/5.8GWIFI Antenna
		5180~5240 MHz	2.0 dBi	
		5745~5825 MHz	2.0 dBi	



**6. Conducted Power**

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	0.19
	39	2441	0.45
	78	2480	0.39
$\pi/4$ DQPSK	0	2402	-0.23
	39	2441	0.07
	78	2480	0.14
8DPSK	0	2402	-0.23
	19	2441	0.21
	39	2480	0.2

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE_1M	0	2402	0.9
	19	2440	0.78
	39	2480	-0.29

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	ANT 1 Peak Conducted Output Power (dBm)	ANT 2 Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	15.79	14.84
	6	2437	15.19	14.16
	11	2462	15.86	14.85
IEEE 802.11g	1	2412	14.09	13.11
	6	2437	14.59	13.29
	11	2462	14.45	13.32
IEEE 802.11n HT20	1	2412	13.58	12.74
	6	2437	13.82	12.87
	11	2462	13.76	12.8
IEEE 802.11n HT40	3	2422	13.22	12.21
	6	2437	12.96	11.03
	9	2452	12.88	11.32





## [5.2GHz WIFI]

Mode	Channel	Frequency (MHz)	ANT 1 Average Conducted Output Power (dBm)	ANT 2 Average Conducted Output Power (dBm)
IEEE 802.11a	36	5180	12.84	11.97
	40	5200	12.51	11.69
	48	5240	12.30	11.54
IEEE 802.11n HT20	36	5180	11.40	10.47
	40	5200	11.97	11.03
	48	5240	11.80	10.77
IEEE 802.11n HT40	38	5190	11.17	9.75
	46	5230	11.01	9.76
IEEE 802.11ac VHT20	36	5180	11.25	10.57
	40	5200	11.90	10.13
	48	5240	10.80	10.03
IEEE 802.11ac VHT40	38	5190	11.14	10.03
	46	5230	11.05	9.80
IEEE 802.11ac VHT80	42	5210	11.05	9.82

## [5.8GHz WIFI]

Mode	Channel	Frequency (MHz)	ANT 1 Average Conducted Output Power (dBm)	ANT 2 Average Conducted Output Power (dBm)
IEEE 802.11a	149	5745	12.30	11.81
	157	5785	12.46	11.15
	165	5825	12.70	11.42
IEEE 802.11n HT20	149	5745	11.59	10.92
	157	5785	11.36	10.25
	165	5825	11.72	10.64
IEEE 802.11n HT40	151	5755	11.15	10.26
	159	5795	10.74	9.79
IEEE 802.11ac VHT20	149	5745	11.68	10.70
	157	5785	11.39	10.37
	165	5825	11.80	10.68
IEEE 802.11ac VHT40	151	5755	11.15	10.28
	159	5795	10.78	9.74
IEEE 802.11ac VHT80	155	5775	10.31	9.40





7. Manufacturing Tolerance

GFSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance ± (dB)	1.0	1.0	1.0
π/4-DQPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance ± (dB)	1.0	1.0	1.0
8-DPSK(Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance ± (dB)	1.0	1.0	1.0

BT LE(Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance ± (dB)	1.0	1.0	1.0

2.4G WIFI for ANT1			
IEEE 802.11b(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11g(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40(Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	13.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0

2.4G WIFI for ANT2			
IEEE 802.11b(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11g(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40(Peak)			
Channel	Channel 03	Channel 06	Channel 09





Target (dBm)	12.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0

5.2G WIFI for ANT1			
IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT80(Average)			
Channel	Channel 42		
Target (dBm)	11.0		
Tolerance ± (dB)	1.0		

5.2G WIFI for ANT2			
IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	11.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	9.0	9.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	9.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT80(Average)			
Channel	Channel 42		
Target (dBm)	9.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Tolerance ± (dB)	1.0
------------------	-----

5.8G WIFI for ANT1			
IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	10.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	10.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT80(Average)			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance ± (dB)	1.0		

5.8G WIFI for ANT2			
IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	9.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	9.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT80(Average)			
Channel	Channel 155		
Target (dBm)	9.0		
Tolerance ± (dB)	1.0		







## 8. Measurement Results

### 8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
GFSK	1.0	1.2589	2.0	1.5849	0.0004	1.0000
$\pi/4$ -DQPSK	1.0	1.2589	2.0	1.5849	0.0004	1.0000
8-DPSK	1.0	1.2589	2.0	1.5849	0.0004	1.0000

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
BLE 1M	1.0	1.2589	2.0	1.5849	0.0004	1.0000

[2.4G WIFI for ANT1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11b	16.0	39.8107	2.0	1.5849	0.0126	1.0000
IEEE 802.11g	15.0	31.6228	2.0	1.5849	0.0100	1.0000
IEEE 802.11n HT20	14.0	25.1189	2.0	1.5849	0.0079	1.0000
IEEE 802.11n HT40	14.0	25.1189	2.0	1.5849	0.0079	1.0000

[2.4G WIFI for ANT2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11b	15.0	31.6228	2.0	1.5849	0.0100	1.0000
IEEE 802.11g	14.0	25.1189	2.0	1.5849	0.0079	1.0000
IEEE 802.11n HT20	13.0	19.9526	2.0	1.5849	0.0063	1.0000
IEEE 802.11n HT40	13.0	19.9526	2.0	1.5849	0.0063	1.0000

[5.2G WIFI for ANT1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	13.0	19.9526	2.0	1.5849	0.0063	1.0000
IEEE 802.11n HT20	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11n HT40	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	2.0	1.5849	0.0050	1.0000

[5.2G WIFI for ANT2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11n HT20	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11n HT40	10.0	10.0000	2.0	1.5849	0.0032	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT80	10.0	10.0000	2.0	1.5849	0.0032	1.0000



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI for ANT1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	13.0	19.9526	2.0	1.5849	0.0063	1.0000
IEEE 802.11n HT20	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11n HT40	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	2.0	1.5849	0.0040	1.0000

[5.8G WIFI for ANT2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	12.0	15.8489	2.0	1.5849	0.0050	1.0000
IEEE 802.11n HT20	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11n HT40	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT80	10.0	10.0000	2.0	1.5849	0.0032	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BT LE&2.4G WIFI&5.2G WIFI&5.8G WIFI Antenna, another one 2.4G WIFI&5.2G WIFI&5.8G WIFI Antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum \sum$  of MPE ratios  $\leq 1.0$

Antenna 1 MAX	Antenna 2 MAX	$\sum$ MPE ratios	Limit	Results
0.0126	0.0100	0.0226	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4.  $MPE\ values = PG/4\pi R^2$

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

