

RF Exposure Evaluation

LIMIT

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW, **G** = gain of antenna in linear scale;

Pi = 3.1416, **R** = distance between observation point and center of the radiator in cm

TEST RESULT

Passed

Not Applicable

Frequency range (MHz)	Type	Conducted Average Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
2402-2480	BT-EDR	10.39	11.00	0.005	1.0000	Pass
2402-2480	BT-BLE	9.24	10.00	0.004	1.0000	Pass
2412-2462	802.11 n(HT20)	13.30	14.00	0.01	1.0000	Pass
5150-5250	802.11 n(HT40)	17.21	18.00	0.0315	1.0000	Pass
5725-5825	802.11 n(HT20)	18.33	19.00	0.0397	1.0000	Pass

Consider the BT and wifi can transmitting simultaneously, the total transmitting MPE rate as below formula:
 $MPE\ rate = Power\ density\ of\ BT/limit + Power\ density\ of\ wifi/limit < 1$

The worst case is BT-EDR and 2.4G WIFI transmitting simultaneously, the result as below:

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BT-EDR	0.005	0.0447	1
5G WIFI	0.0397		

Note:

- 1) The maximum antenna gain is 3dBi (BT and 2.4G WiFi) and 4dBi (5G WiFi)
- 2) The exposure evaluation safety distance is 20cm.