


RF Exposure Evaluation Report

APPLICANT : Suzhou Aquila Solutions Inc.
EQUIPMENT : LTE Module
BRAND NAME : AQUILA
MODEL NAME : MG401
FCC ID : 2ASRY-MG401
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

We, Sporton International (Kunshan) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Reviewed by: Nick Hu / Supervisor



Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8
5.2. Collocated Power Density Calculation.....	9



1. Administration Data

1.1. Testing Laboratory

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Suzhou Aquila Solutions Inc.
Address	Room 201, Building 3, 18 Dongchang Road,Suzhou Industry ParkSuzhou, 215000 China

Manufacturer	
Company Name	Suzhou Aquila Solutions Inc.
Address	Room 201, Building 3, 18 Dongchang Road,Suzhou Industry ParkSuzhou, 215000 China



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	LTE Module
Brand Name	AQUILA
Model Name	MG401
FCC ID	2ASRY-MG401
Wireless Technology and Frequency Range	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 8: 897.5 MHz ~ 900.5 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 25: 1850.7 MHz ~ 1914.3 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 42: 3552.5 MHz ~ 3597.5 MHz LTE Band 43: 3602.5 MHz ~ 3697.5 MHz LTE Band 48: 3552.5 MHz ~ 3697.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz
Mode	LTE: QPSK, 16QAM
Antenna Type	PCB Antenna
HW Version	V1.2
SW Version	CAT4_GS_BYPASS_0.3.3.2_V1.4
EUT Stage	Identical Prototype

Remark:

1. LTE band 42/43 covered by LTE band 48 with the same power level, so only chose LTE band 48 to perform standalone power density calculation.
2. This is a variant report. The difference between current project and previous project is enabled LTE Band 8 by software. So according to the difference, added LTE Band 8 evaluation based on original report FA022705.



3. Maximum RF average output power among production units

Mode		Maximum Average power(dBm)
LTE	Band 2	25.00
	Band 4	25.00
	Band 5	24.00
	Band 8	25.00
	Band 12	24.00
	Band 13	25.00
	Band 14	25.00
	Band 17	24.00
	Band 25	25.00
	Band 26	22.00
	Band 41	25.00
	Band 42	23.00
	Band 43	23.00
	Band 48	23.00
Band 66	25.00	



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
LTE Band 2	1850.7	8.00	25.00	33.00	1995.26	0.397	1.000
LTE Band 4	1710.7	5.00	25.00	30.00	1000.00	0.199	1.000
LTE Band 5	824.7	6.00	24.00	30.00	1000.00	0.199	0.550
LTE Band 8	897.5	9.00	25.00	34.00	2511.89	0.500	0.598
LTE Band 12	699.7	5.00	24.00	29.00	794.33	0.158	0.466
LTE Band 13	779.5	5.00	25.00	30.00	1000.00	0.199	0.520
LTE Band 14	790.5	5.00	25.00	30.00	1000.00	0.199	0.527
LTE Band 17	706.5	5.00	24.00	29.00	794.33	0.158	0.471
LTE Band 25	1850.7	8.00	25.00	33.00	1995.26	0.397	1.000
LTE Band 26	814.7	6.00	22.00	28.00	630.96	0.126	0.543
LTE Band 41	2498.5	5.00	25.00	30.00	1000.00	0.199	1.000
LTE Band 48	3552.5	0.00	23.00	23.00	199.53	0.040	1.000
LTE Band 66	1710.7	5.00	25.00	30.00	1000.00	0.199	1.000

Note:

1. LTE band 42/43 covered by LTE band 48 with the same power level, so only chose LTE band 48 to perform standalone power density calculation.



5.2. Collocated Power Density Calculation

General Note:

- 1. This MPE analysis is applicable to any collocated transmitters with EIRP for WLAN is less than or equal to 28.0dBm and EIRP for Bluetooth is less than or equal to 20.0dBm.
2. A maximum antenna gain of 5dBi for WLAN/BT has been assumed for all collocated antennas.

Table with 9 columns: Band, Frequency (MHz), Antenna Gain (dBi), Maximum Power (dBm), Maximum EIRP (dBm), Average EIRP (mW), Power Density at 20cm (mW/cm^2), Limit (mW/cm^2), Power Density / Limit. Rows include LTE Bands 2, 4, 5, 8, 12, 13, 14, 17, 25, 26, 41, 48, 66, WLANA2.4GHz Band, WLANA5GHz Band, and Bluetooth.



<Collocated analysis>

General Note:

- 1. For collocation analysis, LTE Band 8 is chosen for summation due to the highest (power density/limit) among all WWAN wireless modes.
- 2. $\Sigma(\text{Power Density / Limit})$: This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + WLAN + Bluetooth
- 3. Considering the WWAN module collocation with the other transmitters of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 3 collocated transmitters is compliant.

Max WWAN Power Density / Limit	Max WLAN Power Density / Limit	Max Bluetooth Power Density / Limit	$\Sigma(\text{Power Density / Limit})$ of WWAN + WLAN + Bluetooth
0.836	0.126	0.020	0.982



Conclusion:

Based on 47 CFR §2.1091 and FCC KDB 447498 D01 v06, the analysis concludes that this product when transmitting in standalone within a host device, is compliant with the FCC RF exposure requirements in mobile exposure condition, provided the conducted power and antenna gain do not exceed the limits for each given frequency band per wireless technology as follow table:

Table with 6 columns: Device, Technology, Frequency (MHz), Maximum Conducted Power (dBm), Standalone Maximum Antenna Gain (dBi), Collocated Maximum Antenna Gain (dBi). Rows include MG401 (LTE Bands 2, 4, 5, 8, 12, 13, 14, 17, 25, 26, 41, 48, 66) and Collocated Transmitters (WLNA 2.4GHz Band, WLNA 5GHz Band, Bluetooth).