





RF Exposure Evaluation Report

FCC ID : 2AST4-JR1010621

Equipment : JRUN

Brand Name : JACFIT

Model Name : JR101

Applicant : JSPORTS TECHNOLOGY CO., LTD

Rm. 5, 9F., No.490, Sec. 2, Ren'ai Rd., Linkou Dist.,

New Taipei City 244020, Taiwan (R.O.C.)

Manufacturer : Chen Wei Electronics inc.

No.12, Nanyuan Rd., Zhongli Dist., Taoyuan City

32063, Taiwan (R.O.C.)

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on May 21, 2021, and testing was started from May 28, 2021 and completed on May 31, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5
FAX: 886-3-327-0973 Issued Date : Jul. 08, 2021

Report Template No.: HE1-A3 Ver4.0 FCC ID: 2AST4-JR1010621

Report Version : 02



Table of Contents

1.	Gene	eral Description	. 4
	1.1	Information	.4
	1.1.1	EUT General Information	.4
	1.1.2	Antenna Information	4
	1.1.3	Accessories	4
	1.2	Testing Location Information	. 4
2.	RF E	xposure Evaluation	. (
		plicable Standard	
	2.2 SA	R evaluation	5

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973 Report Template No.: HE1-A3 Ver4.0

FCC ID: 2AST4-JR1010621

Page Number : 2 of 5 Issued Date : Jul. 08, 2021

Report Version : 02



History of This Test Report

Report No.	Version	Description	Issued Date
FA152111	01	Initial issue of report	Jun. 29, 2021
FA152111	02	Exposure Evaluation was re-evaluated. This report is the latest version replacing for the report issued on Jun. 29, 2021.	Jul. 08, 2021

Reviewed by: Sam Tsai

Report Producer: Amber Chiu

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Jul. 08, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 02

FCC ID: 2AST4-JR1010621



1. General Description

1.1 Information

1.1.1 EUT General Information

		RF Gene	ral Information
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth 2400-2483.5 2402-2480 LE: DSSS (GFSK)		LE: DSSS (GFSK)	

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Chip Antenna	N/A	1.54

Note 1: The EUT has one antenna.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Only Ant. 1 can be used as transmitting/receiving antenna.

1.1.3 Accessories

Accessories						
	Brand Name	Mitsubishi Electric	Model Name	CR2032		
Battery	Power Rating	3Vdc, 0.2mAh	Туре	Li-ion, N		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Testing Location Information

Tes	Test Lab. : Sporton International Inc. Hsinhua Laboratory						
\boxtimes	Hsinhua	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)					
	(TAF: 3785)	785) TEL : 886-3-327-3456 FAX : 886-3-327-0973					
	Test site Designation No. TW3785 with FCC.						
	Wen 33rd.St. ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)						
	(TAF: 3785) TEL: 886-3-318-0787 FAX: 886-3-318-0287						
	Test site Designation No. TW0008 with FCC.						

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Jul. 08, 2021

Report Version

: 02

Report Template No.: HE1-A3 Ver4.0

FCC ID: 2AST4-JR1010621



2. RF Exposure Evaluation

2.1 Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2 SAR evaluation

Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
 [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•
 [√f (GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

• f_(GHz) is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Tolerance	Tune-up Max. Power		Test Distance	Frequency	Exclusion
(dBm)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
-1.22	0.5	-0.72	0.85	5	2.402	0.26

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 0.26 < 7.5, RF exposure evaluation is not required.

_____THE END____

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Jul. 08, 2021

FCC ID: 2AST4-JR1010621

Report Template No.: HE1-A3 Ver4.0 Report Version : 02