



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20210400549E-03  
**Applicant:** Shenzhen Leaderment Technology Co.,Ltd  
**Address of Applicant:** 1st Floor, Building 24, Longcheng Industrial Zone, No. 39 Longguan West Road , Gaofeng Community, Dalang Street, Longhua District, Shenzhen  
**Equipment Under Test (EUT):**  
**EUT Name:** Selfie Stick Tripod  
**Model No.:** ATSS082, ATSS084, ATSS091, ATSS092, ATSS093, ATSS094, ATSS095, ATSS096, ATSS097, ATSS098  
**Test Model No.:** ATSS082  
**Brand Name:** ATUMTEK  
**FCC ID:** 2ASUP- ATSS082  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2021-04-26  
**Date of Test:** 2021-04-26 to 2021-05-24  
**Date of Issue:** 2021-05-24  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

*Lewis Zhou*

(Lewis Zhou)

**Reviewed By:**

*Jun Li*

(Jun Li)

**Approved By:**

*Sheek Luo*

( Sheek Luo)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210400549E-03	Rev.01	Initial report	2021-05-24

## 2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Leaderment Technology Co.,Ltd
Address of Applicant:	1st Floor, Building 24, Longcheng Industrial Zone, No. 39 Longguan West Road, Gaofeng Community, Dalang Street, Longhua District, Shenzhen
Manufacturer:	Shenzhen Leaderment Technology Co.,Ltd
Address of Manufacturer:	1st Floor, Building 24, Longcheng Industrial Zone, No. 39 Longguan West Road, Gaofeng Community, Dalang Street, Longhua District, Shenzhen
Factory:	Shenzhen Yuansu Chuangda Technology Co.,Ltd
Address of Factory:	Room 533, Huamei Building, Zhenxing Road, Futian District, Shenzhen City

#### 3.2 General Description of EUT

Product Name:	Selfie Stick Tripod
Model No.:	ATSS082, ATSS084, ATSS091, ATSS092, MATSS093, ATSS094, ATSS095, ATSS096, ATSS097, ATSS098
Test Model No.:	BFSITO-260
Trade Mark:	WOLONOW
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Lekit_200927.exe (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-3.01 dBi
EUT Power Supply:	DC3.3V

Note:

All model: ATSS082, ATSS084, ATSS091, ATSS092, MATSS093, ATSS094, ATSS095, ATSS096, ATSS097, ATSS098

Only the model ATSS082 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

##### 1) For BLE(1Mbps)

##### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.11	0±1	1	1.259
Middle(2440MHz)	0.80	0±1	1	1.259
Highest(2480MHz)	1.06	0.5±1	1.5	1.413

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.11	0±1	1	1.259	0.390	3.0
Middle (2440MHz)	0.80	0±1	1	1.259	0.393	
Highest (2480MHz)	1.06	0.5±1	1.5	1.413	0.445	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20210400549E-01

2) For BLE(2Mbps)

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.29	0±1	1	1.259
Middle(2440MHz)	0.93	0±1	1	1.259
Highest(2480MHz)	1.21	0.5±1	1.5	1.413

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	0.29	0±1	1	1.259	0.390	3.0
Middle (2440MHz)	0.93	0±1	1	1.259	0.393	
Highest (2480MHz)	1.21	0.5±1	1.5	1.413	0.445	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20210400549E-02