

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Toy RC Motorhead Closed Wheel 8inch With Titan Head And Mystery Head operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V Rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -15.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -15.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 79.3 dBμV/m at 3m in the frequency 2475MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -15.93dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 78.4 dBμV/m at 3m in the frequency 2405MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -16.83dBm

which is within the production variation.

The maximum conducted output power specified is -12dBm= 0.063mW

The source- based time-averaging conducted output power

= $0.063 \cdot \text{Duty cycle}$ mW < 0.063 mW (Duty cycle < 100%)

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 \cdot 5 / \sqrt{2.475}$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 3.8913ms

Effective period of the cycle = $152.2\mu\text{s} \times 7 + 1.014\mu\text{s} = 1.066\text{ms}$

DC = $1.066\text{ms} / 3.8913\text{ms} = 0.2739$ or 27.39%