

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an Drone Xtreme Airwave operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 97.2dB $\mu$ V/m at 3m in the frequency 2479MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 1.97dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 95.9dB $\mu$ V/m at 3m in the frequency 2451MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 0.67dBm  
which is within the production variation.

The maximum conducted output power specified is 4.0dBm= 2.512mW

The source- based time-averaging conducted output power  
=2.512mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt} (2.479)$  mW

= 9.52 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2ASUSZS-WLSL002T24G