




FCC PART 95  
MEASUREMENT AND TEST REPORT

For

**Shenzhen Beijia Electronic Technology Co., Ltd.**

2/F, No. 20, Xinkang 2nd Road, Shatian Community, Kengzi Street, Pingshan District, Shenzhen, China

**FCC ID: 2ASV6-T8**

<b>Report Type:</b> Original Report	<b>Product Type:</b> WALKIE TALKIE
<b>Report Number:</b> <u>RSZ200721010-00</u>	
<b>Report Date:</b> <u>2020-08-25</u>	
Jimmy Xiao 	
<b>Reviewed By:</b> <u>RF Engineer</u>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....3**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

    OBJECTIVE .....3

    RELATED SUBMITTAL(S)/GRANT(S).....3

    TEST METHODOLOGY .....3

    MEASUREMENT UNCERTAINTY .....4

    TEST FACILITY .....4

**SYSTEM TEST CONFIGURATION.....5**

    DESCRIPTION OF TEST CONFIGURATION .....5

    EQUIPMENT MODIFICATIONS .....5

    SUPPORT EQUIPMENT LIST AND DETAILS .....5

    BLOCK DIAGRAM OF TEST SETUP .....6

**SUMMARY OF TEST RESULTS .....7**

**TEST EQUIPMENT LIST .....8**

**§2.1093 - RF EXPOSURE INFORMATION .....9**

    APPLICABLE STANDARD .....9

    TEST RESULT .....9

**FCC §95.587(b)(1) – ANTENNA REQUIREMENT .....10**

    APPLICABLE STANDARD .....10

    ANTENNA CONNECTOR CONSTRUCTION .....10

**FCC §2.1046 & §95.567 - RF OUTPUT POWER.....11**

    APPLICABLE STANDARD .....11

    TEST PROCEDURE .....11

    TEST DATA .....11

**FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC .....12**

    APPLICABLE STANDARD .....12

    TEST PROCEDURE .....12

    TEST DATA .....12

**FCC §2.1049 & §95.573 - AUTHORIZED BANDWIDTH AND EMISSION MASK.....23**

    APPLICABLE STANDARD .....23

    TEST PROCEDURE .....23

    TEST DATA .....23

**FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION .....26**

    APPLICABLE STANDARD .....26

    TEST PROCEDURE .....26

    TEST DATA .....26

**FCC§2.1055 (d) & §95.565 - FREQUENCY STABILITY .....28**

    APPLICABLE STANDARD .....28

    TEST PROCEDURE .....28

    TEST DATA .....28

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

Product	WALKIE TALKIE
Tested Model	T8A
Multiple Model	T8, T8B, T9, SC-R60
Model Differences	Refer to the DoS letter
Frequency Range	462.5500~462.7250MHz 467.5625~467.7125MHz
Transmit Power (ERP)	462.5500~462.7250MHz :17.78dBm 467.5625~467.7125MHz: 14.02dBm
Channel Spacing	12.5kHz
Modulation Technique	FM
Antenna Specification	-9.7dBi
Voltage Range	DC 1.5V*4 AAA Batteries
Date of Test	2020-08-03 to 2020-08-04
Sample serial number	RSZ200721010-RF-S1(Assigned by BACL, Shenzhen)
Received date	2020-07-21
Sample/EUT Status	Good condition

### Objective

This report is prepared on behalf of Shenzhen Beijia Electronic Technology Co., Ltd. in accordance with Part 2 and Part 95, Subpart A & Subpart B of the Federal Communication Commissions rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart A, Subpart B of the Federal Communication Commissions rules with TIA-603-E, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

FRS Channel List

Channel No.	Channel Frequency (MHz)	Channel No.	Channel Frequency (MHz)
1	462.5625	12	467.6625
2	462.5875	13	467.6875
3	462.6125	14	467.7125
4	462.6375	15	462.5500
5	462.6625	16	462.5750
6	462.6875	17	462.6000
7	462.7125	18	462.6250
8	467.5625	19	462.6500
9	467.5875	20	462.6750
10	467.6125	21	462.7000
11	467.6375	22	462.7250


### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

**Block Diagram of Test Setup**



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Results</b>
§2.1093	RF Exposure	Compliance
§95.587(b)(1)	Antenna Requirement	Compliance
§2.1046, §95.567	RF Output Power	Compliance
§2.1047, §95.575	Modulation Characteristic	Compliance
§2.1049, §95.573	Authorized Bandwidth & Emission Mask	Compliance
§2.1053, §95.579	Spurious Radiated Emissions	Compliance
§2.1055(d), §95.565	Frequency Stability	Compliance

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
COM-POWER	Dipole Antenna	AD-100	41000	NCR	NCR
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
A.H.System	Horn Antenna	SAS-200/571	135	2018/09/01	2021/08/31
Insulated Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
Agilent	Signal Generator	N5183A	MY51040755	2019/12/04	2020/12/04
<b>RF Conducted test</b>					
HP Agilent	RF Communication test set	8920A	3325UC0859	2020/07/31	2021/07/30
WEINSCHEL	10dB Attenuator	5324	AU3842	2019/11/29	2020/11/28
HP	Microwave frequency counter	5343A	2232A00827	2019/8/29	2022/8/29
Fluke	Digital Multimeter	287	19000011	2020/07/23	2021/07/22
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2019/12/25	2020/12/24
instek	DC Power Supply	GPS-3030DD	EM832096	NCR	NCR
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2020/04/03	2021/04/02
Ducommun Technologies	RF Cable	RG-214	3	Each Time	

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).



## **§2.1093 - RF EXPOSURE INFORMATION**

---

### **Applicable Standard**

§2.1093.

### **Test Result**

Pass, please refer to the SAR report: RSZ200721010-20A.

---

## **FCC §95.587(b)(1) – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 95.587, (b) Antenna. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

### **Antenna Connector Construction**

The EUT has an integral antenna arrangement and the antenna gain is -9.7dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result: Pass**

## FCC §2.1046 & §95.567 - RF OUTPUT POWER

### Applicable Standard

Per FCC §2.1046, and §95.567, Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Harris He on 2020-08-04.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Ant.		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Substituted level (dBm)	Cable Loss (dB)	Ant. Gain (dBd)			
<b>462.6375MHz</b>										
462.6375	81.24	254	1.8	H	6.4	1.32	0.0	5.08	33	27.92
462.6375	89.61	300	2.1	V	19.1	1.32	0.0	17.78	33	15.22
<b>467.6375MHz</b>										
467.6375	79.71	244	1.5	H	4.2	1.28	0.0	2.92	27	24.08
467.6375	86.92	277	2.2	V	15.3	1.28	0.0	14.02	27	12.98

**Test Result: Pass**

---

**FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC**

---

**Applicable Standard**

Per FCC §2.1047 and §95.575: Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

**Test Procedure**

Test Method: TIA/EIA-603-E

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Black Chen on 2020-08-03.*


*Test Mode: Transmitting*

*Please refer to the following tables and plots.*

**MODULATION LIMITING**


Carrier Frequency: 462.6375MHz

Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	0.600	0.069	0.633	0.077	2.500
400	0.829	0.074	0.887	0.085	2.500
500	1.079	0.098	1.123	0.105	2.500
600	1.325	0.110	1.387	0.119	2.500
700	1.401	0.124	1.454	0.129	2.500
800	1.625	0.143	1.636	0.157	2.500
900	1.813	0.159	1.857	0.168	2.500
1000	1.909	0.185	1.916	0.193	2.500
1200	2.049	0.206	2.068	0.215	2.500
1400	2.070	0.243	2.093	0.239	2.500
1600	2.119	0.262	2.168	0.267	2.500
1800	2.137	0.285	2.157	0.288	2.500
2000	2.139	0.326	2.169	0.324	2.500
2100	2.167	0.330	2.189	0.329	2.500
2200	2.155	0.331	2.133	0.316	2.500
2300	2.150	0.342	2.125	0.336	2.500
2400	2.182	0.361	2.139	0.344	2.500
2500	2.161	0.381	2.119	0.362	2.500
2600	2.154	0.385	2.126	0.377	2.500
2700	2.138	0.381	2.169	0.398	2.500
2800	2.133	0.395	2.178	0.412	2.500
2900	2.151	0.422	2.159	0.438	2.500
3000	2.132	0.406	2.169	0.411	2.500



Carrier Frequency: 462.6375 MHz

<b>Audio Frequency (Hz)</b>	<b>Response Attenuation (dB)</b>
300	-11.63
400	-8.50
500	-6.41
600	-4.35
700	-3.35
800	-2.36
900	-1.05
1000	0.00
1200	1.27
1400	2.61
1600	3.76
1800	4.32
2000	5.46
2100	5.59
2200	5.80
2300	6.03
2400	6.58
2500	7.18
2600	7.17
2700	7.23
2800	7.41
2900	7.94
3000	7.68






**Audio frequency lows pass filter response**

Carrier Frequency: 462.6375 MHz


Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-15.36	0.0
4.0	-73.60	-12.5
5.0	-84.21	-22.2
6.0	-85.13	-30.1
7.0	-85.89	-36.8
8.0	-87.03	-42.6
9.0	-86.59	-47.7
10.0	-85.30	-52.3
15.0	-87.75	-69.9
20.0	-87.34	-82.5
30.0	-85.75	-82.5
40.0	-89.40	-82.5
50.0	-91.45	-82.5
60.0	-93.36	-82.5
70.0	-93.78	-82.5



**MODULATION LIMITING**


Carrier Frequency: 467.6375MHz

Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	0.848	0.056	1.756	0.055	2.500
400	1.124	0.070	2.048	0.075	2.500
500	1.333	0.085	2.035	0.101	2.500
600	1.582	0.102	2.246	0.107	2.500
700	1.751	0.112	1.715	0.121	2.500
800	1.967	0.132	1.852	0.127	2.500
900	2.041	0.144	2.045	0.151	2.500
1000	2.118	0.165	2.155	0.164	2.500
1200	2.311	0.187	2.133	0.204	2.500
1400	2.350	0.197	2.086	0.239	2.500
1600	2.341	0.234	1.964	0.276	2.500
1800	2.347	0.257	1.911	0.312	2.500
2000	2.433	0.311	2.010	0.331	2.500
2100	2.416	0.312	1.931	0.355	2.500
2200	2.415	0.321	2.016	0.369	2.500
2300	2.407	0.324	1.918	0.387	2.500
2400	2.411	0.344	2.045	0.444	2.500
2500	2.431	0.354	2.088	0.461	2.500
2600	2.418	0.355	1.969	0.464	2.500
2700	2.310	0.361	1.961	0.475	2.500
2800	2.388	0.395	1.918	0.491	2.500
2900	2.445	0.443	1.922	0.467	2.500
3000	2.382	0.454	1.915	0.465	2.500



Carrier Frequency: 467.6375 MHz


<b>Audio Frequency (Hz)</b>	<b>Response Attenuation (dB)</b>
300	-13.72
400	-9.17
500	-6.86
600	-5.13
700	-3.22
800	-2.23
900	-1.05
1000	0.00
1200	1.95
1400	3.44
1600	4.64
1800	5.77
2000	6.70
2100	7.20
2200	7.65
2300	7.99
2400	8.37
2500	8.66
2600	8.94
2700	9.16
2800	9.41
2900	9.55
3000	9.62



**Audio frequency lows pass filter response**

Carrier Frequency: 467.6375 MHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-14.3	0.0
4.0	-73.5	-12.5
5.0	-85.7	-22.2
6.0	-86.7	-30.1
7.0	-84.9	-36.8
8.0	-88.8	-42.6
9.0	-88.0	-47.7
10.0	-86.8	-52.3
15.0	-87.3	-69.9
20.0	-88.3	-82.5
30.0	-89.6	-82.5
40.0	-92.6	-82.5
50.0	-90.4	-82.5
60.0	-88.6	-82.5
70.0	-88.6	-82.5



## FCC §2.1049 & §95.573 - AUTHOURIZED BANDWIDTH AND EMISSION MASK

### Applicable Standard

According to §95.573. Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

### Test Procedure

TIA-603-E, section 2.2.11

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Black Chen on 2020-08-03.*


*Test Mode: Transmitting*

Modulation	Channel Separation (kHz)	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
FM	12.5	462.6375	9.856	10.337
FM	12.5	467.6375	9.535	10.817

Emission Designator Per CFR 47 §2.201& §2.202&,  $B_n = 2M + 2D$ :


Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.  $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$   
 F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

**OBW, 462.6375 MHz**



Date: 3.AUG.2020 22:57:32


**Emission Mask, 462.6375 MHz**



Date: 3.AUG.2020 22:43:38




**OBW, 467.6375 MHz**



Date: 3.AUG.2020 22:55:31

**Emission Mask, 467.6375 MHz**



Date: 3.AUG.2020 22:54:09

## FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION

### Applicable Standard

FCC §2.1053 and §95.579. Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

- (1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
- (2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
- (3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

### Test Procedure

The transmitter was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =  $10 \lg (\text{TXpwr in Watts}/0.001)$  - the absolute level  
Spurious attenuation limit in dB =  $43 + 10 \text{Log}_{10} (\text{power out in Watts})$

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Harris He on 2020-08-04 for below 1GHz and Lovan Liang on 2020-08-04 for above 1GHz.*

*Test Mode: Transmitting*

Indicated		Table Angle Degree	Test Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	Receiver Reading (dBuV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)			
<b>462.6375MHz</b>										
925.275	44.72	128	2.4	H	-55.9	1.31	0.0	-57.21	-13	44.21
925.275	54.51	137	2.2	V	-44.8	1.31	0.0	-46.11	-13	33.11
1387.91	56.93	235	1.9	H	-51.4	1.60	7.90	-45.10	-13	32.10
1387.91	51.49	304	1.1	V	-57.1	1.60	7.90	-50.80	-13	37.80
1850.55	50.60	162	1.2	H	-52.7	1.30	9.40	-44.60	-13	31.60
1850.55	47.22	296	1.4	V	-56.3	1.30	9.40	-48.20	-13	35.20
2313.19	56.14	57	2.3	H	-49.8	1.30	10.00	-41.10	-13	28.10
2313.19	61.58	39	1.8	V	-44.3	1.30	10.00	-35.60	-13	22.60
2775.83	46.49	355	1.3	H	-58.1	1.80	10.50	-49.40	-13	36.40
2775.83	46.97	197	1.9	V	-57.2	1.80	10.50	-48.50	-13	35.50
3238.46	48.03	180	2.1	H	-52.8	1.60	11.50	-42.90	-13	29.90
3238.46	48.42	176	1.2	V	-52.7	1.60	11.50	-42.80	-13	29.80
3701.10	52.85	55	2.3	H	-49.9	1.60	11.90	-39.60	-13	26.60
3701.10	48.56	155	1.2	V	-53.6	1.60	11.90	-43.30	-13	30.30
<b>467.6375 MHz</b>										
935.275	50.78	145	1.3	H	-49.8	1.31	0.0	-51.11	-13	38.11
935.275	57.69	312	2.3	V	-41.7	1.31	0.0	-43.01	-13	30.01
1402.91	59.29	183	2.2	H	-49.0	1.60	7.90	-42.70	-13	29.70
1402.91	55.53	340	1.5	V	-53.0	1.60	7.90	-46.70	-13	33.70
2338.19	58.26	305	2.2	H	-47.7	1.30	10.00	-39.00	-13	26.00
2338.19	61.45	87	1.3	V	-44.4	1.30	10.00	-35.70	-13	22.70

**Note 1:** The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

**Note 2:** Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

## **FCC§2.1055 (d) & §95.565 - FREQUENCY STABILITY**

### **Applicable Standard**

According to FCC §2.1055(a) (1), the frequency stability shall be measured with variation of ambient temperature from  $-30\text{ }^{\circ}\text{C}$  to  $+50\text{ }^{\circ}\text{C}$ , and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.565, Each FRS transmitter type must be designed such that the carrier frequencies remain within  $\pm 2.5$  parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

### **Test Procedure**

**Frequency Stability vs. Temperature:** The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage (item 1 or item 2 will be chosen according to different condition) :

1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	20 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Black Chen on 2020-08-03.*

*Test Mode: Transmitting*

**FRS**

<b>Reference Frequency: 462.6375 MHz, Limit: ±2.5 ppm</b>			
<b>Environment Temperature (°C)</b>	<b>Power Supplied (V<sub>DC</sub>)</b>	<b>Measurement Frequency (MHz)</b>	<b>Frequency Error (ppm)</b>
Frequency Stability Ver. Temperature			
50	6.0	462.637256	-0.53
40	6.0	462.637261	-0.52
30	6.0	462.637263	-0.51
20	6.0	462.637242	-0.56
10	6.0	462.637269	-0.50
0	6.0	462.637276	-0.48
-10	6.0	462.637259	-0.52
-20	6.0	462.637281	-0.47
-30	6.0	462.637244	-0.55
Frequency Stability Ver. Input Voltage			
20	5.0	462.637253	-0.53
20	6.6	462.637261	-0.52

<b>Reference Frequency: 467.6375 MHz, Limit: ±2.5 ppm</b>			
<b>Environment Temperature (°C)</b>	<b>Power Supplied (V<sub>DC</sub>)</b>	<b>Measurement Frequency (MHz)</b>	<b>Frequency Error (ppm)</b>
Frequency Stability Ver. Temperature			
50	6.0	467.637262	-0.51
40	6.0	467.637253	-0.53
30	6.0	467.637266	-0.50
20	6.0	467.637267	-0.50
10	6.0	467.637269	-0.49
0	6.0	467.637274	-0.48
-10	6.0	467.637271	-0.49
-20	6.0	467.637247	-0.54
-30	6.0	467.637258	-0.52
Frequency Stability Ver. Input Voltage			
20	5.0	467.637273	-0.49
20	6.6	467.637277	-0.48

**\*\*\*\*\* END OF REPORT \*\*\*\*\***