



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190500020EX-02
Applicant: MAYFLASH LIMITED
Address of Applicant: 3/F, Buiding No.1, TingWei Industrial Park, LiuFang Rd, No.67, BaoAn, Shenzhen, China.
Manufacturer: MAYFLASH LIMITED
Address of Manufacturer: 3/F, Buiding No.1, TingWei Industrial Park, LiuFang Rd, No.67, BaoAn, Shenzhen, China.
Equipment Under Test (EUT):
Product: MAGIC-NS
Model No.: MAGIC-NS
Brand Name: N/A
FCC ID: 2ASVQ-MAGICNS
Standards: 47 CFR Part 15, Subpart C
Date of Test: May 10, 2019 to May 30, 2019
Date of Issue: May 30, 2019
Test Result : PASS*

Tested By:

(Daisy Qin)

Reviewed By:

(Aaron Ma)

Approved By:

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190500020EX-02	Rev.01	Initial report	May 30, 2019

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	MAYFLASH LIMITED
Address of Applicant:	3/F, Buiding No.1, TingWei Industrial Park, LiuFang Rd, No.67, BaoAn, Shenzhen, China.
Manufacturer:	MAYFLASH LIMITED
Address of Manufacturer:	3/F, Buiding No.1, TingWei Industrial Park, LiuFang Rd, No.67, BaoAn, Shenzhen, China.

3.2 General Description of EUT

Product Name:	MAGIC-NS
Test Model No.:	MAGIC-NS
Trade Mark:	N/A
Hardware Version:	V 2.0
Software Version:	V 1.26
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2/ EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi
EUT Power Supply:	DC 5V from PC

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right]^* \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

2) For EDR/BDR

Measurement Data

GFSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	3.761	4.0	4	2.512	0.779	3.0
Middle (2441MHz)	2.744	3.0	3	1.995	0.623	
Highest (2480MHz)	4.118	4.5	4.5	2.818	0.888	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

$\pi/4$ DQPSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	3.871	4.0	4	2.512	0.779	3.0
Middle (2441MHz)	2.766	3.0	3	1.995	0.623	
Highest (2480MHz)	4.147	4.5	4.5	2.818	0.888	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

8DPSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	3.947	4.0	4	2.512	0.779	3.0
Middle (2441MHz)	2.808	3.0	3	1.995	0.623	
Highest (2480MHz)	4.163	4.5	4.5	2.818	0.888	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190500020EX-01