



RF EXPOSURE EVALUATION METHOD

FCC ID: 2ASVQ-MAGICSPRO2

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT

BT 1M			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	-0.712	0.849
CH39	2441	-0.926	0.808
CH78	2480	-0.655	0.860
BT 2M			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	-0.801	0.832
CH39	2441	-0.739	0.844
CH78	2480	-0.624	0.866
BT 3M			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	-0.379	0.916
CH39	2441	-0.307	0.932
CH78	2480	-0.094	0.979

Remark: The best case gain of the antenna is 2dBi.

0 dBi logarithmic terms convert to numeric result is nearly 1.00

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test



separation distances ≤ 50 mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}]$$

BT

Test Channel	max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit
BT 1M						
CH00	-0.712	0.849	5	2.402	0.263	3
CH19	-0.926	0.808	5	2.441	0.252	3
CH39	-0.655	0.860	5	2.480	0.271	3
BT 2M						
CH00	-0.801	0.832	5	2.402	0.258	3
CH19	-0.739	0.844	5	2.441	0.264	3
CH39	-0.624	0.866	5	2.480	0.273	3
BT 3M						
CH00	-0.379	0.916	5	2.402	0.284	3
CH19	-0.307	0.932	5	2.441	0.291	3
CH39	-0.094	0.979	5	2.480	0.308	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.