

| | | - | |
|--|---|--|--|
| IE | SI REPOR | | |
| | For Bluetooth-EDR | | |
| Report No: | CHTEW22050110 | Report Verificati | on: |
| Project No | SHT2203115005EW | | |
| FCC ID | 2ASWW-GT20 | | |
| Applicant's name: | XINCHUANGXIN INTERNA | TIONAL CO.,LTI | D |
| Address: | ROOM 605 6/F, FA YUEN C YUEN STREET MONGKOK | OMMERCIAL BU KL | JILDING, 75-77 FA |
| Product Name: | Feature Phone | | |
| Trade Mark | CORN | | |
| Model No | GT20 | | |
| Listed Model(s) | - | | |
| Standard: | FCC CFR Title 47 Part 15 S | ubpart C Sectio | on 15.247 |
| Date of receipt of test sample: | Apr. 28, 2022 | | |
| Date of testing | Apr. 29, 2022- May. 17, 2022 | 2 | |
| Date of issue: | May. 18, 2022 | | |
| Result: | PASS | | |
| Compiled by (Position+Printed name+Signature): | File administrator Silvia Li | 5 | silvia Li |
| Supervised by (Position+Printed name+Signature): | Project Engineer David Cher | 1 | David Chen |
| Approved by (Position+Printed name+Signature): | RF Manager Hans Hu | ł | tomstu |
| Testing Laboratory Name: | Shenzhen Huatongwei Inte | rnational Inspe | ction Co., Ltd. |
| Address | 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China | | |
| Shenzhen Huatongwei International Inspe | ction Co., Ltd. All rights reserv | ed. | |
| Huatongwei International Inspection Co., Ltd. Shenzhen Huatongwei International Inspection damages resulting from the reader's interpret | or in part for non-commercial pu is acknowledged as copyright or on Co., Ltd. takes no responsibilit tation of the reproduced material | rposes as long as wner and source o y for and will not a due to its placeme | the Shenzhen f the material. ssume liability for nt and context |

The test report merely correspond to the test sample.

Contents

| 1. | TEST STANDARDS AND REPORT VERSION | 3 |
|--------------|---|--------|
| 1.1. 1.2. | Test Standards Report version | 3 3 |
| 2. | TEST DESCRIPTION | 4 |
| 3. | SUMMARY | 5 |
| 3.1. | Client Information | 5 |
| 3.2. | Product Description | 5 |
| 3.3. | Radio Specification Description | 5 |
| 3.4. | Testing Laboratory Information | 6 |
| 4. | TEST CONFIGURATION | 7 |
| 4.1. | Test frequency list | 7 |
| 4.2. | Descriptions of Test mode | 7 |
| 4.3. | Test mode | 7 |
| 4.4. | Test sample information | 8 |
| 4.5. | Support unit used in test configuration and system | 8 |
| 4.6. | lesting environmental condition | 8 |
| 4.7. | Statement of the measurement uncertainty | 8 |
| 4.8. | Equipment Used during the Test | 9 |
| 5. | TEST CONDITIONS AND RESULTS | 11 |
| 5.1. | Antenna Requirement | 11 |
| 5.2. | AC Conducted Emission | 12 |
| 5.3. | Peak Output Power | 14 |
| 5.4. | 20 dB Bandwidth | 15 |
| 5.5. | 99% Occupied Bandwidth | 16 |
| 5.6. | Carrier Frequencies Separation | 17 |
| 5.7. | Hopping Channel Number | 18 |
| 5.8. | Dwell Time | 19 |
| 5.9. | Duty Cycle Correction Factor (DCCF) | 20 |
| 5.10. | Pseudorandom Frequency Hopping Sequence | 21 |
| 5.11. | Conducted Band edge and Spurious Emission | 22 |
| 5.1Z. | Radiated Band edge Emission Rediated Sourieue Emission | 24 |
| 5.13. | Radiated Spurious Emission | 20 |
| 6. | TEST SETUP PHOTOS | 32 |
| 7. | EXTERANAL AND INTERNAL PHOTOS | 33 |
| 8. | APPENDIX REPORT | 33 |

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- <u>FCC Rules Part 15.247</u>: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- <u>ANSI C63.10:2013</u>: American National Standard for Testing Unlicensed Wireless Devices
- KDB 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

| Revision No. | Date of issue | Description |
|--------------|---------------|-------------|
| N/A | 2022-05-18 | Original |
| | | |
| | | |
| | | |
| | | |

2. TEST DESCRIPTION

| Report clause | Test Items | Standard Requirement | Result | Test Engineer |
|------------------|--|-------------------------|--------------------|---------------|
| 5.1 | Antenna Requirement | 15.203/15.247 (c) | PASS | Xiaoqin Li |
| 5.2 | AC Conducted Emission | 15.207 | PASS | Xiaoqin Li |
| 5.3 | Peak Output Power | 15.247 (b)(1) | PASS | Xiaoqin Li |
| 5.4 | 20 dB Bandwidth | 15.247 (a)(1) | PASS | Xiaoqin Li |
| 5.5 | 99% Occupied Bandwidth | - | PASS ^{*1} | Xiaoqin Li |
| 5.6 | Carrier Frequency Separation | 15.247 (a)(1) | PASS | Xiaoqin Li |
| 5.7 | Hopping Channel Number | 15.247 (a)(1) | PASS | Xiaoqin Li |
| 5.8 | Dwell Time | 15.247 (a)(1) | PASS | Xiaoqin Li |
| 5.9 | Duty Cycle Correction Factor | - | PASS ^{*1} | Xiaoqin Li |
| 5.10 | Pseudorandom Frequency Hopping Sequence | 15.247(b)(4) | PASS | Xiaoqin Li |
| 5.11 | Conducted Band Edge and Spurious Emission | 15.247(d)/15.205 | PASS | Xiaoqin Li |
| 5.12 | Radiated Band Edge Emission | 15.205/15.209 | PASS | Pan Xie |
| 5.13 | Radiated Spurious Emission | 15.247(d)/15.205/15.209 | PASS | Pan Xie |

Note:

- The measurement uncertainty is not included in the test result.

*1: No requirement on standard, only report these test data.

2022-05-18

3.1. Client Information

| Applicant: | XINCHUANGXIN INTERNATIONAL CO.,LTD | |
|---------------|---|--|
| Address: | ROOM 605 6/F, FA YUEN COMMERCIAL BUILDING, 75-77 FA YUEN STREET MONGKOK KL | |
| Manufacturer: | Shenzhen Chiteng Technology Co.,LTD | |
| Address: | Second Floor,Area A, Building 4, Huiye Technology Workshop, Guanguang Road, Tangjia Community, Gongming Street, Guangming New District, Shenzhen, Guangdong | |

3.2. Product Description

| Main unit information: | |
|-----------------------------|--|
| Product Name: | Feature Phone |
| Trade Mark: | CORN |
| Model No.: | GT20 |
| Listed Model(s): | - |
| Power supply: | DC 3.7V from battery |
| Hardware version: | ZS583T_MB_V1.1 |
| Software version: | ZS583T_128160_A18307_GT20_CORN_EnFrPoSp_V01 |
| Accessory unit information: | |
| Battery information: | 3.7Vdc, 1000mAh |
| Adapter information: | Model:FSF-01 Input: AC100-240V, 50/60Hz, 0.15A Output: 5.0Vdc, 500mA |

3.3. Radio Specification Description

| Bluetooth version: | V2.1 |
|----------------------------------|-----------------------|
| Support function ^{*2} : | EDR |
| Modulation: | GFSK, π/4DQPSK, 8DPSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 79 |
| Channel separation: | 1MHz |
| Antenna type: | Interna Antenna |
| Antenna gain: | 1.1dBi |

Note:

*2: only show the RF function associated with this report.

2022-05-18

| Laboratory Name | Shenzhen Huatongwei International Inspection Co., Ltd. | | |
|----------------------|---|----------------------|--|
| Laboratory Location | 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China | | |
| | Phone: 86-755-26715499 | | |
| Connect information: | E-mail: <u>cs@szhtw.com.cn</u> | | |
| | http://www.szhtw.com.cn | | |
| Qualifications | Туре | Accreditation Number | |
| Quaincations | FCC | 762235 | |

2022-05-18

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00 | 2402 |
| 01 | 2403 |
| ÷ | : |
| 39 | 2441 |
| ÷ | ÷ |
| 77 | 2479 |
| 78 | 2480 |

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

- 1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
- 2) All the test data for each data rate were verified, found 8DPSK Modulation which is worse case mode

4.3. Test mode

| For RF test items: | | | | |
|---|---------------|-------------------|----------------|--|
| The engineering test program was provided and enabled to make EUT continuous transmitting. | | | | |
| Modulation / Data Rate | | | | |
| Test Item | GFSK 1Mbps | π/4DQPSK 2Mbps | 8DPSK 3Mbps | |
| Conducted test item | ✓ | ✓ | \checkmark | |
| Radiated test item 🗸 | | | | |
| Remark: — For radiated test item, the worst mode data rate 3Mbps was reported only, because this data rate has | | | | |

the highest RF output power at preliminary tests.

The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

4.4. Test sample information

| Test item | HTW sample no. | |
|-------------------------|--|--|
| RF Conducted test items | Please refer to the description in the appendix report | |
| RF Radiated test items | YPHT22031150007 | |
| EMI test items | YPHT22031150007 | |

Note:

RF Conducted test items: Peak Output Power, 20 dB Bandwidth, 99% Occupied Bandwidth, Carrier Frequency Separation, Hopping Channel Number, Dwell Time, Duty Cycle Correction Factor, Pseudorandom Frequency Hopping Sequence ,Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission EMI test items: AC Conducted Emission

4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

| Whether support unit is used? | | | | |
|-------------------------------|-----------|------------|-----------|--|
| ✓ No | | | | |
| ltem | Equipment | Trade Name | Model No. | |
| 1 | | | | |
| 2 | | | | |

4.6. Testing environmental condition

| Туре | Requirement | Actual |
|--------------------|--------------|----------|
| Temperature: | 15~35°C | 25°C |
| Relative Humidity: | 25~75% | 50% |
| Air Pressure: | 860~1060mbar | 1000mbar |

4.7. Statement of the measurement uncertainty

| Test Item | Measurement Uncertainty |
|--------------------------------------|-----------------------------------|
| AC Conducted Emission (150kHz~30MHz) | 3.00 dB |
| Radiated Emission (30MHz~1000MHz | 4.36 dB |
| Radiated Emissions (1GHz~25GHz) | 5.10 dB |
| Peak Output Power | 0.77dB |
| Power Spectral Density | 0.77dB |
| Conducted Spurious Emission | 0.77dB |
| 6dB Bandwidth | 70Hz for <1GHz 130Hz for >1GHz |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

| • | Conducted Emission | | | | | | | |
|------|------------------------|--------------------|---------------|--------------------|-------------------|------------------------------|------------------------------|--|
| Used | Test Equipment | Manufacturer | Equipment No. | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | |
| • | Shielded Room | Albatross projects | HTWE0114 | N/A | N/A | 2018/09/28 | 2023/09/27 | |
| • | EMI Test Receiver | R&S | HTWE0111 | ESCI | 101247 | 2021/09/14 | 2022/09/13 | |
| • | Artificial Mains | SCHWARZBECK | HTWE0113 | NNLK 8121 | 573 | 2021/09/17 | 2022/09/16 | |
| • | Pulse Limiter | R&S | HTWE0033 | ESH3-Z2 | 100499 | 2021/09/16 | 2022/09/15 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0113-02 | ENVIROFLE X_142 | EF-NM- BNCM-2M | 2021/09/17 | 2022/09/16 | |
| • | Test Software | R&S | N/A | ES-K1 | N/A | N/A | N/A | |

4.8. Equipment Used during the Test

| • | Radiated emission-6th test site | | | | | | |
|------|---------------------------------|--------------------|---------------|-------------|------------|------------------------------|------------------------------|
| Used | Test Equipment | Manufacturer | Equipment No. | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
| • | Semi-Anechoic Chamber | Albatross projects | HTWE0127 | SAC-3m-02 | C11121 | 2018/09/30 | 2022/09/29 |
| • | EMI Test Receiver | R&S | HTWE0099 | ESCI | 100900 | 2021/09/14 | 2022/09/13 |
| • | Loop Antenna | R&S | HTWE0170 | HFH2-Z2 | 100020 | 2021/04/06 | 2024/04/05 |
| • | Ultra-Broadband Antenna | SCHWARZBECK | HTWE0123 | VULB9163 | 538 | 2021/04/06 | 2024/04/05 |
| • | Pre-Amplifer | SCHWARZBECK | HTWE0295 | BBV 9742 | N/A | 2021/11/05 | 2022/11/04 |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0062-01 | N/A | N/A | 2022/02/25 | 2023/02/24 |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0062-02 | SUCOFLEX104 | 501184/4 | 2022/02/25 | 2023/02/24 |
| • | Test Software | R&S | N/A | ES-K1 | N/A | N/A | N/A |

| • | Radiated emission-7th test site | | | | | | | |
|------|---------------------------------|--------------------|---------------|-----------------------|-------------|------------------------------|------------------------------|--|
| Used | Test Equipment | Manufacturer | Equipment No. | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | |
| • | Semi-Anechoic Chamber | Albatross projects | HTWE0122 | SAC-3m-01 | N/A | 2018/09/27 | 2022/09/26 | |
| • | Spectrum Analyzer | R&S | HTWE0098 | FSP40 | 100597 | 2021/09/13 | 2022/09/12 | |
| ● | Horn Antenna | SCHWARZBECK | HTWE0126 | 9120D | 1011 | 2020/04/01 | 2023/03/31 | |
| • | Broadband Horn Antenna | SCHWARZBECK | HTWE0103 | BBHA9170 | BBHA9170472 | 2020/04/27 | 2023/04/26 | |
| ● | Pre-amplifier | CD | HTWE0071 | PAP-0102 | 12004 | 2021/11/05 | 2022/11/04 | |
| • | Broadband Pre- amplifier | SCHWARZBECK | HTWE0201 | BBV 9718 | 9718-248 | 2022/02/28 | 2023/02/27 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0120-01 | 6m 18GHz S Serisa | N/A | 2022/02/25 | 2023/02/24 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0120-02 | 6m 3GHz RG Serisa | N/A | 2022/02/25 | 2023/02/24 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0120-03 | 6m 3GHz RG Serisa | N/A | 2022/02/25 | 2023/02/24 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0120-04 | 6m 3GHz RG Serisa | N/A | 2022/02/25 | 2023/02/24 | |
| • | RF Connection Cable | HUBER+SUHNER | HTWE0121-01 | 6m 18GHz S Serisa | N/A | 2018/09/27 | 2022/09/26 | |
| ● | Test Software | Audix | N/A | E3 | N/A | N/A | N/A | |

Page:

| • | RF Conducted Method | | | | | |
|------|---------------------------------|--------------|-----------|------------|------------------------------|------------------------------|
| Used | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
| • | Signal and spectrum Analyzer | R&S | FSV40 | 100048 | 2021/09/13 | 2022/09/12 |
| • | Spectrum Analyzer | Agilent | N9020A | MY50510187 | 2021/09/13 | 2022/09/12 |
| • | Power Meter | Anritsu | ML249A | N/A | 2021/09/13 | 2022/09/12 |
| 0 | Radio communication tester | R&S | CMW500 | 137688-Lv | 2021/09/13 | 2022/09/12 |