

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	1.1	1.29	-5.0	0.32	20.00	0.0001	1.0
GSM850	824-849	0	1.00	25.97	395.37	20.00	0.079	0.55
GSM1900	1850-1910	0	1.00	22.97	198.15	20.00	0.04	1.0
LTE/NB-IoT B2	1850-1910	0	1.00	22.00	158.49	20.00	0.03	1.0
LTE/NB-IoT B4	1710-1755	0	1.00	22.00	158.49	20.00	0.03	1.0
LTE/NB-IoT B5	824-849	0	1.00	22.00	158.49	20.00	0.03	0.55
LTE/NB-IoT B12	699-716	0	1.00	22.00	158.49	20.00	0.03	0.47
LTE/NB-IoT B13	777-787	0	1.00	22.00	158.49	20.00	0.03	0.52
LTE/NB-IoT B25	1850-1915	0	1.00	22.00	158.49	20.00	0.03	1.0
LTE B26	814-849	0	1.00	22.00	158.49	20.00	0.03	0.54
LTE/NB-IoT B66	1710-1780	0	1.00	22.00	158.49	20.00	0.03	1.0
NB-IoT B71	663-698	0	1.00	22.00	158.49	20.00	0.03	0.44
LTE/NB-IoT B85	698-716	0	1.00	22.00	158.49	20.00	0.03	0.47

The device contain a certified WWAN module, FCC ID: XMR201910BG95M3

The BLE and WWAN module can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

=S_{2.4}/S_{limit- 2.4}+ S₅/S_{limit- 5}

=0.079/0.55+0.0001/1

=0.14

< 1.0

Result: The device meet FCC MPE at 20 cm distance