


3 in 1 USB wireless charger



INSTRUCTION
MANUAL

MOBILE PHONE WIRELESS
SENSING AREA



WATCH WIRELESS
SENSING AREA

EARPHONE/PHONE WIRELESS
SENSING AREA

LED induction



Wireless charger for mobile phone		OPERATIONAL STATES			
LED	STANDBY	Charging	Full charge	FAULT	
LED green	on	flashing	on	off	
LED red	off	off	off	on	
Wireless Charger for IP watch		OPERATIONAL STATES			
LED	STANDBY	Charging	Full charge	FAULT	
LED green	on	off	off	off	
LED red	off	on	off	off	
Wireless Charger for earphone		OPERATIONAL STATES			
LED	STANDBY	Charging	Full charge	FAULT	
LED green	on	flashing	on	off	
LED red	off	off	off	on	


Product parameters

Product model : KT-IW
 Product material : ABS+PC
 Dimension : 200 * 80 * 8.5mm
 Input port : TYPE-C
 Input : 5V/3.1A ; 9V/2A-3A MAX
 Output
 1. mobile phone wireless output: 5W / 7.5W / 10W (MAX)
 2. earphones wireless output: 2.5W (MAX) / mobile phone wireless output: 5W / 7.5W / 10W (MAX)
 3. IP Watch wireless output: 2.5W (MAX)
 4. USB port output: 5V / 1.5A (MAX)
 Charging distance : 4-9mm
 Charging frequency : 110~205KHZ
 charging frequency: 300~350KHZ



MADE IN CHINA

三合一 无线充电器



使用说明书

手机无线感应区域



手表无线感应区域

手机/耳机无线感应区域

产品工作状态



手机无线充电

待机 绿灯常亮；充电 绿灯闪烁；
 充满 绿灯常亮；故障 红灯常亮。

手表无线充电

待机 绿灯常亮；充电 红灯常亮。

耳机/手机无线充电

待机 绿灯常亮；充电 绿灯闪烁；
 充满 绿灯常亮；故障 红灯常亮。

产品参数

产品名称：三合一无线充电器
 产品颜色：白色
 产品材质：ABS+PC
 产品型号：KT-IW
 产品规格：200*80*8.5mm
 输入接口：TYPE-C
 输入：5V/3.1A；9V/2A-3A MAX
 输出：1. 手机无线输出：5W/7.5W/10W(MAX)
 2. 耳机无线输出：2.5W (MAX)
 手机无线输出：5W/7.5W/10W(MAX)
 3. IP Watch无线输出：2.5W (MAX)
 4. USB口输出：5V/1.5A(MAX)
 充电距离：4~9mm
 充电效率：≥75%
 充电频率：110~205KHZ
 充电频率：300~350KHz



MADE IN CHINA

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio/TV technician for help.

The equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. During the operation of device a distance of 15 cm surrounding the device and 20 cm above the top surface of the device must be respected.