

## Appendix 5

### RF Exposure Information

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2407	-0.7	0.85
2443	-2.1	0.62
2477	-1.7	0.68

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.85/5) * \sqrt{2.407} = 0.26 < 3.0$$

$$(0.62/5) * \sqrt{2.443} = 0.19 < 3.0$$

$$(0.68/5) * \sqrt{2.477} = 0.21 < 3.0$$

**Conclusion:**

No SAR is required.