



Fanguang Inspection & Testing Co., Ltd.
Phone: +86-510-68790033
Web: www.fgtest.cn



RF Exposure Evaluation Declaration

Report No.: S202105198538E04

Issue Date: 07-23-2021

Applicant: Shanghai Ortek Electronics Co., Ltd.
Address: No.1 Jiefangdao Road, Bridge 16 Southern, Caoan Road, Jiading District, Shanghai, China
FCC ID: 2AT62TD-68
Application Type: Certification
Product: Car Audio
Model No.: TD-68
Trade Mark: N/A
FCC Classification: Digital Transmission System (DTS)
Spread Spectrum Transmitter (DSS)

Reviewed By

Amos Xia

(Amos Xia)

Senior Test Engineer

Approved By

Kerry Zhou

(Kerry Zhou)

Engineer Manager

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of Fanguang Inspection & Testing Co., Ltd.

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Headquarters Add.: Area B of the 3rd floor, XEDA Sci-Tech Park, Xiqing Economic Development Area, Tianjin, China

Tel: +86-020-66289500-8260

Email: fygd@grgtest.com

<http://www.fgtest.cn>

TRF No.: FG.WI-07-FCC part 1.1310

Reports Inquiry : <https://grgtest.com>

Revision History

Report No.	Version	Description	Issue Date
S202105198538E04	Rev. 01	/	07-23-2021

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Car Audio
Model Name:	TD-68
Additional Model:	N/A
Input Voltage Range:	12V-24V==2A Max
Bluetooth Version:	3.0+4.0
Antenna Type:	PCB Antenna
Antenna Gain:	2.81dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Car Audio
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum PK Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
BLE	2402 ~ 2480	-0.78	0.000404	1
BT	2402 ~ 2480	2.01	0.000959	1

Note: /

CONCLUSION:

The Max Power Density at R (20 cm) = 0.000959mW/cm² < 1mW/cm².

So the EUT complies with the requirement.

_____ The End _____