

## FCC Test Report

**Report No.:** RF190507C26

**FCC ID:** 2AT66-DIRISDGWM

**Test Model:** DIRIS Digiware M-70

**Series Model:** DIRIS Digiware M-50 (refer to item 3.1 for more details)

**Received Date:** May 07, 2019

**Test Date:** May 18 ~ Jul. 09, 2019

**Issued Date:** Jul. 11, 2019

**Applicant:** SOCOMEC SAS.

**Address:** Rue de Westhouse - B.P. 60010, 67235 - Benfeld cedex - France

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|   |           |
|---|-----------|
| <b>Release Control Record</b> .....                             | <b>4</b>  |
| <b>1 Certificate of Conformity</b> .....                        | <b>5</b>  |
| <b>2 Summary of Test Results</b> .....                          | <b>6</b>  |
| 2.1 Measurement Uncertainty.....                                | 6         |
| 2.2 Modification Record.....                                    | 6         |
| <b>3 General Information</b> .....                              | <b>7</b>  |
| 3.1 General Description of EUT.....                             | 7         |
| 3.2 Description of Test Modes.....                              | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....    | 9         |
| 3.3 Duty Cycle of Test Signal.....                              | 10        |
| 3.4 Description of Support Units.....                           | 11        |
| 3.4.1 Configuration of System under Test.....                   | 11        |
| 3.5 General Description of Applied Standards.....               | 11        |
| <b>4 Test Types and Results</b> .....                           | <b>12</b> |
| 4.1 Radiated Emission and Bandedge Measurement.....             | 12        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement..... | 12        |
| 4.1.2 Test Instruments.....                                     | 13        |
| 4.1.3 Test Procedures.....                                      | 14        |
| 4.1.4 Deviation from Test Standard.....                         | 14        |
| 4.1.5 Test Setup.....   | 15        |
| 4.1.6 EUT Operating Conditions.....                             | 16        |
| 4.1.7 Test Results.....   | 17        |
| 4.2 6dB Bandwidth Measurement.....                              | 24        |
| 4.2.1 Limits of 6dB Bandwidth Measurement.....                  | 24        |
| 4.2.2 Test Setup.....   | 24        |
| 4.2.3 Test Instruments.....                                     | 24        |
| 4.2.4 Test Procedure.....                                       | 24        |
| 4.2.5 Deviation from Test Standard.....                         | 24        |
| 4.2.6 EUT Operating Conditions.....                             | 24        |
| 4.2.7 Test Result.....  | 25        |
| 4.3 Conducted Output Power Measurement.....                     | 26        |
| 4.3.1 Limits of Conducted Output Power Measurement.....         | 26        |
| 4.3.2 Test Setup.....   | 26        |
| 4.3.3 Test Instruments.....                                     | 26        |
| 4.3.4 Test Procedures.....                                      | 26        |
| 4.3.5 Deviation from Test Standard.....                         | 26        |
| 4.3.6 EUT Operating Conditions.....                             | 26        |
| 4.3.7 Test Results.....   | 26        |
| 4.4 Power Spectral Density Measurement.....                     | 27        |
| 4.4.1 Limits of Power Spectral Density Measurement.....         | 27        |
| 4.4.2 Test Setup.....   | 27        |
| 4.4.3 Test Instruments.....                                     | 27        |
| 4.4.4 Test Procedure.....                                       | 27        |
| 4.4.5 Deviation from Test Standard.....                         | 27        |
| 4.4.6 EUT Operating Condition.....                              | 27        |
| 4.4.7 Test Results.....   | 28        |
| 4.5 Conducted Out of Band Emission Measurement.....             | 29        |
| 4.5.1 Limits of Conducted Out of Band Emission Measurement..... | 29        |
| 4.5.2 Test Setup.....   | 29        |
| 4.5.3 Test Instruments.....                                     | 29        |
| 4.5.4 Test Procedure.....                                       | 29        |
| 4.5.5 Deviation from Test Standard.....                         | 29        |
| 4.5.6 EUT Operating Condition.....                              | 29        |

|   |           |
|---|-----------|
| 4.5.7 Test Results .....  | 29        |
| <b>5 Pictures of Test Arrangements.....</b>                     | <b>31</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b> | <b>32</b> |

### Release Control Record

| Issue No.   | Description      | Date Issued   |
|-------------|------------------|---------------|
| RF190507C26 | Original release | Jul. 11, 2019 |

## 1 Certificate of Conformity

**Product:** DIRIS Digiware

**Brand:** SOCOMEC

**Test Model:** DIRIS Digiware M-70

**Series Model:** DIRIS Digiware M-50 (refer to item 3.1 for more details)

**Sample Status:** Engineering sample

**Applicant:** SOCOMEC SAS.

**Test Date:** May 18 ~ Jul. 09, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Celine Chou , **Date:** Jul. 11, 2019  
Celine Chou / Senior Specialist

**Approved by :** Bruce Chen , **Date:** Jul. 11, 2019  
Bruce Chen / Project Engineer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |  |        |  |
|--|--|--------|--|
| FCC Clause                                     | Test Item                                    | Result | Remarks  |
| 15.207   | AC Power Conducted Emission                  | N/A    | EUT is powered from DC   |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions and Band Edge Measurement | Pass   | Meet the requirement of limit. Minimum passing margin is -0.7dB at 2483.50MHz. |
| 15.247(d)                                      | Antenna Port Emission                        | Pass   | Meet the requirement of limit.   |
| 15.247(a)(2)                                   | 6dB bandwidth                                | Pass   | Meet the requirement of limit.   |
| 15.247(b)                                      | Conducted power                              | Pass   | Meet the requirement of limit.   |
| 15.247(e)                                      | Power Spectral Density                       | Pass   | Meet the requirement of limit.   |
| 15.203   | Antenna Requirement                          | Pass   | No antenna connector is used.  |

N/A: Not Applicable

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency        | Expanded Uncertainty (k=2) ( $\pm$ ) |
|--------------------------------|------------------|--------------------------------------|
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz     | 3.04 dB                              |
|                                | 30MHz ~ 200MHz   | 3.86 dB                              |
|                                | 200MHz ~ 1000MHz | 3.87 dB                              |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz     | 2.29 dB                              |
|                                | 18GHz ~ 40GHz    | 2.29 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                     |                                  |
|---------------------|----------------------------------|
| Product             | DIRIS Digiware                   |
| Brand               | SOCOMEK                          |
| Test Model          | DIRIS Digiware M-70              |
| Series Model        | DIRIS Digiware M-50              |
| Model Difference    | Refer to note                    |
| Sample Status       | Engineering sample               |
| Power Supply Rating | 24Vdc                            |
| Modulation Type     | GFSK                             |
| Transfer Rate       | 1Mbps                            |
| Operating Frequency | 2402 ~ 2480MHz                   |
| Number of Channel   | 40                               |
| Channel Spacing     | 2MHz                             |
| Output Power        | 2.065mW                          |
| Antenna Type        | Printed antenna with 2.5dBi gain |
| Antenna Connector   | NA                               |
| Accessory Device    | NA                               |
| Cable Supplied      | NA                               |

Note:

1. The following models are provided to this EUT.

| Brand   | Model               | Description  |
|---------|---------------------|--|
| SOCOMEK | DIRIS Digiware M-50 | <ul style="list-style-type: none"> <li>● DIRIS Digiware M-50 Multipoint interface Ref. 4829 0221</li> <li>● Ethernet output Modbus TCP BACnet IP SNMP v1, v2 &amp; v3</li> <li>● Web-Config GUI</li> </ul>   |
|         | DIRIS Digiware M-70 | <ul style="list-style-type: none"> <li>● DIRIS Digiware M-70 Multipoint interface Ref. 4829 0222</li> <li>● Ethernet output Modbus TCP BACnet IP SNMP v1, v2 &amp; v3</li> <li>● Web-Config GUI</li> <li>WEBVIEW-M Power &amp; Energy Monitoring software</li> </ul> |

\* The model of the DIRIS Digiware M-70 was chosen for final test.

2. The EUT has two types for sale which are only different in HW version.

| HW version | Description   |
|------------|---|
| Index B    | Initial samples definition  |
| Index C    | Added an XT 132 test point on the PB4 port, slight increase in the footprint of N3 and N7 |

### 3.2 Description of Test Modes

40 channels are provided to this EUT:

| Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0       | 2402        | 10      | 2422        | 20      | 2442        | 30      | 2462        |
| 1       | 2404        | 11      | 2424        | 21      | 2444        | 31      | 2464        |
| 2       | 2406        | 12      | 2426        | 22      | 2446        | 32      | 2466        |
| 3       | 2408        | 13      | 2428        | 23      | 2448        | 33      | 2468        |
| 4       | 2410        | 14      | 2430        | 24      | 2450        | 34      | 2470        |
| 5       | 2412        | 15      | 2432        | 25      | 2452        | 35      | 2472        |
| 6       | 2414        | 16      | 2434        | 26      | 2454        | 36      | 2474        |
| 7       | 2416        | 17      | 2436        | 27      | 2456        | 37      | 2476        |
| 8       | 2418        | 18      | 2438        | 28      | 2458        | 38      | 2478        |
| 9       | 2420        | 19      | 2440        | 29      | 2460        | 39      | 2480        |



### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       |        |      | Description |
|--------------------|---------------|-------|--------|------|-------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC    | APCM |             |
| A                  | √             | √     | Note 2 | √    | Index B     |
| B                  | -             | √     | -      | -    | Index C     |

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement  
 RE<1G: Radiated Emission below 1GHz  
 PLC: Power Line Conducted Emission  
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
2. No need to concern of PLC due to the EUT is powered from DC.

#### Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A                  | 0 to 39           | 0, 19, 39      | GFSK            | 1                |

#### Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A, B               | 0 to 39           | 39             | GFSK            | 1                |

#### Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A, B               | 0 to 39           | 0, 19, 39      | GFSK            | 1                |


#### Test Condition:

| Applicable to | Environmental Conditions | Input Power | Tested by  |
|---------------|--------------------------|-------------|------------|
| RE $\geq$ 1G  | 25 deg. C, 66% RH        | 24Vdc       | James Yang |
| RE<1G         | 25 deg. C, 66% RH        | 24Vdc       | James Yang |
| APCM          | 25 deg. C, 60% RH        | 24Vdc       | Alan Wu    |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98%.

Duty cycle =  $0.600/10.524 = 0.057$ , Duty factor =  $10 * \log(1/0.057) = 12.44$



### 3.4 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product         | Brand    | Model No. | Serial No. | FCC ID | Remarks |
|----|-----------------|----------|-----------|------------|--------|---------|
| A. | Load            | NA       | NA        | NA         | NA     | -       |
| B. | DC Power Supply | Keysight | U8002A    | MY56330015 | NA     | -       |

Note: All power cords of the above support units are non-shielded (1.8m).

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|---------|
| 1. | RJ45 Cable   | 1    | 1          | N                  | 0            | -       |
| 2. | DC Cable     | 1    | 1          | N                  | 0            | -       |

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**KDB 558074 D01 15.247 Meas Guidance v05r02**

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer               | Model No.                             | Serial No.  | Cal. Date     | Cal. Due      |
|--|---------------------------------------|---|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ         | ESCI                                  | 100424  | Jan. 03, 2019 | Jan. 02, 2020 |
| BILOG Antenna<br>SCHWARZBECK             | VULB9168                              | 9168-171  | Nov. 22, 2018 | Nov. 21, 2019 |
| HORN Antenna<br>SCHWARZBECK              | 9120D                                 | 209   | Nov. 25, 2018 | Nov. 24, 2019 |
| HORN Antenna<br>SCHWARZBECK              | BBHA 9170                             | BBHA9170241   | Nov. 25, 2018 | Nov. 24, 2019 |
| Loop Antenna<br>EMCI                     | EM-6879                               | 269   | Sep. 07, 2018 | Sep. 06, 2019 |
| Preamplifier<br>Agilent<br>(Below 1GHz)  | 8447D                                 | 2944A10738  | Aug. 21, 2018 | Aug. 20, 2019 |
| Preamplifier<br>Agilent<br>(Above 1GHz)  | 8449B                                 | 3008A01976  | Aug. 21, 2018 | Aug. 20, 2019 |
| RF signal cable<br>HUBER+SUHNER          | SUCOFLEX 104                          | Cable-CH3-03<br>(223653/4)                          | Aug. 21, 2018 | Aug. 20, 2019 |
| RF signal cable<br>HUBER+SUHNER&<br>EMCI | SUCOFLEX<br>104&EMC104-SM-S<br>M-8000 | Cable-CH3-03<br>(309224+170907)                     | Aug. 21, 2018 | Aug. 20, 2019 |
| Software<br>BV ADT                       | ADT_Radiated_<br>V7.6.15.9.5          | NA  | NA            | NA            |
| Antenna Tower<br>inn-co GmbH             | MA 4000                               | 013303  | NA            | NA            |
| Antenna Tower Controller<br>BV ADT       | AT100                                 | AT93021702  | NA            | NA            |
| Turn Table<br>BV ADT                     | TT100                                 | TT93021702  | NA            | NA            |
| Turn Table Controller<br>BV ADT          | SC100                                 | SC93021702  | NA            | NA            |
| Boresight Antenna Fixture                | FBA-01                                | FBA-SIP01   | NA            | NA            |
| Pre-amplifier (18GHz-40GHz)<br>EMC       | EMC184045B                            | 980175  | Nov. 14, 2018 | Nov. 13, 2019 |
| USB Wideband Power Sensor<br>KEYSIGHT    | U2021XA                               | MY55050005/MY5519<br>0004/MY55190007/MY<br>55210005 | Jul. 17, 2018 | Jul. 16, 2019 |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.

### 4.1.3 Test Procedures

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

#### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- a. Set the EUT under transmission condition continuously at specific channel frequency.



#### 4.1.7 Test Results

Above 1 GHz Data:

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| CHANNEL         | TX Channel 0 | DETECTOR FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   |                           |

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 2390.00     | 61.5 PK                 | 74.0           | -12.5       | 1.60 H             | 195                  | 28.6             | 32.9                     |
| 2   | 2390.00     | 48.6 AV                 | 54.0           | -5.4        | 1.60 H             | 195                  | 15.7             | 32.9                     |
| 3   | *2402.00    | 100.8 PK                |                |             | 1.56 H             | 199                  | 67.9             | 32.9                     |
| 4   | *2402.00    | 100.5 AV                |                |             | 1.56 H             | 199                  | 67.6             | 32.9                     |
| 5   | 4804.00     | 49.1 PK                 | 74.0           | -24.9       | 1.85 H             | 44                   | 45.5             | 3.6                      |
| 6   | 4804.00     | 35.9 AV                 | 54.0           | -18.1       | 1.85 H             | 44                   | 32.3             | 3.6                      |

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 2390.00     | 61.8 PK                 | 74.0           | -12.2       | 1.25 V             | 119                  | 28.9             | 32.9                     |
| 2   | 2390.00     | 49.2 AV                 | 54.0           | -4.8        | 1.25 V             | 119                  | 16.3             | 32.9                     |
| 3   | *2402.00    | 89.7 PK                 |                |             | 1.52 V             | 145                  | 56.8             | 32.9                     |
| 4   | *2402.00    | 89.0 AV                 |                |             | 1.52 V             | 145                  | 56.1             | 32.9                     |
| 5   | 4804.00     | 48.4 PK                 | 74.0           | -25.6       | 1.88 V             | 206                  | 44.8             | 3.6                      |
| 6   | 4804.00     | 34.9 AV                 | 54.0           | -19.1       | 1.88 V             | 206                  | 31.3             | 3.6                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |               |                   |                           |
|-----------------|---------------|-------------------|---------------------------|
| CHANNEL         | TX Channel 19 | DETECTOR FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   |                           |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | *2440.00    | 100.9 PK                |                |             | 1.55 H             | 0                    | 68.0             | 32.9                     |
| 2   | *2440.00    | 100.2 AV                |                |             | 1.55 H             | 0                    | 67.3             | 32.9                     |
| 3   | 4880.00     | 49.6 PK                 | 74.0           | -24.4       | 2.09 H             | 360                  | 45.6             | 4.0                      |
| 4   | 4880.00     | 36.2 AV                 | 54.0           | -17.8       | 2.09 H             | 360                  | 32.2             | 4.0                      |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | *2440.00    | 93.3 PK                 |                |             | 1.87 V             | 128                  | 60.4             | 32.9                     |
| 2   | *2440.00    | 92.3 AV                 |                |             | 1.87 V             | 128                  | 59.4             | 32.9                     |
| 3   | 4880.00     | 50.1 PK                 | 74.0           | -23.9       | 2.78 V             | 221                  | 46.1             | 4.0                      |
| 4   | 4880.00     | 36.1 AV                 | 54.0           | -17.9       | 2.78 V             | 221                  | 32.1             | 4.0                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                 |               |                   |                           |
|-----------------|---------------|-------------------|---------------------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   |                           |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO.      | FREQ. (MHz)    | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|----------|----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1        | *2480.00       | 96.1 PK                 |                |             | 1.57 H             | 2                    | 63.1             | 33.0                     |
| 2        | *2480.00       | 95.3 AV                 |                |             | 1.57 H             | 2                    | 62.3             | 33.0                     |
| 3        | 2483.50        | 62.3 PK                 | 74.0           | -11.7       | 1.52 H             | 6                    | 29.3             | 33.0                     |
| <b>4</b> | <b>2483.50</b> | <b>53.3 AV</b>          | <b>54.0</b>    | <b>-0.7</b> | <b>1.52 H</b>      | <b>6</b>             | <b>20.3</b>      | <b>33.0</b>              |
| 5        | 4960.00        | 50.0 PK                 | 74.0           | -24.0       | 1.99 H             | 285                  | 45.5             | 4.5                      |
| 6        | 4960.00        | 36.7 AV                 | 54.0           | -17.3       | 1.99 H             | 285                  | 32.2             | 4.5                      |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | *2480.00    | 90.2 PK                 |                |             | 1.51 V             | 150                  | 57.2             | 33.0                     |
| 2   | *2480.00    | 89.1 AV                 |                |             | 1.51 V             | 150                  | 56.1             | 33.0                     |
| 3   | 2483.50     | 61.5 PK                 | 74.0           | -12.5       | 1.55 V             | 146                  | 28.5             | 33.0                     |
| 4   | 2483.50     | 49.9 AV                 | 54.0           | -4.1        | 1.55 V             | 146                  | 16.9             | 33.0                     |
| 5   | 4960.00     | 50.5 PK                 | 74.0           | -23.5       | 2.24 V             | 130                  | 46.0             | 4.5                      |
| 6   | 4960.00     | 37.3 AV                 | 54.0           | -16.7       | 2.24 V             | 130                  | 32.8             | 4.5                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. Margin value = Emission Level – Limit value.
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.


Below 1GHz worst-case data:

|                 |               |                   |                 |
|-----------------|---------------|-------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz   |                   |                 |
| TEST MODE       | A             |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 134.89      | 38.7 QP                 | 43.5           | -4.8        | 1.99 H             | 81                   | 48.9             | -10.2                    |
| 2   | 222.38      | 43.7 QP                 | 46.0           | -2.3        | 1.50 H             | 101                  | 54.5             | -10.8                    |
| 3   | 276.82      | 33.7 QP                 | 46.0           | -12.3       | 1.01 H             | 63                   | 42.0             | -8.3                     |
| 4   | 329.32      | 33.3 QP                 | 46.0           | -12.7       | 1.01 H             | 52                   | 40.3             | -7.0                     |
| 5   | 613.19      | 29.2 QP                 | 46.0           | -16.8       | 1.50 H             | 161                  | 30.6             | -1.4                     |
| 6   | 900.94      | 34.2 QP                 | 46.0           | -11.8       | 1.01 H             | 43                   | 30.3             | 3.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report




|                 |               |                   |                 |
|-----------------|---------------|-------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz   |                   |                 |
| TEST MODE       | A             |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 53.23       | 35.6 QP                 | 40.0           | -4.4        | 1.00 V             | 5                    | 45.5             | -9.9                     |
| 2   | 134.89      | 33.2 QP                 | 43.5           | -10.3       | 1.49 V             | 172                  | 43.4             | -10.2                    |
| 3   | 230.16      | 38.2 QP                 | 46.0           | -7.8        | 1.00 V             | 296                  | 48.8             | -10.6                    |
| 4   | 317.65      | 29.8 QP                 | 46.0           | -16.2       | 1.49 V             | 167                  | 37.1             | -7.3                     |
| 5   | 673.46      | 30.0 QP                 | 46.0           | -16.0       | 1.49 V             | 297                  | 30.5             | -0.5                     |
| 6   | 852.33      | 34.2 QP                 | 46.0           | -11.8       | 1.49 V             | 186                  | 31.5             | 2.7                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report




|                 |               |                   |                 |
|-----------------|---------------|-------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz   |                   |                 |
| TEST MODE       | B             |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 40.57       | 35.6 QP                 | 40.0           | -4.4        | 2.00 H             | 76                   | 45.9             | -10.3                    |
| 2   | 84.02       | 30.0 QP                 | 40.0           | -10.0       | 2.00 H             | 69                   | 44.5             | -14.5                    |
| 3   | 160.17      | 40.5 QP                 | 43.5           | -3.0        | 1.49 H             | 99                   | 49.7             | -9.2                     |
| 4   | 226.27      | 39.7 QP                 | 46.0           | -6.3        | 1.00 H             | 256                  | 50.4             | -10.7                    |
| 5   | 269.05      | 35.8 QP                 | 46.0           | -10.2       | 1.00 H             | 258                  | 44.3             | -8.5                     |
| 6   | 432.37      | 30.2 QP                 | 46.0           | -15.8       | 1.49 H             | 187                  | 35.1             | -4.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report




|                 |               |                      |                 |
|-----------------|---------------|----------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz   |                      |                 |
| TEST MODE       | B             |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 35.96       | 35.8 QP                 | 40.0           | -4.2        | 1.01 V             | 177                  | 46.9             | -11.1                    |
| 2   | 132.95      | 38.1 QP                 | 43.5           | -5.4        | 1.01 V             | 186                  | 48.4             | -10.3                    |
| 3   | 166.00      | 38.5 QP                 | 43.5           | -5.0        | 1.50 V             | 269                  | 47.8             | -9.3                     |
| 4   | 232.11      | 37.8 QP                 | 46.0           | -8.2        | 1.01 V             | 72                   | 48.2             | -10.4                    |
| 5   | 300.16      | 33.0 QP                 | 46.0           | -13.0       | 1.50 V             | 225                  | 40.7             | -7.7                     |
| 6   | 432.37      | 36.3 QP                 | 46.0           | -9.7        | 1.01 V             | 123                  | 41.2             | -4.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report




## 4.2 6dB Bandwidth Measurement

### 4.2.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.2.2 Test Setup



### 4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.2.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 4.2.5 Deviation from Test Standard

No deviation.

### 4.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.






### 4.3 Conducted Output Power Measurement

#### 4.3.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

Same as item 4.3.6.

#### 4.3.7 Test Results


| Channel | Frequency (MHz) | Peak Power (mW) | Peak Power (dBm) | Limit (dBm) | Pass/Fail |
|---------|-----------------|-----------------|------------------|-------------|-----------|
| 0       | 2402            | 2.014           | 3.04             | 30.00       | Pass      |
| 19      | 2440            | <b>2.065</b>    | 3.15             | 30.00       | Pass      |
| 39      | 2480            | 0.731           | -1.36            | 30.00       | Pass      |

## 4.4 Power Spectral Density Measurement

### 4.4.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm per 3kHz.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Condition

Same as item 4.3.6




## 4.5 Conducted Out of Band Emission Measurement

### 4.5.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW  $\geq$  300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW  $\geq$  300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition



Same as item 4.3.6

### 4.5.7 Test Results



The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



### CH 0




### CH 19




### CH 39



### CH 0 Band edge



### CH 39 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---