

# Radio Exposure Evaluation Report

**FCC ID** : 2AT6813002019

**Equipment** : CBRSYS1300-WTE-3S

**Brand Name** : CBRSYS1300-WTE-3S

**Model Name** : CBRSYS1300-WTE-3S

**Applicant/Manufacturer** : Celliber Technologies Private Limited  
2nd Floor VYSHAK CENTRE,1027, 24th Main 11th  
Cross, Sector 1 HSR Layout, Bangalore 560102 India

**Standard** : 47 CFR Part 2.1091

The product was received on Mar. 13, 2020, and testing was started from Apr. 08, 2020 and completed on Apr. 08, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



# Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 EUT General Information .....5

1.2 Table for Permissive Change .....5

1.3 Testing Location .....5

**2 MAXIMUM PERMISSIBLE EXPOSURE .....6**

2.1 Limit of Maximum Permissible Exposure .....6

2.2 MPE Calculation Method .....6

2.3 Calculated Result and Limit .....7

**Photographs of EUT V01**



### History of this test report

Report No.	Version	Description	Issued Date
FA971005-01	01	Initial issue of report	May 18, 2020



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None.

Reviewed by: Sam Tsai

Report Producer: Jenny Yang

# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)

## 1.2 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA971005

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
5825MHz was added	Exposure evaluation
Added a relay system power	N/A
Add one power cord for 1.8m	
GPS function can be working	
Equipment, Brand Name and Model Name was updated	
Spiliter/Combiner (MPN: ZACS622-100WS) was removed	

## 1.3 Testing Location

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

**WLAN 2.4G:**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	5.00	26.59	31.59	0.50	32.09	1.61808	20	0.32191	1.00000
2.4G;D1D	5.00	26.80	31.80	0.50	32.30	1.69824	20	0.33785	1.00000

**WLAN 5G:**

Master:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	5.00	15.90	20.90	0.50	21.40	0.13804	20	0.02746	1.00000
5.8G;D1D	5.00	25.36	30.36	0.50	30.86	1.21899	20	0.24251	1.00000

Slave:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	5.00	23.97	28.97	0.50	29.47	0.88512	20	0.17609	1.00000
5.8G;D1D	5.00	25.36	30.36	0.50	30.86	1.21899	20	0.24251	1.00000

—————THE END—————