



MPE Test Report

Report No.: WKE-18DE2149VTSHPB-2

FCC ID: 2AT6A-VMGT3000

Product: Wireless Label Printer

Model: GT3000, GT3030, VM3000, VM3030

Received Date: Dec. 28, 2018

Test Date: Dec.28,2018 to Mar.18, 2019

Issued Date: Sept.10, 2019

Applicant: Varicut(Shanghai)Electronics Component Co. ,Ltd.

Address: No.655,Fengmao Rd,Malu Town, Jiading District, Shanghai

Manufacturer: Varicut(Shanghai)Electronics Component Co. ,Ltd.

Address: No.655,Fengmao Rd,Malu Town, Jiading District, Shanghai

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Address: No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Release Control Record.....	3
1 Certificate of Conformity	4
2 General Information.....	5
2.1 General Description of EUT.....	5
3 RF Exposure Measurement.....	6
3.1 Test requirement	6
3.2 Calculation Result of Maximum Exposure	6



Release Control Record

Issue No.	Description	Date Issued
WKE-18DE2149VTSHPB-2	Original release	Sept.10, 2019



1 Certificate of Conformity

Product: Wireless Label Printer

Brand: --

Model: GT3000, GT3030, VM3000, VM3030

Applicant: Varicut(Shanghai)Electronics Component Co., Ltd.

Test Date: Dec.28,2018 to Mar.18, 2019

Standards: FCC Part 2 (Section 2.1093)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Will YAN

, **Date:** Sept.10, 2019

Project Engineer

Approved by :


Daniel SUN

, **Date:** Sept.10, 2019

RF Supervisor

2 General Information

2.1 General Description of EUT

Product	Wireless Label Printer
Brand	--
Test Model	GT3000, GT3030, VM3000, VM3030
Model Difference	The appearance, structure and function are all the same, Only with different model names
Power Rating	AC 120Vac/60Hz
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 4.1
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Connector	--
Antenna Gain	1.3dBi

Note: For more details, please refer to the User's manual of the EUT.

3 RF Exposure Measurement

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

3.1 Test requirement

According to KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f}(\text{GHz})] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

3.2 Calculation Result of Maximum Exposure

Channel	Transmit Frequency (MHz)	Mode	Measured Power		Tune-up Tolerance (dBm)	Min. Separation distance (mm)	Calculation Result	1-g SAR
			dBm	mw				
0	2402	GFSK	2.36	1.722	2±1	5	0.620	3
19	2440	GFSK	-0.95	0.804	0±1	5	0.393	3
39	2480	GFSK	-0.85	0.822	0±1	5	0.397	3

Conclusion:

The calculation result of MPE is less than the limit, and no simultaneous SAR measurement is required.

--- END ---