



### Tapdn 3.0 PIR Sensor Instruction Manual Model: TAPDN-PIR-0001

- 1) Open top cover by holding the PIR sensor lens gently and pulling the top cover
- 2) Insert 2x AA batteries into lower housing per the illustrations in the housing
- 3) Ensure green LED is flashing, then replace top cover, taking note of alignment tabs
- 4) Remove paper backing and stick to desired flat surface
  - 1) May also mount with screws (not included)
- 5) Use Tapdn Onboarding app to configure the sensor on the LoRaWAN network



#### **FCC ID: 2AT6B-0001**

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS.

(1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

WARNING: CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.