

Test Report

FCC ID: 2AT6NAU-D1

Date of issue: Dec. 16, 2019

Report number:	MTi19111505-4E1
Sample description:	High Resolution Streaming Digital Audio Player
Model(s):	AU-D1
Applicant:	AUSOUNDS INTELLIGENCE, LLC
Address:	929 108TH AVE NE STE 1200, BELLEVUE, WA, 98004-4787, UNITED STATES
Date of test:	Nov. 19, 2019 to Dec. 10, 2019

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel: (86-755) 88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Table of Contents

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF EUT	5
1.2. OPERATION CHANNEL LIST	5
1.3. TEST CHANNEL LIST	6
1.4. ANCILLARY EQUIPMENT LIST	6
1.5. DESCRIPTION OF SUPPORT UNITS	6
2. SUMMARY OF TEST RESULTS	7
3. TEST FACILITIES AND ACCREDITATIONS	8
3.1. TEST LABORATORY	8
3.2. ENVIRONMENTAL CONDITIONS	8
3.3. MEASUREMENT UNCERTAINTY	8
3.4. TEST SOFTWARE	8
4. EQUIPMENT LIST	9
5. TEST RESULT	11
5.1. ANTENNA REQUIREMENT	11
5.1.1 <i>Standard Requirement</i>	11
5.1.2 <i>EUT Antenna</i>	11
5.2. PEAK OUTPUT POWER TEST	12
5.2.1 <i>Limit</i>	12
5.2.2 <i>Test setup</i>	12
5.2.3 <i>Test Procedure</i>	12
5.2.4 <i>EUT Operation Condition</i>	12
5.2.5 <i>Test Results</i>	12
5.3. CONDUCTED EMISSION	15
5.3.1 <i>Limits</i>	15
5.3.2 <i>Test Setup</i>	15
5.3.3 <i>Test Procedure</i>	16
5.3.4 <i>Test Results</i>	16
5.4. RADIATED SPURIOUS EMISSION	21
5.4.1 <i>Limits</i>	21
5.4.2 <i>Test Setup</i>	22
5.4.3 <i>Test Procedure</i>	23
5.4.4 <i>Test Results</i>	24
5.4.4.1 <i>Band edge-radiated</i>	31
5.5. POWER SPECTRAL DENSITY TEST	35
5.5.1 <i>Limit</i>	35
5.5.2 <i>Test Procedure</i>	35
5.5.3 <i>Test Setup</i>	35
5.5.4 <i>EUT Operation Conditions</i>	35
5.5.5 <i>Test Results</i>	36
5.6. 6DB BANDWIDTH	38
5.6.1 <i>Limit</i>	38
5.6.2 <i>Test Procedure</i>	38
5.6.3 <i>Test Setup</i>	38
5.6.4 <i>EUT Operation Conditions</i>	38
5.6.5 <i>Test Result</i>	38
5.7. DUTY CYCLE	41
5.7.1 <i>Conformance Limit</i>	41
5.7.2 <i>Measuring Instruments</i>	41
5.7.3 <i>Test Setup</i>	41
5.7.4 <i>Test Procedure</i>	41



5.7.5	Test Results.....	42
5.8	CONDUCTED BAND EDGE.....	44
5.8.1	Limits.....	44
5.8.2	Test Setup.....	44
5.8.3	Test Procedure.....	44
5.8.4	EUT Operation Conditions.....	44
5.8.5	Test Result	44
5.9	SPURIOUS RF CONDUCTED EMISSIONS	46
5.9.1	Conformance Limit.....	46
5.9.2	Measuring Instruments.....	46
5.9.3	Test Setup.....	46
5.9.4	Test Procedure.....	46
5.9.5	Test Results.....	46
PHOTOGRAPHS OF THE TEST SETUP		49
PHOTOGRAPHS OF THE EUT.....		51

PRODUCT INFORMATION

Applicant's name: AUSOUNDS INTELLIGENCE, LLC

Address: 929 108TH AVE NE STE 1200, BELLEVUE, WA, 98004-4787, UNITED STATES

Manufacture's name: Shenzhen Ausounds Intelligence Co., Ltd.

Address: 606B, 6th Floor, Xuyuan Building, No. 5003 Longgang Avenue, Longgang District, Shenzhen

Product name: High Resolution Streaming Digital Audio Player

Trademark: AUSOUNDS

Model name: AU-D1

Standards: FCC Part 15.247

Test procedure: ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:



Demi Mu

Dec. 10, 2019


Reviewed by:



Blue Zheng

Dec. 16, 2019

Approved by:



Smith Chen

Dec. 16, 2019

1. General Information

1.1. Description of EUT

Product name:	High Resolution Streaming Digital Audio Player
Model name:	AU-D1
Serial model:	N/A
Difference in series models:	N/A
Operation frequency:	2402-2480MHz
Modulation type:	GFSK
Bit Rate of transmitter:	1 Mbps
Antenna type:	FPC Antenna
Antenna gain:	1.15dBi
Max. output power:	-6.01dBm
Hardware version:	F201-MB-V1.1
Software version:	20191107_f201
Power supply:	DC 5V from adapter AC 120V/60Hz or DC 3.8V from battery
Adapter information:	N/A
Battery:	DC 3.8V 1500mAh
Serial number:	MTi19111505-4-S0001

1.2. Operation channel list

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.3. Test channel list

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	19	2440
High	39	2480

1.4. Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
Adapter	EQ-24BCN	/	Huizhou Dongyang Yienbi Electronics Co., Ltd.	/

1.5. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
/	/	/	/	/	
/	/	/	/	/	

Note:

- (1)The support equipment was authorized by Declaration of Confirmation.
- (2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2. Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	

3. Test Facilities and Accreditations

3.1. Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2. Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$ where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3.4. Test software

Software Name	Manufacturer	Model	Version
Bluetooth and WiFi Test System	Shenzhen JS tonskend co., ltd	JS1120-3	2.5.77.0418

4. Equipment list

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI7	100314	2019/10/09	2020/10/08
MTI-E006	TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-872	2019/10/15	2020/10/14
MTI-E014	amplifier	Hewlett-Packard	8447D	3113A06150	2019/10/09	2020/10/08
MTI-E036	Single path vehicle AMN(LISN)	Schwarzbeck	NNBM 8124	01175	2019/10/09	2020/10/08
MTI-E038	Low noise active vertical monopole antenna	Schwarzbeck	VAMP 9243	#565	2019/10/16	2020/10/15
MTI-E039	Biconical antenna	Schwarzbeck	BBA 9106	#164	2019/10/15	2020/10/14
MTI-E041	MXG Vector Signal Generator	Agilent	N5182A	MY49060455	2019/04/16	2020/04/15
MTI-E042	ESG Series Analog signal generator	Agilent	E4421B	GB40051240	2019/05/21	2020/05/20
MTI-E044	Thermometer clock humidity monitor	-	HTC-1	/	2019/04/17	2020/04/16
MTI-E062	Log Periodic Antenna	Schwarzbeck	VUSLP 9111B	#312	2018/04/11	2020/04/10
MTI-E063	Log Periodic Dipole Array Antenna	ETS-LINDGREN	3148B	00224524	2018/04/11	2020/04/10
MTI-E065	Amplifier	EMtrace	RP06A	00117	2019/04/29	2020/04/28
MTI-E071	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2019/10/25	2020/10/24
MTI-E076	EMI Test Receiver	Rohde&schwarz	ESIB26	100273	2019/04/16	2020/04/15
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A01957	2019/04/16	2020/04/15
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027695	2019/04/16	2020/04/15
MTI-E093	Artificial mains network	3ctest	LISN J50	ES3911805	2019/04/16	2020/04/15
MTI-E096	Power amplifier	Space-Dtronics	EWLNA0118G-P40	1852001	2019/04/29	2020/04/28
MTI-E097	Current Probe	SOLAR ELECTRONICS CO.	9207-1	220095-1	2019/04/17	2020/04/16
MTI-E098	Loop Sensor	SOLAR ELECTRONICS CO.	7334-1	220095-2	2019/04/21	2020/04/20
MTI-E081	EPM Series Power Meter	Agilent	E4419B	MY50000438	2019/04/16	2021/04/15
MTI-E052	18-40GHz amplifier	Chengdu step Micro Technology	ZLNA-18-40G-21	1608001	2019/04/16	2021/04/15
MTI-E053	15-40G Antenna	Schwarzbeck	BBHA9170	BBHA9170582	2019/04/16	2021/04/15



MTI-E058	Artificial power network	Schwarzbeck	NSLK8127	#841	2019/04/16	2021/04/15
Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).						

5. Test Result

5.1. Antenna requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna


The EUT antenna is FPC Antenna (1.15dBi). It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2. Peak Output Power Test

5.2.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.2.2 Test setup



5.2.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
 RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.2.4 EUT Operation Condition

The EUT tested system was configured as the statements of 2.4 unless otherwise a special operating condition is specified in the follows during the testing.

5.2.5 Test Results



EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Test Channel	Frequency	Maximum Conducted Output Power(PK)	Limit
	(MHz)	(dBm)	dBm
CH00	2402	-6.01	30
CH19	2440	-6.66	30
CH39	2480	-6.68	30

2402MHz





2440MHz



2480MHz



5.3. Conducted emission

5.3.1 Limits


FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note

(1)The tighter limit applies at the band edges.

(2)The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.3.2 Test Setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.3.3 Test Procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.


5.3.4 Test Results

Test data

The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is GFSK CH00

Note1: Emission Level = Reading Level + Factor, Margin= Emission Level- Limit, Factor = LISN modulus + Cable Loss


EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	43.26	9.73	52.99	66.00	-13.01	QP
2		0.1500	14.43	9.73	24.16	56.00	-31.84	AVG
3		0.5380	28.71	9.92	38.63	56.00	-17.37	QP
4		0.5380	13.24	9.92	23.16	46.00	-22.84	AVG
5		1.7217	27.38	10.00	37.38	56.00	-18.62	QP
6		1.7217	14.08	10.00	24.08	46.00	-21.92	AVG
7		4.3059	26.87	10.05	36.92	56.00	-19.08	QP
8		4.3059	13.37	10.05	23.42	46.00	-22.58	AVG
9		9.6456	28.65	10.31	38.96	60.00	-21.04	QP
10		9.6456	16.53	10.31	26.84	50.00	-23.16	AVG
11		19.8139	19.78	10.21	29.99	60.00	-30.01	QP
12		19.8139	10.90	10.21	21.11	50.00	-28.89	AVG




EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1700	40.62	9.73	50.35	64.96	-14.61	QP
2		0.1700	13.07	9.73	22.80	54.96	-32.16	AVG
3	*	0.5299	32.55	9.92	42.47	56.00	-13.53	QP
4		0.5299	8.31	9.92	18.23	46.00	-27.77	AVG
5		1.5500	24.79	9.99	34.78	56.00	-21.22	QP
6		1.5500	9.98	9.99	19.97	46.00	-26.03	AVG
7		3.0979	22.76	10.03	32.79	56.00	-23.21	QP
8		3.0979	9.00	10.03	19.03	46.00	-26.97	AVG
9		9.8057	28.19	10.32	38.51	60.00	-21.49	QP
10		9.8057	16.22	10.32	26.54	50.00	-23.46	AVG
11		19.8139	22.64	10.21	32.85	60.00	-27.15	QP
12		19.8139	16.97	10.21	27.18	50.00	-22.82	AVG




EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	37.55	9.73	47.28	65.16	-17.88	QP
2		0.1660	11.92	9.73	21.65	55.16	-33.51	AVG
3		0.5580	26.20	9.93	36.13	56.00	-19.87	QP
4		0.5580	12.86	9.93	22.79	46.00	-23.21	AVG
5		1.1500	23.88	9.98	33.86	56.00	-22.14	QP
6		1.1500	11.32	9.98	21.30	46.00	-24.70	AVG
7		2.1579	23.50	10.01	33.51	56.00	-22.49	QP
8		2.1579	11.24	10.01	21.25	46.00	-24.75	AVG
9		4.3539	24.67	10.06	34.73	56.00	-21.27	QP
10		4.3539	15.94	10.06	26.00	46.00	-20.00	AVG
11	*	9.6938	33.20	10.31	43.51	60.00	-16.49	QP
12		9.6938	19.27	10.31	29.58	50.00	-20.42	AVG



EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	Charging+TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2059	35.91	9.73	45.64	63.37	-17.73	QP
2		0.2059	14.06	9.73	23.79	53.37	-29.58	AVG
3		0.5340	26.70	9.92	36.62	56.00	-19.38	QP
4		0.5340	15.31	9.92	25.23	46.00	-20.77	AVG
5		1.3819	26.87	9.99	36.86	56.00	-19.14	QP
6		1.3819	13.92	9.99	23.91	46.00	-22.09	AVG
7		3.4780	24.73	10.04	34.77	56.00	-21.23	QP
8		3.4780	15.63	10.04	25.67	46.00	-20.33	AVG
9	*	9.8258	32.99	10.32	43.31	60.00	-16.69	QP
10		9.8258	16.09	10.32	26.41	50.00	-23.59	AVG
11		19.8139	24.24	10.21	34.45	60.00	-25.55	QP
12		19.8139	16.52	10.21	26.73	50.00	-23.27	AVG



5.4. Radiated spurious emission

5.4.1 Limits


Frequency (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range	RBW	VBW	Measurement
30MHz-1GHz	1MHz	3MHz	Peak
Above 1GHz	1MHz	10Hz ^{Note1}	Average
	1MHz	>1/T ^{Note2}	Average
Note1	When duty cycle is no less than 98%		
Note2	When duty cycle is less than 98%		


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.4.2 Test Setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.4.3 Test Procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter shield area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

5.4.4 Test Results

Below 30MHz

EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	Charging+TX	Polarization::	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

Between 30MHz – 1GHz:

Note: The high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is CH00.

EUT has two different voltage supports, reporting only the worst voltage mode.


EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010 hPa	Phase:	H
Test Mode:	Charging+TX	Test Voltage:	DC 5V from adapter AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		48.8429	28.96	-6.99	21.97	40.00	-18.03	QP
2		94.0978	34.23	-9.84	24.39	43.50	-19.11	QP
3		122.8340	38.48	-10.28	28.20	43.50	-15.30	QP
4	*	191.0738	39.69	-8.98	30.71	43.50	-12.79	QP
5		341.9786	27.73	-5.27	22.46	46.00	-23.54	QP
6		729.3582	29.77	-1.36	28.41	46.00	-17.59	QP



EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1010 hPa	Phase:	V
Test Mode:	Charging+TX	Test Voltage:	DC 5V from adapter AC 120V/60Hz




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		36.0007	36.28	-8.83	27.45	40.00	-12.55	QP
2		68.8721	38.15	-10.21	27.94	40.00	-12.06	QP
3		107.8876	38.45	-8.75	29.70	43.50	-13.80	QP
4	*	162.6106	45.17	-11.17	34.00	43.50	-9.50	QP
5		437.1197	32.83	-4.43	28.40	46.00	-17.60	QP
6		900.1472	29.75	0.65	30.40	46.00	-15.60	QP

1-25GHz


 Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
 (2) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:






EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	H
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2402MHz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV		dBuV/m	dBuV/m	dB	Detector
1		19328.000	37.35	19.03	56.38	74.00	-17.62	peak
2		19328.000	27.27	19.03	46.30	54.00	-7.70	AVG
3		21120.000	37.94	19.04	56.98	74.00	-17.02	peak
4		21120.000	26.66	19.04	45.70	54.00	-8.30	AVG
5		23328.000	38.89	19.50	58.39	74.00	-15.61	peak
6	*	23328.000	27.70	19.50	47.20	54.00	-6.80	AVG




EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	V
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2402MHz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		6219.000	46.91	0.41	47.32	74.00	-26.68	peak
2		6219.000	35.79	0.41	36.20	54.00	-17.80	AVG
3		11302.000	43.72	7.04	50.76	74.00	-23.24	peak
4		11302.000	31.56	7.04	38.60	54.00	-15.40	AVG
5		15841.000	44.79	8.32	53.11	74.00	-20.89	peak
6	*	15841.000	33.58	8.32	41.90	54.00	-12.10	AVG



EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	V
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2402MHz		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		19024.000	37.10	19.13	56.23	74.00	-17.77	peak
2		19024.000	25.67	19.13	44.80	54.00	-9.20	AVG
3		21648.000	37.49	19.15	56.64	74.00	-17.36	peak
4		21648.000	26.05	19.15	45.20	54.00	-8.80	AVG
5		23584.000	37.00	19.55	56.55	74.00	-17.45	peak
6	*	23584.000	27.35	19.55	46.90	54.00	-7.10	AVG

5.4.4.1 Band edge-radiated


Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
 (3) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:






EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	H
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2480MHz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV		dBuV/m	dBuV/m	dB	Detector
1	X	2479.925	97.17	2.06	99.23	74.00	25.23	peak
2	*	2479.925	85.44	2.06	87.50	54.00	33.50	AVG
3		2483.500	48.62	2.06	50.68	74.00	-23.32	peak
4		2483.500	36.43	2.06	38.49	54.00	-15.51	AVG




EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	V
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2402MHz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2310.000	46.45	-8.01	38.44	74.00	-35.56	peak
2		2310.000	37.41	-8.01	29.40	54.00	-24.60	AVG
3		2400.000	50.16	-7.97	42.19	74.00	-31.81	peak
4		2400.000	38.57	-7.97	30.60	54.00	-23.40	AVG
5	X	2402.000	86.62	-7.97	78.65	74.00	4.65	peak
6	*	2402.000	77.27	-7.97	69.30	54.00	15.30	AVG



EUT:	High Resolution Streaming Digital Audio Player	Model name:	AU-D1
Pressure:	1010hPa	Polarization:	V
Test voltage:	DC 5V from adapter AC 120V/60Hz	Test mode:	TX
Test channel:	GFSK-2480MHz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	Detector
1	X	2480.025	94.14	-7.94	86.20	74.00	12.20	peak
2	*	2480.025	83.04	-7.94	75.10	54.00	21.10	AVG
3		2483.500	49.37	-7.94	41.43	74.00	-32.57	peak
4		2483.500	37.76	-7.94	29.82	54.00	-24.18	AVG

5.5 Power spectral density test

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.5.2 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test Setup




5.5.4 EUT Operation Conditions

The EUT tested system was configured as the statements of 2.1 unless otherwise a special operating condition is specified in the follows during the testing.

5.5.5 Test Results

EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1015 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-22.228	8	PASS
2440 MHz	-22.940	8	PASS
2480 MHz	-24.775	8	PASS





TX CH19



TX CH39



5.6 6dB bandwidth


5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{kHz}$ (6dB bandwidth)	2400-2483.5

5.6.2 Test Procedure

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Test Setup



5.6.4 EUT Operation Conditions


The EUT tested system was configured as the statements of 2.1 unless otherwise a special operating condition is specified in the follows during the testing

5.6.5 Test Result




EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	639.8	500	Pass
Middle	2440	646.7	500	Pass
High	2480	651.0	500	Pass





TX CH 19



TX CH 39



5.7 Duty Cycle


5.7.1 Conformance Limit

No limit requirement.

5.7.2 Measuring Instruments

The Measuring equipment is listed in the section 4 of this test report.

5.7.3 Test Setup



5.7.4 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz (the largest available value)

VBW = 8MHz ($\geq$ RBW)

Number of points in Sweep > 100

Detector function = peak


Trace = Clear write

Measure Ttotal and Ton

Calculate Duty Cycle = $Ton / Ttotal$


5.7.5 Test Results

EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		






TX CH 19



TX CH 39



5.8 Conducted band edge

5.8.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2 Test Setup



5.8.3 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

5.8.4 EUT Operation Conditions

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing

5.8.5 Test Result




EUT:	High Resolution Streaming Digital Audio Player	Model Name:	AU-D1
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH39		

BLE: Band Edge, Left Side



BLE: Band Edge, Right Side



5.9 Spurious RF Conducted Emissions

5.9.1 Conformance Limit

Below -20dB of the highest emission level in operating band.

5.9.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

5.9.3 Test Setup

Please refer to Section 6.1 of this test report.

5.9.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.9.5 Test Results


Remark: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.



GFSK on Channel 00



GFSK on Channel 00




GFSK on Channel 00



GFSK on Channel 19




GFSK on Channel 19



GFSK on Channel 19



GFSK on Channel 39



GFSK on Channel 39




GFSK on Channel 39



Photographs of the Test Setup

Radiated emission





Conducted emission



Photographs of the EUT

See the APPENDIX 1: EUT PHOTO in the report No.: MTi19111505-4E1-1.

----END OF REPORT----