



## SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR230800169001

Page: 1 of 60

# TEST REPORT

<b>Application No.:</b>	SHCR2308001690HS
<b>FCC ID:</b>	2AT72-KIWI
<b>IC:</b>	25565-KIWI
<b>Applicant:</b>	VIS (Shanghai) Technology Limited
<b>Address of Applicant:</b>	No.58 Linsheng Road, Tinglin Town, Jinshan District, Shanghai, China
<b>Manufacturer:</b>	FOREO AB
<b>Address of Manufacturer:</b>	KARLAVÄGEN 41, 114 31 STOCKHOLM, SWEDEN
<b>Factory:</b>	VIS (Shanghai) Technology Limited
<b>Address of Factory:</b>	No.58 Linsheng Road, Tinglin Town, Jinshan District, Shanghai, China
<b>Equipment Under Test (EUT):</b>	
<b>EUT Name:</b>	Pore suctioning devices
<b>Model No.:</b>	KIWI™, KIWI™ derma
<b>Remark:</b>	Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
<b>Trade Mark:</b>	FOREO
<b>Standard(s) :</b>	47 CFR Part 15, Subpart C 15.247 RSS-247 Issue 2, February 2017 RSS-Gen Issue 5 Amendment 2 (February 2021)
<b>Date of Receipt:</b>	2023-08-25
<b>Date of Test:</b>	2023-08-29 to 2023-09-15
<b>Date of Issue:</b>	2023-09-20

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





# SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR230800169001

Page: 2 of 60

Revision Record			
Version	Description	Date	Remark
00	Original	2023-09-20	/

Authorized for issue by:			
Tested By		 Bill Wu	
		Bill Wu/Project Engineer	
Approved By		 Parlam Zhan	
		Parlam Zhan / Reviewer	

## 2 Test Summary

<b>Radio Spectrum Technical Requirement</b>				
<b>Item</b>	<b>FCC Requirement</b>	<b>IC Requirement</b>	<b>Method</b>	<b>Result</b>
Antenna Requirement	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	RSS-Gen Clause 6.8	N/A	Customer Declaration

N/A: Not applicable

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>FCC Requirement</b>	<b>IC Requirement</b>	<b>Method</b>	<b>Result</b>
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247a(2)	RSS-247 Clause 5.2(a)	ANSI C63.10 (2013) Section 11.8.1	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247(b)(3)	RSS-247 Clause 5.4(d)	ANSI C63.10 (2013) Section 11.9.1	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247(e)	RSS-247 Clause 5.2(b)	ANSI C63.10 (2013) Section 11.10.2	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247(d)	RSS-247 Clause 5.5	ANSI C63.10 (2013) Section 11.13.3.2	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247(d)	RSS-247 Clause 5.5	ANSI C63.10 (2013) Section 11.11	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	RSS-247 Section 3.3 & RSS-Gen Section 8.9	ANSI C63.10 (2013) Section 6.10.5	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	RSS-247 Section 3.3 & RSS-Gen Section 8.9	ANSI C63.10 (2013) Section 6.4,6.5,6.6	Pass
99% Bandwidth	-	RSS-Gen Section 6.7	ANSI C63.10 Section 6.9.3	Pass

Note1: There are series models mentioned in this report, and they are the similar in electrical and electronic characters. Only the model KIWI™ was tested since their differences were the model number and appearance, KIWI™ has additional blue light than KIWI™ derma, KIWI™ derma has additional motor than KIWI™.

Note2: Considering the difference, we performed the below testing in this report.

Model No.	Test Items
KIWI™	All test items
KIWI™ derma	Radiated Emissions which fall in the restricted bands & Radiated Spurious Emissions

### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY.....	3
3 CONTENTS .....	4
4 GENERAL INFORMATION.....	6
4.1 DETAILS OF E.U.T.....	6
4.2 DESCRIPTION OF SUPPORT UNITS.....	6
4.3 POWER LEVEL SETTING USING IN TEST .....	6
4.4 MEASUREMENT UNCERTAINTY .....	7
4.5 TEST LOCATION .....	7
4.6 TEST FACILITY .....	8
4.7 DEVIATION FROM STANDARDS .....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
5 EQUIPMENT LIST .....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....	10
6.1 ANTENNA REQUIREMENT .....	10
6.1.1 Test Requirement: .....	10
6.1.2 Conclusion.....	10
7 RADIO SPECTRUM MATTER TEST RESULTS .....	11
7.1 CONDUCTED PEAK OUTPUT POWER .....	11
7.1.1 E.U.T. Operation.....	11
7.1.2 Test Mode Description .....	11
7.1.3 Test Setup Diagram .....	11
7.1.4 Measurement Procedure and Data.....	11
7.2 MINIMUM 6DB BANDWIDTH .....	12
7.2.1 E.U.T. Operation.....	12
7.2.2 Test Mode Description .....	12
7.2.3 Test Setup Diagram .....	12
7.2.4 Measurement Procedure and Data.....	12
7.3 POWER SPECTRUM DENSITY .....	13
7.3.1 E.U.T. Operation.....	13
7.3.2 Test Mode Description .....	13
7.3.3 Test Setup Diagram .....	13
7.3.4 Measurement Procedure and Data.....	13
7.4 CONDUCTED BAND EDGES MEASUREMENT .....	14
7.4.1 E.U.T. Operation.....	14
7.4.2 Test Mode Description .....	14
7.4.3 Test Setup Diagram .....	14
7.4.4 Measurement Procedure and Data.....	14
7.5 CONDUCTED SPURIOUS EMISSIONS.....	15
7.5.1 E.U.T. Operation.....	15
7.5.2 Test Mode Description .....	15
7.5.3 Test Setup Diagram .....	15
7.5.4 Measurement Procedure and Data.....	15
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	16
7.6.1 E.U.T. Operation.....	16
7.6.2 Test Mode Description .....	16

7.6.3	<i>Test Setup Diagram</i> .....	17
7.6.4	<i>Measurement Procedure and Data</i> .....	17
7.7	RADIATED SPURIOUS EMISSIONS BELOW 1GHz .....	26
7.7.1	<i>E.U.T. Operation</i> .....	26
7.7.2	<i>Test Mode Description</i> .....	26
7.7.3	<i>Test Setup Diagram</i> .....	26
7.7.4	<i>Measurement Procedure and Data</i> .....	27
7.8	RADIATED SPURIOUS EMISSIONS ABOVE 1GHz.....	32
7.8.1	<i>E.U.T. Operation</i> .....	32
7.8.2	<i>Test Mode Description</i> .....	32
7.8.3	<i>Test Setup Diagram</i> .....	32
7.8.4	<i>Measurement Procedure and Data</i> .....	33
7.9	99% BANDWIDTH .....	46
7.9.1	<i>E.U.T. Operation</i> .....	46
7.9.2	<i>Test Mode Description</i> .....	46
7.9.3	<i>Test Setup Diagram</i> .....	46
7.9.4	<i>Measurement Procedure and Data</i> .....	46
8	<b>TEST SETUP PHOTO</b> .....	47
9	<b>EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)</b> .....	47
10	<b>APPENDIX</b> .....	47
10.1	APPENDIX A: DTS BANDWIDTH .....	47
10.1.1	<i>Test Result</i> .....	47
10.1.2	<i>Test Graphs</i> .....	48
10.2	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....	49
10.2.1	<i>Test Result</i> .....	49
10.2.2	<i>Test Graphs</i> .....	50
10.3	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....	51
10.3.1	<i>Test Result</i> .....	51
10.3.2	<i>Test Graphs</i> .....	52
10.4	APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....	53
10.4.1	<i>Test Result</i> .....	53
10.4.2	<i>Test Graphs</i> .....	54
10.5	APPENDIX E: BAND EDGE MEASUREMENTS .....	55
10.5.1	<i>Test Result</i> .....	55
10.5.2	<i>Test Graphs</i> .....	56
10.6	APPENDIX F: CONDUCTED SPURIOUS EMISSION .....	57
10.6.1	<i>Test Result</i> .....	57
10.6.2	<i>Test Graphs</i> .....	58

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 3.7V 520mAh Rechargeable battery
Test Voltage:	DC 3.7V
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi (Provided by manufacturer)
Date Rate:	1Mbps
S/N:	KIWI™: Yf1948U7Eef7Cs KIWI™ derma: F1955xz3SXxCx87
Firmware Version:	KIWI™: KIWI F.REV.A KIWI™ derma: KIWI derma F.REV.A

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

### 4.3 Power level setting using in test

Channel	Power setting
0	Default
19	Default
39	Default

#### 4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$8.4 \times 10^{-8}$
2	Timeout	2s
3	Duty cycle	0.4%
4	Occupied Bandwidth	3%
5	RF conducted power	0.6dB
6	RF power density	2.9dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-6GHz)
		5.4dB (6GHz-18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

#### 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

- SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc ) is provided by the applicant. (if applicable).
- SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).

## SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR230800169001

Page: 8 of 60

### 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

### 4.7 Deviation from Standards

None

### 4.8 Abnormalities from Standard Conditions

None

## 5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
<b>RF Conducted Test</b>					
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2022-12-20	2023-12-19
Spectrum Analyzer	Keysight	N9020B	SHEM241-1	2022-12-20	2023-12-19
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2023-08-02	2024-08-01
Signal Generator	R&S	SMR20	SHEM006-1	2023-08-02	2024-08-01
Signal Generator	Agilent	N5182A	SHEM182-1	2023-08-02	2024-08-01
Communication Tester	R&S	CMW270	SHEM183-1	2023-06-01	2024-05-31
Communication Tester	R&S	CMW500	SHEM268-1	2023-06-01	2024-05-31
Power Sensor	Keysight	U2021XA * 4	SHEM184-1	2023-08-02	2024-08-01
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2022-11-08	2024-11-07
AC Power Stabilizer	APC	KDF-31020T-V0-F0	SHEM216-1	2022-12-20	2023-12-19
DC Power Supply	MCH	MCH-303A	SHEM210-1	2022-12-20	2023-12-19
Conducted test Cable	/	RF01~RF04	/	2022-12-20	2023-12-19
Switcher	Tonscend	JS0806	SHEM184-1	2023-08-02	2024-08-01
Test software	Tonscend	JS Tonscend BT/WIFI System	Version: 2.6	/	/
Coaxial Cable	TST		SHEM263-1	2023-08-02	2024-08-01
Test software	TST	TST PASS	Version: 2.0	/	/
<b>RF Radiated Test</b>					
EMI test Receiver	R&S	ESU40	SHEM051-1	2022-12-20	2023-12-19
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2022-12-20	2023-12-19
Communication Tester	R&S	CMW500	SHEM268-1	2023-06-01	2024-05-31
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2022-12-20	2023-12-19
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2022-09-11	2024-09-10
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM202-1	2022-05-07	2024-05-06
Horn Antenna (1-18GHz)	Schwarzbeck	HF906	SHEM009-1	2022-08-11	2024-08-10
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2022-09-18	2024-09-17
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2022-09-18	2024-09-17
Pre-Amplifier	HP	8447D	SHEM236-1	2023-08-02	2024-08-01
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2022-12-20	2023-12-19
Band Filter	LORCH	9BRX-875/X150	SHEM156-1	/	/
Band Filter	LORCH	13BRX-1950/X500	SHEM083-2	/	/
Band Filter	LORCH	5BRX-2400/X200	SHEM155-1	/	/
Band Filter	LORCH	5BRX-5500/X1000	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2021-05-25	2024-05-24
RE test Cable	/	RE01, RE02, RE06	/	2023-01-07	2024-01-06
Test software	ESE	E3	Version: 6.111221a	/	/

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 0 dBi.

Antenna location: Refer to internal photo.

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.8 °C


Humidity: 64.4 % RH

Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

#### 7.1.3 Test Setup Diagram



#### 7.1.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

## 7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:  $\geq 500$  kHz

### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.4 % RH      Atmospheric Pressure: 1010 mbar

### 7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

### 7.2.3 Test Setup Diagram



### 7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

#### 7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.3 % RH      Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.2 % RH      Atmospheric Pressure: 1010 mbar

### 7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

### 7.4.3 Test Setup Diagram



### 7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.2 % RH      Atmospheric Pressure: 1010 mbar

### 7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details

**7.6 Radiated Emissions which fall in the restricted bands**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**7.6.1 E.U.T. Operation**


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.3 % RH      Atmospheric Pressure: 1010 mbar

**7.6.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(1Mbps)_Keep the KIWI derma in continuously transmitting mode with GFSK modulation.

### 7.6.3 Test Setup Diagram




### 7.6.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dB <sub>uV</sub>	dB/m	dB	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	2365.88	43.70	28.68	3.14	35.16	40.36	74.00	-33.64	Peak
2	2390.00	41.68	28.80	3.13	35.18	38.43	74.00	-35.57	Peak
3 p	2402.25	86.10	28.85	3.13	35.19	82.89	74.00	8.89	Peak

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2379.45	45.26	28.76	3.14	35.17	41.99	74.00	-32.01	Peak
2	2390.00	43.71	28.80	3.13	35.18	40.46	74.00	-33.54	Peak
3 p	2402.25	90.04	28.85	3.13	35.19	86.83	74.00	12.83	Peak

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Level	Factor	Loss	Factor				
	MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB
1 p	2479.66	83.88	29.08	3.20	35.25	80.91	74.00	6.91 Peak
2	2483.50	44.32	29.09	3.20	35.26	41.35	74.00	-32.65 Peak
3	2487.52	45.77	29.09	3.23	35.26	42.83	74.00	-31.17 Peak

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level	
1 p	2479.66	87.76	29.08	3.20	35.25	84.79	74.00 10.79 Peak
2	2483.50	44.61	29.09	3.20	35.26	41.64	74.00 -32.36 Peak
3	2493.39	44.82	29.10	3.23	35.26	41.89	74.00 -32.11 Peak

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dB <sub>uV</sub>	dB/m	dB	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	2387.23	43.29	28.80	3.13	35.18	40.04	74.00	-33.96	Peak
2	2390.00	40.89	28.80	3.13	35.18	37.64	74.00	-36.36	Peak
3 p	2402.25	87.62	28.85	3.13	35.19	84.41	74.00	10.41	Peak

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2380.66	45.25	28.76	3.14	35.17	41.98	74.00	-32.02	Peak
2	2390.00	43.32	28.80	3.13	35.18	40.07	74.00	-33.93	Peak
3 p	2402.25	89.41	28.85	3.13	35.19	86.20	74.00	12.20	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High



Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Level	Line	
	MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB
1 p	2480.25	84.76	29.08	3.20	35.25	81.79	74.00	7.79 Peak
2	2483.50	43.13	29.09	3.20	35.26	40.16	74.00	-33.84 Peak
3	2494.36	44.14	29.10	3.23	35.26	41.21	74.00	-32.79 Peak

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High



Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level	
1 p	2479.66	86.33	29.08	3.20	35.25	83.36	74.00 9.36 Peak
2	2483.50	44.84	29.09	3.20	35.26	41.87	74.00 -32.13 Peak
3	2499.50	45.18	29.12	3.23	35.27	42.26	74.00 -31.74 Peak

## 7.7 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 &amp; 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.8 °C


Humidity: 64.6 % RH

Atmospheric Pressure: 1010 mbar

### 7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(1Mbps)_Keep the KIWI derma in continuously transmitting mode with GFSK modulation.

### 7.7.3 Test Setup Diagram




**7.7.4 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Test Mode: 00; Polarity: Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :1690HS

Test mode :00

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1	40.276	25.47	13.46	0.95	33.70	6.18	40.00	-33.82 QP
2	49.707	26.22	13.93	1.01	33.70	7.46	40.00	-32.54 QP
3	59.025	26.08	13.10	1.18	33.61	6.75	40.00	-33.25 QP
4	142.324	26.81	13.25	2.47	33.51	9.02	43.50	-34.48 QP
5	153.200	27.39	13.80	2.46	33.49	10.16	43.50	-33.34 QP
6	925.756	26.30	23.77	7.22	32.05	25.24	46.00	-20.76 QP

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical



Antenna Polarity : VERTICAL


EUT/Project : 1690HS

Test mode : 00

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	35.005	34.92	12.60	0.94	33.70	14.76	40.00	-25.24 QP
2	51.843	33.13	13.90	1.06	33.68	14.41	40.00	-25.59 QP
3	90.537	29.82	7.67	1.86	33.60	5.75	43.50	-37.75 QP
4	159.225	26.29	13.70	2.49	33.46	9.02	43.50	-34.48 QP
5	428.019	30.02	16.62	4.43	32.96	18.11	46.00	-27.89 QP
6	938.833	26.10	23.70	7.27	32.02	25.05	46.00	-20.95 QP

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 01; Polarity: Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :1690HS

Test mode :01

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	49.014	26.17	14.00	1.00	33.70	7.47	40.00	-32.53 QP
2	56.197	27.25	13.58	1.13	33.64	8.32	40.00	-31.68 QP
3	72.084	31.01	11.10	1.51	33.58	10.04	40.00	-29.96 QP
4	153.200	28.06	13.80	2.46	33.49	10.83	43.50	-32.67 QP
5	322.189	26.88	14.14	3.98	33.00	12.00	46.00	-34.00 QP
6	916.069	26.03	23.93	7.12	32.07	25.01	46.00	-20.99 QP

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Test Mode: 01; Polarity: Vertical



Antenna Polarity : VERTICAL

EUT/Project : 1690HS

Test mode : 01

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	50.057	34.74	13.90	1.02	33.70	15.96	40.00	-24.04 QP
2	56.197	34.98	13.58	1.13	33.64	16.05	40.00	-23.95 QP
3	67.438	32.11	11.95	1.38	33.60	11.84	40.00	-28.16 QP
4	159.784	27.03	13.60	2.49	33.45	9.67	43.50	-33.83 QP
5	428.019	29.12	16.62	4.43	32.96	17.21	46.00	-28.79 QP
6	968.934	26.57	23.70	7.27	31.88	25.66	54.00	-28.34 QP

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

## 7.8 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

### 7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 64.9 % RH      Atmospheric Pressure: 1010 mbar

### 7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(1Mbps)_Keep the KIWI derma in continuously transmitting mode with GFSK modulation.

### 7.8.3 Test Setup Diagram




**7.8.4 Measurement Procedure and Data**

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4804.00	46.11	33.57	4.53	36.79	47.42	74.00	-26.58	Peak
2	7206.00	41.89	36.24	6.66	35.53	49.26	74.00	-24.74	Peak
3 p	9608.00	38.60	37.75	8.56	33.58	51.33	74.00	-22.67	Peak

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB	
1	4804.00	47.12	33.57	4.53	36.79	48.43	74.00	-25.57	Peak
2	7206.00	43.10	36.24	6.66	35.53	50.47	74.00	-23.53	Peak
3 p	9608.00	38.63	37.75	8.56	33.58	51.36	74.00	-22.64	Peak

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line			
MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1	4880.00	45.62	33.66	4.73	36.81	47.20	74.00	-26.80	Peak
2	7320.00	42.05	36.33	6.59	35.42	49.55	74.00	-24.45	Peak
3 p	9760.00	38.49	37.54	8.69	33.50	51.22	74.00	-22.78	Peak

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB	
1	4880.00	47.35	33.66	4.73	36.81	48.93	74.00	-25.07	Peak
2	7320.00	42.82	36.33	6.59	35.42	50.32	74.00	-23.68	Peak
3 p	9760.00	38.60	37.54	8.69	33.50	51.33	74.00	-22.67	Peak

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4960.00	46.08	33.65	4.92	36.83	47.82	74.00	-26.18	Peak
2	7440.00	41.70	36.31	6.61	35.34	49.28	74.00	-24.72	Peak
3 p	9920.00	38.42	37.62	8.87	33.41	51.50	74.00	-22.50	Peak

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Over	Remark
	Level	Factor	Loss	Factor	Level	Line				
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4960.00	45.77	33.65	4.92	36.83	47.51	74.00	-26.49	Peak	
2	7440.00	40.98	36.31	6.61	35.34	48.56	74.00	-25.44	Peak	
3 p	9920.00	38.58	37.62	8.87	33.41	51.66	74.00	-22.34	Peak	

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4804.00	45.84	33.57	4.53	36.79	47.15	74.00	-26.85	Peak
2	7206.00	41.64	36.24	6.66	35.53	49.01	74.00	-24.99	Peak
3 p	9608.00	38.63	37.75	8.56	33.58	51.36	74.00	-22.64	Peak

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4804.00	45.30	33.57	4.53	36.79	46.61	74.00	-27.39	Peak
2	7206.00	40.90	36.24	6.66	35.53	48.27	74.00	-25.73	Peak
3 p	9608.00	38.87	37.75	8.56	33.58	51.60	74.00	-22.40	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dB <sub>UV</sub>	dB/m	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB	
1	4880.00	45.88	33.66	4.73	36.81	47.46	74.00	-26.54	Peak
2	7320.00	41.05	36.33	6.59	35.42	48.55	74.00	-25.45	Peak
3 p	9760.00	38.90	37.54	8.69	33.50	51.63	74.00	-22.37	Peak

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:middle




Freq	ReadAntenna		Cable		Preamp		Limit Level	Over Line	Over Limit	Remark
	Level	Factor	Loss	Factor	Level	dBuV/m				
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4880.00	45.72	33.66	4.73	36.81	47.30	74.00	-26.70	Peak	
2	7320.00	40.87	36.33	6.59	35.42	48.37	74.00	-25.63	Peak	
3 p	9760.00	38.71	37.54	8.69	33.50	51.44	74.00	-22.56	Peak	

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High



Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Level			
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4960.00	46.43	33.65	4.92	36.83	48.17	74.00	-25.83	Peak
2	7440.00	40.59	36.31	6.61	35.34	48.17	74.00	-25.83	Peak
3 p	9920.00	37.91	37.62	8.87	33.41	50.99	74.00	-23.01	Peak

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High



Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4960.00	45.45	33.65	4.92	36.83	47.19	74.00	-26.81	Peak
2	7440.00	42.77	36.31	6.61	35.34	50.35	74.00	-23.65	Peak
3 p	9920.00	38.54	37.62	8.87	33.41	51.62	74.00	-22.38	Peak

## 7.9 99% Bandwidth

Test Requirement RSS-Gen Section 6.7

Test Method: ANSI C63.10 (2013) Section 6.9.3

### 7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 25.8 °C      Humidity: 65.0 % RH      Atmospheric Pressure: 1010 mbar

### 7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the KIWI in continuously transmitting mode with GFSK modulation.

### 7.9.3 Test Setup Diagram



### 7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SHCR2308001690HS

## 9 EUT Constructional Details (EUT Photos)

Refer to Appendix - Photographs of EUT Constructional Details for SHCR2308001690HS

## 10 Appendix

### 10.1 Appendix A: DTS Bandwidth

#### 10.1.1 Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.712	2401.556	2402.268	0.5	PASS
		2440	0.724	2439.548	2440.272	0.5	PASS
		2480	0.716	2479.548	2480.264	0.5	PASS

### 10.1.2 Test Graphs



**10.2 Appendix B: Occupied Channel Bandwidth****10.2.1 Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0486	2401.3864	2402.4350	---	---
		2440	1.0500	2439.3846	2440.4346	---	---
		2480	1.0574	2479.3804	2480.4378	---	---

### 10.2.2 Test Graphs





## SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR230800169001


Page: 51 of 60

### 10.3 Appendix C: Maximum conducted output power

#### 10.3.1 Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-2.99	≤30	PASS
		2440	-3.13	≤30	PASS
		2480	-4.21	≤30	PASS

### 10.3.2 Test Graphs



**SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.**

SHEM-TRF-001 Rev. 02 Sep01, 2023


Report No.: SHCR230800169001

Page: 53 of 60

**10.4 Appendix D: Maximum power spectral density****10.4.1 Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-13.09	≤8.00	PASS
		2440	-12.94	≤8.00	PASS
		2480	-14.53	≤8.00	PASS


## 10.4.2 Test Graphs



**10.5 Appendix E: Band edge measurements****10.5.1 Test Result**

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-4.29	-49.22	≤-24.29	PASS
		High	2480	-4.94	-49.45	≤-24.94	PASS


### 10.5.2 Test Graphs



**10.6 Appendix F: Conducted Spurious Emission****10.6.1 Test Result**

Test Mode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-4.71	-4.71	---	PASS
			30~1000	-4.71	-57.92	≤-24.71	PASS
			1000~26500	-4.71	-33.87	≤-24.71	PASS
		2440	Reference	-3.50	-3.50	---	PASS
			30~1000	-3.50	-57.53	≤-23.5	PASS
			1000~26500	-3.50	-35.39	≤-23.5	PASS
		2480	Reference	-6.52	-6.52	---	PASS
			30~1000	-6.52	-58.26	≤-26.52	PASS
			1000~26500	-6.52	-37.92	≤-26.52	PASS

### 10.6.2 Test Graphs



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.


SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR230800169001


Page: 59 of 60




BLE 1M Ant1 2440 30~1000



BLE 1M Ant1 2440 1000~26500



BLE\_1M\_Ant1\_2480\_0~Reference



- End of the Report -