

Test Report

Applicant: SportBak

Address of Applicant: 60 avenue Andre Roussin 13016, Marseille, France

Manufacturer: SportBak

Address of Manufacturer: 60 avenue Andre Roussin 13016, Marseille, France

Equipment Under Test (EUT)

Product Name: Ankle Wrist

Model No.: FutBak V1

FCC ID: 2AT74-FUTBAK

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: November 12, 2019

Date of Test: November 13-December 12, 2019

Date of report issued: December 13, 2019

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature of Robinson Lo is overlaid on a circular blue stamp. The stamp contains the text 'TECHNOLOGY SERVICES' at the top, 'GLOBAL TESTING' in the center, and 'GTS' at the bottom. The date '11/10/2019' is also visible on the stamp.


Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	December 13, 2019	Original

Prepared By:



Date:

December 13, 2019

Project Engineer

Check By:



Date:

December 13, 2019

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
6 TEST INSTRUMENTS LIST.....	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT.....	10
7.2 CONDUCTED EMISSIONS	11
7.3 RADIATED EMISSION METHOD	14
7.3.1 Field Strength of The Fundamental Signal	16
7.3.2 Spurious emissions.....	17
7.3.3 Bandedge emissions.....	25
7.4 20dB OCCUPY BANDWIDTH	29
8 TEST SETUP PHOTO	31
9 EUT CONSTRUCTIONAL DETAILS	31

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Ankle Wrist
Model No.:	FutBak V1
Serial No.:	NA
Hardware Version:	V1
Software Version:	V1
Test sample(s) ID:	GTS201911000064-1
Sample(s) Status	Engineered sample
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	40
Channel separation:	2MHz
Modulation type:	GFSK
Antenna Type:	Inner Antenna
Antenna gain:	1.5dBi(declare by applicant)
Power supply:	Battery: DC 3.7V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
...
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	85.56	82.69	83.09

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
DELTA	ADAPTER	ADP-60ADT	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

• **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

• **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 26 2019	June. 25 2020
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 26 2019	June. 25 2020
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 26 2019	June. 25 2020
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 26 2019	June. 25 2020
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 26 2019	June. 25 2020
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 26 2019	June. 25 2020
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 26 2019	June. 25 2020


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020


7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is inner antenna, the best case gain of the antenna is 1.5dBi, reference to the appendix II for details	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<small>* Decreases with the logarithm of the frequency.</small>																
Test setup:	 <p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>LISN</p> <p>Filter</p> <p>AC power</p> <p>EMI Receiver</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar											
Test results:	Pass																

Measurement data:
Line:


Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.16	43.11	0.40	0.08	43.59	65.38	-21.79	QP
0.16	32.34	0.40	0.08	32.82	55.38	-22.56	Average
0.32	33.74	0.39	0.10	34.23	59.71	-25.48	QP
0.32	25.65	0.39	0.10	26.14	49.71	-23.57	Average
0.40	33.81	0.35	0.11	34.27	57.77	-23.50	QP
0.40	27.27	0.35	0.11	27.73	47.77	-20.04	Average
0.73	36.96	0.25	0.13	37.34	56.00	-18.66	QP
0.73	30.27	0.25	0.13	30.65	46.00	-15.35	Average
2.33	31.18	0.20	0.18	31.56	56.00	-24.44	QP
2.33	24.86	0.20	0.18	25.24	46.00	-20.76	Average
7.85	37.20	0.20	0.19	37.59	60.00	-22.41	QP
7.85	27.96	0.20	0.19	28.35	50.00	-21.65	Average


Neutral:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.16	43.53	0.40	0.08	44.01	65.38	-21.37	QP
0.16	30.32	0.40	0.08	30.80	55.38	-24.58	Average
0.24	34.60	0.40	0.11	35.11	62.08	-26.97	QP
0.24	23.37	0.40	0.11	23.88	52.08	-28.20	Average
0.32	33.77	0.39	0.10	34.26	59.71	-25.45	QP
0.32	22.58	0.39	0.10	23.07	49.71	-26.64	Average
0.78	37.76	0.24	0.14	38.14	56.00	-17.86	QP
0.78	25.22	0.24	0.14	25.60	46.00	-20.40	Average
2.35	32.40	0.20	0.18	32.78	56.00	-23.22	QP
2.35	23.69	0.20	0.18	24.07	46.00	-21.93	Average
5.71	33.00	0.20	0.18	33.38	60.00	-26.62	QP
5.71	24.22	0.20	0.18	24.60	50.00	-25.40	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	9kHz to 25GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value				
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark					
	2400MHz-2483.5MHz	94.00		Average Value					
		114.00		Peak Value					
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)		Remark					
	0.009MHz-0.490MHz	2400/F(kHz) @300m		Quasi-peak Value					
	0.490MHz-1.705MHz	24000/F(kHz) @30m		Quasi-peak Value					
	1.705MHz-30.0MHz	30 @30m		Quasi-peak Value					
	30MHz-88MHz	100 @3m		Quasi-peak Value					
	88MHz-216MHz	150 @3m		Quasi-peak Value					
	216MHz-960MHz	200 @3m		Quasi-peak Value					
	960MHz-1GHz	500 @3m		Quasi-peak Value					
	Above 1GHz	500 @3m		Average Value					
		5000 @3m		Peak Value					
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.								
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz								



For radiated emissions above 1GHz



Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test results:	Pass

Measurement data:

7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	82.77	27.58	5.39	30.18	85.56	114	-28.44	Vertical
2402.00	79.35	27.58	5.39	30.18	82.14	114	-31.86	Horizontal
2440.00	81.75	27.55	5.43	30.06	84.67	114	-29.33	Vertical
2440.00	78.52	27.55	5.43	30.06	81.44	114	-32.56	Horizontal
2480.00	81.02	27.52	5.47	29.93	84.08	114	-29.92	Vertical
2480.00	78.11	27.52	5.47	29.93	81.17	114	-32.83	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	74.10	27.58	5.39	30.18	76.89	94	-17.11	Vertical
2402.00	71.50	27.58	5.39	30.18	74.29	94	-19.71	Horizontal
2440.00	72.17	27.55	5.43	30.06	75.09	94	-18.91	Vertical
2440.00	69.56	27.55	5.43	30.06	72.48	94	-21.52	Horizontal
2480.00	71.39	27.52	5.47	29.93	74.45	94	-19.55	Vertical
2480.00	69.28	27.52	5.47	29.93	72.34	94	-21.66	Horizontal

Note: RBW 3MHz VBW 3MHz PK detector is for PK value , RMS detector is for AV value


7.3.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
30.000	38.81	11.20	0.12	30.20	19.93	40.00	-20.07	QP
48.163	37.35	12.28	0.51	30.01	20.13	40.00	-19.87	QP
114.114	38.01	10.43	0.96	29.82	19.58	43.50	-23.92	QP
168.414	39.14	8.47	1.14	29.60	19.15	43.50	-24.35	QP
327.887	33.39	14.12	1.62	30.05	19.08	46.00	-26.92	QP
519.065	33.62	17.74	2.18	29.42	24.12	46.00	-21.88	QP

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
37.155	37.97	11.70	0.14	30.12	19.69	40.00	-20.31	QP
45.058	37.99	12.25	0.38	30.04	20.58	40.00	-19.42	QP
114.917	36.03	10.26	0.96	29.82	17.43	43.50	-26.07	QP
201.393	36.21	10.44	1.23	29.51	18.37	43.50	-25.13	QP
365.539	33.40	14.78	1.71	29.75	20.14	46.00	-25.86	QP
584.790	32.84	19.17	2.39	29.48	24.92	46.00	-21.08	QP

■ Above 1GHz


Test channel:	Lowest channel
---------------	----------------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	33.22	31.20	4.61	32.09	36.94	54.00	-17.06	Average
4804.000	44.62	31.20	4.61	32.09	48.34	74.00	-25.66	Peak
7206.000	24.59	36.16	6.48	32.00	35.23	54.00	-18.77	Average
7206.000	30.16	36.16	6.48	32.00	40.80	74.00	-33.20	Peak
9608.000	23.24	37.93	7.97	31.62	37.52	54.00	-16.48	Average
9608.000	29.23	37.93	7.97	31.62	43.51	74.00	-30.49	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	31.70	31.20	4.61	32.09	35.42	54.00	-18.58	Average
4804.000	40.58	31.20	4.61	32.09	44.30	74.00	-29.70	Peak
7206.000	26.08	36.16	6.48	32.00	36.72	54.00	-17.28	Average
7206.000	33.41	36.16	6.48	32.00	44.05	74.00	-29.95	Peak
9608.000	24.34	37.93	7.97	31.62	38.62	54.00	-15.38	Average
9608.000	30.04	37.93	7.97	31.62	44.32	74.00	-29.68	Peak


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	33.99	31.31	4.69	32.12	37.87	54.00	-16.13	Average
4880.000	43.39	31.31	4.69	32.12	47.27	74.00	-26.73	Peak
7320.000	26.92	36.43	6.63	31.89	38.09	54.00	-15.91	Average
7320.000	34.39	36.43	6.63	31.89	45.56	74.00	-28.44	Peak
9760.000	24.30	38.10	8.03	31.59	38.84	54.00	-15.16	Average
9760.000	30.53	38.10	8.03	31.59	45.07	74.00	-28.93	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	32.09	31.31	4.69	32.12	35.97	54.00	-18.03	Average
4880.000	40.30	31.31	4.69	32.12	44.18	74.00	-29.82	Peak
7320.000	27.58	36.43	6.63	31.89	38.75	54.00	-15.25	Average
7320.000	35.66	36.43	6.63	31.89	46.83	74.00	-27.17	Peak
9760.000	24.74	38.10	8.03	31.59	39.28	54.00	-14.72	Average
9760.000	29.77	38.10	8.03	31.59	44.31	74.00	-29.69	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	29.07	31.44	4.79	32.16	33.14	54.00	-20.86	Average
4960.000	37.70	31.44	4.79	32.16	41.77	74.00	-32.23	Peak
7440.000	24.52	36.66	6.77	31.78	36.17	54.00	-17.83	Average
7440.000	31.75	36.66	6.77	31.78	43.40	74.00	-30.60	Peak
9920.000	22.95	38.30	8.09	31.88	37.46	54.00	-16.54	Average
9920.000	29.89	38.30	8.09	31.88	44.40	74.00	-29.60	Peak

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	27.88	31.44	4.79	32.16	31.95	54.00	-22.05	Average
4960.000	36.38	31.44	4.79	32.16	40.45	74.00	-33.55	Peak
7440.000	26.58	36.66	6.77	31.78	38.23	54.00	-15.77	Average
7440.000	34.36	36.66	6.77	31.78	46.01	74.00	-27.99	Peak
9920.000	23.58	38.30	8.09	31.88	38.09	54.00	-15.91	Average
9920.000	29.82	38.30	8.09	31.88	44.33	74.00	-29.67	Peak


Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.3.3 Bandedge emissions


Test channel:	Lowest channel
---------------	----------------

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.64	27.14	2.81	34.11	25.48	54.00	-28.52	Average
2310.000	38.93	27.14	2.81	34.11	34.77	74.00	-39.23	Peak
2390.000	28.03	27.37	2.91	34.01	24.30	54.00	-29.70	Average
2390.000	39.81	27.37	2.91	34.01	36.08	74.00	-37.92	Peak
2400.000	33.18	27.41	2.91	34.01	29.49	54.00	-24.51	Average
2400.000	45.48	27.41	2.91	34.01	41.79	74.00	-32.21	Peak


Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.67	27.14	2.81	34.11	25.51	54.00	-28.49	Average
2310.000	37.08	27.14	2.81	34.11	32.92	74.00	-41.08	Peak
2390.000	29.45	27.37	2.91	34.01	25.72	54.00	-28.28	Average
2390.000	37.77	27.37	2.91	34.01	34.04	74.00	-39.96	Peak
2400.000	35.76	27.41	2.91	34.01	32.07	54.00	-21.93	Average
2400.000	49.47	27.41	2.91	34.01	45.78	74.00	-28.22	Peak


Test channel:	Highest channel
---------------	-----------------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	28.38	27.66	2.99	33.92	25.11	54.00	-28.89	Average
2483.500	36.29	27.66	2.99	33.92	33.02	74.00	-40.98	Peak
2500.000	27.54	27.70	3.01	33.90	24.35	54.00	-29.65	Average
2500.000	35.97	27.70	3.01	33.90	32.78	74.00	-41.22	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	29.79	27.66	2.99	33.92	26.52	54.00	-27.48	Average
2483.500	36.31	27.66	2.99	33.92	33.04	74.00	-40.96	Peak
2500.000	28.17	27.70	3.01	33.90	24.98	54.00	-29.02	Average
2500.000	35.86	27.70	3.01	33.90	32.67	74.00	-41.33	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.225	Pass
Middle	1.221	Pass
Highest	1.235	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----