

Report No.: TW2204150E File Reference No.: 2022-04-14

Applicant: Shenzhen Innosystem Technology Ltd

Product: Bluetooth speakers

Model No.: MZ368, MZ508, MZ511, MZ200, MZ500

Trademark: INWA

Test Standards: FCC Part 15.247

Test Result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for

the evaluation of electromagnetic compatibility

Approved By

Terry long

Terry Tang

Manager

Dated: April 14, 2022

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: TW2204150E Page 2 of 67

Date: 2022-04-14



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details.	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT.	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT.	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	13
7.0	20dB Bandwidth	20
8.0	Maximum Output Power.	28
9.0	Carrier Frequency Separation.	30
10.0	Number of Hopping Channel.	33
11.0	Time of Occupancy (Dwell Time).	36
12.0	Out of Band Measurement.	44
13.0	Antenna Requirement.	54
14.0	FCC ID Label.	55
15.0	Photo of Test Setup and EUT View.	56

Report No.: TW2204150E Page 4 of 67

Date: 2022-04-14



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site Listed with Federal Communications commission (FCC)

Registration Number:744189 For 3m Anechoic Chamber

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A

For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Shenzhen Innosystem Technology Ltd

Address: 2F, Building 3, Shenzhen Software Park, Technology Middle 2Rd, Hi-Tech Park, ShenZhen

Telephone: -Fax: --

1.3 Description of EUT

Product: Bluetooth speakers

Manufacturer: Shenzhen Innosystem Technology Ltd

Address: 2F, Building 3, Shenzhen Software Park, Technology Middle 2Rd, Hi-Tech Park,

ShenZhen

Trademark: INWA Model Number: MZ368

Additional Model Number: MZ508, MZ511, MZ200, MZ500

Type of Modulation GFSK, Л/4D-QPSK

Frequency range 2402-2480MHz for Bluetooth

Channel Spacing 1MHz for Bluetooth

Frequency Selection By software

Channel Number 79 channels for Bluetooth

Antenna: PCB antenna. The gain of the antennas is 0dBi (Declared by the applicant)

Rating: DC5V, 1A, 5W

Battery: DC3.7V, 750mAh Li-ion battery

1.4 Submitted Sample: 1 Samples

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2204150E Page 5 of 67

Date: 2022-04-14



1.5 Test Duration

2022-04-11 to 2022-04-14

Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty = 6.0dB

Occupied Channel Bandwidth Uncertainty =5%

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Andy Xing

Page 6 of 67

Report No.: TW2204150E

Date: 2022-04-14



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2021-06-18	2022-06-17
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2021-06-18	2022-06-17
Loop Antenna	EMCO	6507	00078608	2021-06-18	2024-06-17
Spectrum	R&S	FSIQ26	100292	2021-06-18	2022-06-17
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2021-07-02	2024-07-01
Horn Antenna	R&S	BBHA 9120D	9120D-631	2021-07-02	2024-07-01
Power meter	Anritsu	ML2487A	6K00003613	2021-06-18	2022-06-17
Power sensor	Anritsu	MA2491A	32263	2021-06-18	2022-06-17
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2021-07-02	2024-07-01
9*6*6 Anechoic			N/A	2021-07-02	2022-07-01
EMI Test Receiver	RS	ESVB	826156/011	2021-06-18	2022-06-17
EMI Test Receiver	RS	ESH3	860904/006	2021-06-18	2022-06-17
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2021-06-18	2022-06-17
Spectrum	HP/Agilent	E4407B	MY50441392	2021-06-18	2022-06-17
Spectrum	RS	FSP	1164.4391.38	2022-01-15	2023-01-14
RF Cable	Zhengdi	ZT26-NJ-NJ-8 M/FA		2021-06-18	2022-06-17
RF Cable	Zhengdi	7m		2021-06-18	2022-06-17
RF Switch	EM	EMSW18	060391	2021-06-18	2022-06-17
Pre-Amplifier	Schwarebeck	BBV9743	#218	2021-06-18	2022-06-17
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2021-06-18	2022-06-17
LISN	SCHAFFNER	NNB42	00012	2022-01-05	2023-01-04

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

Page 7 of 67

Report No.: TW2204150E

Date: 2022-04-14



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	Pass	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	Pass	Complies
Carrier Frequency Separation	15.247(a)(1)	Pass	Complies
20dB Channel Bandwidth	15.247 (a)(1)	Pass	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	Pass	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	Pass	Complies
Spurious Emission, Band Edge, and Restricted bands	15.247(d),15.205(a), 15.209 (a),15.109	Pass	Complies
Conducted Emissions	15.207	Pass	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	Pass	Complies

Note: the multi-functional base and simple base were tested and only the worst case was reported. The multi-functional base was the worst case.

Test Standards 3.2

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 **EUT Modification**

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Page 8 of 67


Report No.: TW2204150E

Date: 2022-04-14



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~60Hz Block diagram of Test setup



5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Page 9 of 67

Report No.: TW2204150E

Date: 2022-04-14



A. EUT

Device	Manufacturer	Model	FCC ID
Bluetooth speakers	Shanzhan Innasystam Taahnalagy I td	MZ368, MZ508, MZ511,	2AT7C-MZ368
Diuctooni speakers	Shenzhen Innosystem Technology Ltd	MZ200, MZ500	2A1 / C-IVIZ 308

B. Internal Device

Device	Manufacturer	Model	Rating
N/A			

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (dB μ V)				
(MHz)	Quasi-peak Level	Average Level			
0.15 ~ 0.50	66.0~56.0*	56.0~ 6.0*			
$0.50 \sim 5.00$	56.0	46.0			
5.00 ~ 30.00	60.0	50.0			

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2022-04-14



A: Conducted Emission on Live Terminal (150kHz to 30MHz)


EUT Operating Environment

Humidity: 65%RH Atmospheric Pressure: 101 kPa Temperature: 26°C

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.8442	22.78	9.78	32.56	56.00	-23.44	QP	Р
2	0.8442	16.12	9.78	25.90	46.00	-20.10	AVG	Р
3	2.5251	19.91	9.82	29.73	56.00	-26.27	QP	Р
4	2.5251	11.43	9.82	21.25	46.00	-24.75	AVG	Р
5	4.1973	26.72	9.90	36.62	56.00	-19.38	QP	Р
6	4.1973	21.39	9.90	31.29	46.00	-14.71	AVG	Р
7	5.8859	10.90	9.97	20.87	60.00	-39.13	QP	Р
8	5.8859	0.88	9.97	10.85	50.00	-39.15	AVG	Р
9	7.5708	13.95	10.04	23.99	60.00	-36.01	QP	Р
10	7.5708	4.39	10.04	14.43	50.00	-35.57	AVG	Р
11	9.2361	10.90	10.12	21.02	60.00	-38.98	QP	Р
12	9.2361	2.96	10.12	13.08	50.00	-36.92	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Date: 2022-04-14



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


EUT Operating Environment

Humidity: 65%RH Atmospheric Pressure: 101 kPa Temperature: 26°C

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.8442	22.78	9.78	32.56	56.00	-23.44	QP	Р
2	0.8442	16.12	9.78	25.90	46.00	-20.10	AVG	Р
3	2.5251	19.91	9.82	29.73	56.00	-26.27	QP	Р
4	2.5251	11.43	9.82	21.25	46.00	-24.75	AVG	Р
5	4.1973	26.72	9.90	36.62	56.00	-19.38	QP	Р
6	4.1973	21.39	9.90	31.29	46.00	-14.71	AVG	Р
7	5.8859	10.90	9.97	20.87	60.00	-39.13	QP	Р
8	5.8859	0.88	9.97	10.85	50.00	-39.15	AVG	Р
9	7.5708	13.95	10.04	23.99	60.00	-36.01	QP	Р
10	7.5708	4.39	10.04	14.43	50.00	-35.57	AVG	Р
11	9.2361	10.90	10.12	21.02	60.00	-38.98	QP	Р
12	9.2361	2.96	10.12	13.08	50.00	-36.92	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: TW2204150E Page 12 of 67

Date: 2022-04-14




6 Radiated Emission Test

6.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup


For radiated emissions from 9kHz to 30MHz




Date: 2022-04-14



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.
- 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Report No.: TW2204150E Page 14 of 67

Date: 2022-04-14



Frequencies in restricted band are complied to limit on Paragraph 15.209

	1	8 1
Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	20log(2400/F(kHz)) +40log (300/3)
0.490-1.705	3	20log(24000/F(kHz)) +40log (30/3)
1.705-30	3	69.5
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. GFSK was the worst case because it has highest output power
- 5. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 6. For radiated emissions from 9kHz to 30MHz, the emission level is much less than the limit for more than 20dB. No necessary to take down the record.
- 7. Battery full charged during tests.

Date: 2022-04-14



Page 15 of 67

Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

EUT set Condition: Keep Bluetooth Transmitting


Results: Pass

Page 16 of 67 Report No.: TW2204150E

Test Figure:

Date: 2022-04-14

H



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	53.274	15.36	-11.51	40.0	-24.64	Peak	206.00	100	Horizontal	Pass
2	287.956	20.43	-11.27	47.0	-26.57	Peak	71.00	100	Horizontal	Pass
3	347.111	22.72	-9.43	47.0	-24.28	Peak	110.00	100	Horizontal	Pass
4	383.962	29.97	-9.16	47.0	-17.03	Peak	258.00	100	Horizontal	Pass
5	767.986	32.22	-3.20	47.0	-14.78	Peak	101.00	100	Horizontal	Pass
6	863.992	26.83	-2.34	47.0	-20.17	Peak	62.00	100	Horizontal	Pass


Page 17 of 67 Report No.: TW2204150E

Date: 2022-04-14



Test Figure:

V



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	355.111	19.49	-9.43	46.0	-26.51	Peak	360.00	100	Vertical	Pass
2	383.962	23.73	-9.16	46.0	-22.27	Peak	360.00	100	Vertical	Pass
3	404.569	22.73	-8.54	46.0	-23.27	Peak	20.00	100	Vertical	Pass
4	479.968	21.73	-7.40	46.0	-24.27	Peak	20.00	100	Vertical	Pass
5	739.863	24.67	-3.55	46.0	-21.33	Peak	88.00	100	Vertical	Pass
6	889.933	26.01	-1.90	46.0	-19.99	Peak	97.00	100	Vertical	Pass

Page 18 of 67 Report No.: TW2204150E

Date: 2022-04-14



Operation Mode: Transmitting under Low Channel (2402MHz)

	8		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4804	48.32	Н	74(Peak)/ 54(AV)
4804	45.19	V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Operation Mode: Transmitting g under Middle Channel (2441MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4882	47.05	Н	74(Peak)/ 54(AV)
4882		V	74(Peak)/ 54(AV)
7323		H/V	74(Peak)/ 54(AV)
9764		H/V	74(Peak)/ 54(AV)
12205		H/V	74(Peak)/ 54(AV)
14646		H/V	74(Peak)/ 54(AV)
17087		H/V	74(Peak)/ 54(AV)
19528		H/V	74(Peak)/ 54(AV)
21969		H/V	74(Peak)/ 54(AV)
24410		H/V	74(Peak)/ 54(AV)

Report No.: TW2204150E Page 19 of 67

Date: 2022-04-14



Operation Mode: Transmitting under High Channel (2480MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4960	46.70	Н	74(Peak)/ 54(AV)
4960		V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp

- 2. For the radiated emissions above 18G and Below 30MHz, it is the floor noise.
- 3. The measured PK value less than the AV limit, no necessary to take down the AV measurement result.
- 4. Remark "---" means that the emissions level is too low to be measured

Report No.: TW2204150E Page 20 of 67

Date: 2022-04-14



7.0 20dB Bandwidth Measurement

7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.2 Limits of 20dB Bandwidth Measurement

N/A

7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =2 or 2.4MHz, RBW =30 or 36 kHz, VBW=91or 110 kHz, Sweep = auto Detector function = peak, Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

7.4 Test Result

Type of Modulation: GFSK

Type of Modulation of Si							
EUT	UT Bluetooth speakers		Model	MZ368			
Mode	Mode Keep Transmitting		Input Voltage	DC3.7V			
Temperat	mperature 24 deg. C,		Humidity	56% RH			
Channel Channel Frequency (MHz)		20 dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass/ Fail			
Low	2402	0.961		Pass			
Middle	2441	0.963		Pass			
High	2480	0.965		Pass			

Page 21 of 67


Report No.: TW2204150E

Date: 2022-04-14



Test Figure:

1. Condition: Low Channel




Page 22 of 67

Report No.: TW2204150E

Date: 2022-04-14



2. Condition: Middle Channel




Page 23 of 67

Report No.: TW2204150E

Date: 2022-04-14



3. High Channel



Date: 2022-04-14



Page 24 of 67

Test Result

Type of Modulation: JI/4D-QPSK

EUT	Bl	Bluetooth speakers		MZ368
Mode	Mode Keep Transmitting		Keep Transmitting Input Voltage	
Temperat	perature 24 deg. C,		Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1.490		Pass
Middle	2441	1.491		Pass
High	2480	1.491		Pass

Page 25 of 67


Report No.: TW2204150E

Date: 2022-04-14



Test Figure:

1. Condition: Low Channel




Page 26 of 67

Report No.: TW2204150E

Date: 2022-04-14



2. Condition: Middle Channel




Page 27 of 67

Report No.: TW2204150E

Date: 2022-04-14



3. High Channel



Date: 2022-04-14



Page 28 of 67

8. Maximum Output Power

8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW = 10MHz, RBW=3MHz; Sweep = 60s; Detector function = PK; Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 29 of 67

Report No.: TW2204150E

Date: 2022-04-14



8.4Test Results

Type of Modulation: GFSK

EUT	Bl	Bluetooth speakers		Model	MZ368		
Mode	Ke	Keep Transmitting Input Voltage		Voltage	DC3.7V		
Temperature	е	24 deg. C,		24 deg. C, Humidity		dity	56% RH
Channel	Channel Frequency (MHz)		Max. Power Output (dBm)		Pass/ Fail		
		Peak		(dBm)			
Low	2402	4.79		30	Pass		
Middle	2441	4.50		30	Pass		
High	2480	3.60		30	Pass		

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

- 2. The worst case was recorded
- 3. The Peak power was measured

Type of Modulation: JI/4D-QPSK

EUT	EUT Bluetooth speakers		Model		MZ368	
Mode	Mode Keep Transmitting		Input Voltage		DC3.7V	
Temperature	e	24 deg. C,		24 deg. C, Humidity		56% RH
Channel	Channel Frequency	Max. Power Output (dBm)	Peak Power	Pass/ Fail	
	(MHz)	Peak		Limit (dBm)		
Low	2402	0.75		30	Pass	
Middle	2441	0.46		30	Pass	
High	2480	-0.55		30	Pass	

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

- 2. The worst case was recorded
- 3. The Peak power was measured

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2022-04-14



Page 30 of 67

9. Carrier Frequency Separation

9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 31 of 67

Date: 2022-04-14




9.4Test Result

Type of Modulation: GFSK

Report No.: TW2204150E

EUT	Bluetooth spea	Model		MZ368	
Mode	Hopping On I		Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity			56% RH
Carrier I	Frequency Separation		Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2/3	of the 20 dB ban	dwidth	Pass

Test Plots



Report No.: TW2204150E Page 32 of 67


Date: 2022-04-14



Type of Modulation: $\sqrt{1/4}$ D-QPSK

EUT	Bluetooth spea	Model		MZ368	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity			56% RH
Carrier Frequency Separation			Limit		Pass/ Fail
	0.996MHz	≥ 25 kHz or 2	2/3 of 20 dB bandy	width	Pass

Test Plots



Date: 2022-04-14



Page 33 of 67

10. Number of Hopping Channels

10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

10.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=300 kHz, VBW=300 kHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Record the number of hopping channels.

Page 34 of 67

Report No.: TW2204150E

Date: 2022-04-14




10.4Test Result

Type of Modulation: GFSK

EUT	Bluetooth speakers		Model		MZ368
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	2	24 deg. C,	Humidity		56% RH
Operating Free	quency	Number of hopp	oing channels	Limit	Pass/ Fail
2402-2480MHz		79		≥ 15	Pass

Test Plot



Page 35 of 67

Report No.: TW2204150E


Date: 2022-04-14



Type of Modulation: $\pi/4D$ -QPSK

EUT	Bluetooth speakers		Model	MZ368	
Mode	Hopping On		Input Voltage		DC3.7V
Temperature	24 deg. C,		Humidity		56% RH
Operating Frequency		Number of hopping channels	Limit		Pass/ Fail
2402-2480MHz		79	≥ 15		Pass

Test Plot



Date: 2022-04-14



Page 36 of 67

11. Time of Occupancy (Dwell Time)

11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Report No.: TW2204150E

Date: 2022-04-14



Page 37 of 67

11.4 Test Result

Type of Modulation: GFSK

type of Modulation. Of bix										
Ant1										
	TX	Frequency	Packet	Duration of	Observation	Num of Pulse in	Dwell	Limit	\/a ==d:a+	
Mode	Туре	(MHz)	Type	Single Pulse (ms)	Period (s)	Observation Period	Time (ms)	(ms)	Verdict	
			DH1	0.384	31.600	319	122.496	<=400	Pass	
GFSK	SISO	SISO	HOPP	DH3	1.640	31.600	167	273.880	<=400	Pass
			DH5	2.888	31.600	111	320.568	<=400	Pass	
			2DH1	0.392	31.600	319	125.048	<=400	Pass	
Pi/4DQPSK	SISO	HOPP	2DH3	1.644	31.600	154	253.176	<=400	Pass	
			2DH5	2.892	31.600	99	286.308	<=400	Pass	


Page 38 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Plots:




Page 39 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Plots:




Page 40 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Plots:



Page 41 of 67

Report No.: TW2204150E


Date: 2022-04-14



Test Result

Type of Modulation: $\pi/4D$ -QPSK

Test Plots: **2DH1**




Page 42 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Plots:




Page 43 of 67

Report No.: TW2204150E

Date: 2022-04-14



Test Plots:




Report No.: TW2204150E Page 44 of 67

Date: 2022-04-14



12 Out of Band Measurement

12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Report No.: TW2204150E Page 45 of 67


Date: 2022-04-14



Type of Modulation: GFSK

Band Edge Test Result 12.4

Product:	Bluetooth speakers	Test Mode:	Low Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 46 of 67


Date: 2022-04-14



Type of Modulation: GFSK

12.4 Band Edge Test Result

Product:	Bluetooth speakers	Test Mode:	High Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 47 of 67


Date: 2022-04-14



Type of Modulation: GFSK

Band Edge Test Result

Product:	Bluetooth speakers	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 48 of 67


Date: 2022-04-14



Type of Modulation: GFSK

Band Edge Test Result

Product:	Bluetooth speakers	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 49 of 67


Date: 2022-04-14



Type of Modulation: $\pi/4D$ -QPSK

Out of Band Test Result 12.4

Product:	Bluetooth speakers	Test Mode:	Low Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 50 of 67


Date: 2022-04-14



Type of Modulation: $\pi/4D$ -QPSK

Band Edge Test Result

Product:	Bluetooth speakers	Test Mode:	High Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK



Page 51 of 67 Report No.: TW2204150E


Date: 2022-04-14



Type of Modulation: $\pi/4D$ -QPSK

Out of Band Test Result

Product:	Bluetooth speakers	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK



Report No.: TW2204150E Page 52 of 67


Date: 2022-04-14



Type of Modulation: $\pi/4D$ -QPSK

Out of Band Test Result

Product:	Bluetooth speakers	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK



Page 53 of 67

Report No.: TW2204150E

Date: 2022-04-14



12.4 Restricted band Measurement

EUT	Blueto	oth speakers	Model	MZ368			
Mode	Keep	Γransmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
	Low Channel, Horizontal						
2390	PK (dBµV/m)	42.95	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)		Limit	54(dBµV/m)			
	Low Channel, Vertical						
2390	PK (dBμV/m)	41.85	Limit	74(dBµV/m)			
	AV (dBμV/m)		Limit	54(dBµV/m)			

12.4 Restricted band Measurement

EUT	Blueto	oth speakers	Model	MZ368			
Mode	Keep	Transmitting	Input Voltage	DC3.7V			
Temperature	24	l deg. C,	Humidity	56% RH			
Test Result:	Pass		Detector	PK			
High Channel, Horizontal							
2483.5	PK (dBµV/m)	57.36	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)	49.83	Limit	$54(dB\mu V/m)$			
High Channel, Vertical							
2483.5	PK (dBµV/m)	54.85	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)	45.18	Limit	$54(dB\mu V/m)$			

Note: 1. For Restricted band test, All modulation mode was tested and only the worst case was reported. GFSK was the worst case.

2. "--" The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Report No.: TW2204150E

Date: 2022-04-14



Page 54 of 67

13.0 Antenna Requirement

13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected constructions PCB antenna with gain 0dBi maximum

Report No.: TW2204150E Page 55 of 67

Date: 2022-04-14




14.0 FCC ID Label

FCC ID: 2AT7C-MZ368

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 56 of 67 Report No.: TW2204150E

Date: 2022-04-14



15.0 Photo of testing

Conducted Emission Test Setup:




Page 57 of 67

Report No.: TW2204150E

Date: 2022-04-14



Radiated Emission Test Setup:



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the propert.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 58 of 67

Report No.: TW2204150E

Date: 2022-04-14



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 59 of 67 Report No.: TW2204150E

Date: 2022-04-14



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Page 60 of 67

Report No.: TW2204150E

Date: 2022-04-14



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 61 of 67

Report No.: TW2204150E

Date: 2022-04-14



Outside View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 62 of 67

Report No.: TW2204150E

Date: 2022-04-14



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 63 of 67 Report No.: TW2204150E

Date: 2022-04-14



Outside View



Page 64 of 67


Report No.: TW2204150E

Date: 2022-04-14



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the propert.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 65 of 67

Report No.: TW2204150E

Date: 2022-04-14



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the propert. discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Page 66 of 67

Report No.: TW2204150E

Date: 2022-04-14



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 67 of 67


Report No.: TW2204150E

Date: 2022-04-14



Inside view





-- End of Report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.