



# FCC TEST REPORT

**Test report**  
**On Behalf of**  
**Shenzhen Whakin Innovation Technology Co.,Ltd.**  
**For**  
**Car electric wireless charger**  
**Model No.: VK-AH02WL**  
**FCC ID: 2AT7TVK-AH02WL**

**Prepared for :** Shenzhen Whakin Innovation Technology Co.,Ltd.  
4/F, L Bldg, Jingtie Technology Industrial Park, No.49 Changjiangpu Rd. HeAo  
Community Longgang district, Shenzhen 518116, China

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

**Date of Test:** Jul. 22, 2019 ~ Jul. 31, 2019

**Date of Report:** Aug. 2, 2019

**Report Number:** HK1908021877-1E



### TEST RESULT CERTIFICATION

**Applicant's name** ..... : Shenzhen Whakin Innovation Technology Co.,Ltd.  
 4/F, L Bldg, Jingtie Technology Industrial Park, No.49  
**Address** ..... : Changjiangpu Rd. HeAo Community Longgang district,  
 Shenzhen 518116, China

**Manufacture's Name**..... : Shenzhen Whakin Innovation Technology Co.,Ltd.  
 4/F, L Bldg, Jingtie Technology Industrial Park, No.49  
**Address** ..... : Changjiangpu Rd. HeAo Community Longgang district,  
 Shenzhen 518116, China

**Product description**

**Trade Mark** ..... : N/A  
**Product name**..... : Car electric wireless charger  
**Model and/or type reference** : VK-AH02WL

**Standards** ..... : FCC Rules and Regulations Part 15 Subpart C (Section 15.209),  
 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :  
**Date (s) of performance of tests**..... : Jul. 22, 2019 ~ Jul. 31, 2019  
**Date of Issue**..... : Aug. 2, 2019  
**Test Result**..... : **Pass**

Testing Engineer : Gary Qian  
 (Gary Qian)

Technical Manager : Eden Hu  
 (Eden Hu)

Authorized Signatory : Jason Zhou  
 (Jason Zhou)



<b>Table of Contents</b>	<b>Page</b>
1 . TEST SUMMARY.....	4
1.1 TEST PROCEDURES AND RESULTS .....	4
1.2 TEST FACILITY .....	4
1.3 MEASUREMENT UNCERTAINTY .....	4
2. GENERAL INFORMATION .....	5
2.1 General Description of EUT .....	5
2.2. Carrier Frequency of Channels.....	6
2.3 Operation of EUT during testing .....	6
2.4 Description of Test Setup.....	6
2.5 Measurement Instruments List.....	7
3. CONDUCTED EMISSION TEST .....	8
3.1 Block Diagram of Test Setup .....	8
3.2 Conducted Power Line Emission Limit .....	8
3.3 Test Procedure.....	8
3.4 Test Result .....	8
4. Occupied Bandwidth.....	11
4.1 Block Diagram of Test Setup .....	11
4.2 Rules and specifications .....	11
4.3 Test Procedure.....	11
4.4 Test Result .....	11
5. RADIA TED EMISSIONS.....	13
5.1 Block Diagram of Test Setup .....	13
5.2 Rules and specifications .....	14
5.3 Test Procedure.....	15
5.4 Test Result.....	15
6 ANTENNA REQUIREMENT.....	18
7. PHOTOGRAPH OF TEST.....	19
7.1 Radiated Emission .....	19
7.2 Conducted Emission .....	20
8. PHOTOGRAPH OF EUT.....	21



## 1. TEST SUMMARY

### 1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

### 1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

### 1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty	
Conducted Emission Expanded Uncertainty	= 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.06dB, k=2



## 2. GENERAL INFORMATION

### 2.1 General Description of EUT

Equipment	Car electric wireless charger
Model Name	VK-AH02WL
Serial No.	N/A
Model Difference	/
Trade Mark	N/A
FCC ID	2AT7TVK-AH02WL
Antenna Type	Coil Antenna
Antenna Gain	1dBi
Operation frequency	125KHz
Number of Channels	1
Modulation Type	ASK
Power Rating	Input voltage: DC5V/2A,DC9V/2A Output: 10W Max



### 2.2. Carrier Frequency of Channels

Operation Frequency each of channel	
Channel	Frequency
1	125KHz


### 2.3 Operation of EUT during testing

Operating Mode

The mode is used: Transmitting mode

### 2.4 Description of Test Setup

Operation of EUT during testing



Setup: Transmission mode

- Mobile phone information  
Model: S7  
Input: 5VDC




## 2.5 Measurement Instruments List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 27, 2018	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 27, 2018	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 27, 2018	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 27, 2018	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2017	3 Year



### 3. CONDUCTED EMISSION TEST

#### 3.1 Block Diagram of Test Setup



#### 3.2 Conducted Power Line Emission Limit

According to FCC Part 15.207(a)

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

\* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207 Line Conducted Emission Limit is same as above table.

#### 3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes

#### 3.4 Test Result


PASS





Please refer to following diagram for individual

Test Specification: Line




Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
3.318000	37.40	9.8	56	18.6	QP	L1	GND
3.592500	37.40	9.8	56	18.6	QP	L1	GND
4.146000	37.50	9.8	56	18.5	QP	L1	GND
4.425000	36.60	9.8	56	19.4	QP	L1	GND
4.699500	37.20	9.8	56	18.8	QP	L1	GND
4.974000	37.30	9.8	56	18.7	QP	L1	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
3.318000	28.90	9.8	46	17.1	AV	L1	GND
3.592500	31.60	9.8	46	14.4	AV	L1	GND
4.146000	30.80	9.8	46	15.2	AV	L1	GND
4.425000	27.60	9.8	46	18.4	AV	L1	GND
4.699500	29.40	9.8	46	16.6	AV	L1	GND
4.978500	25.90	9.8	46	20.1	AV	L1	GND

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



Test Specification: Neutral




Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.465000	37.60	10.0	57	19.0	QP	N	GND
2.764500	34.10	9.8	56	21.9	QP	N	GND
3.318000	34.80	9.8	56	21.2	QP	N	GND
3.867000	34.00	9.8	56	22.0	QP	N	GND
4.141500	34.00	9.8	56	22.0	QP	N	GND
4.425000	34.10	9.8	56	21.9	QP	N	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
3.318000	26.80	9.8	46	19.2	AV	N	GND
3.592500	29.40	9.8	46	16.6	AV	N	GND
3.867000	29.00	9.8	46	17.0	AV	N	GND
4.425000	23.90	9.8	46	22.1	AV	N	GND
4.699500	27.30	9.8	46	18.7	AV	N	GND
4.974000	28.80	9.8	46	17.2	AV	N	GND

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level



#### 4. Occupied Bandwidth

##### 4.1 Block Diagram of Test Setup



##### 4.2 Rules and specifications

CFR 47 Part 15.215(c)

ANSI C63.10-2013


##### 4.3 Test Procedure

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equip compliance with the 20dB attenuation specification may base on measurement at the intentional radiator's antenna output terminal unless the intentional radiator uses a permanently attached antenna, in which case compliance shall be demonstrated by measuring the radiated emissions.

##### 4.4 Test Result



PASS

Mode	Freq (KHz)	20dB Bandwidth (KHz)	Limit (kHz)	Conclusion
Tx Mode	125	2.851	/	PASS



## 5. RADIA TED EMISSIONS

### 5.1 Block Diagram of Test Setup





### 5.2 Rules and specifications

CFR 47 Part 15, section 15.205

Only spurious emissions are permitted in any of the frequency bands listed the tables in these sections.

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

CFR 47 Part 15, section 15.209

The emissions from an intentional radiator shall not exceed the limits in the tables in these sections using an average detector

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

Limit calculation and transfer to 3m distance as showed in the following table:

Frequency (MHz)	Limit (dBuV/m)	Distance (m)
0.009-0.490	$20\log(2400/F(KHz))+40\log(300/3)$	3
0.490-1.705	$20\log(24000/F(KHz))+40\log(30/3)$	3
1.705-30.0	69.5	3
30-88	40.0	3
88-216	43.5	3
216-960	46.0	3
Above 960	54.0	3

CFR 47 Part 15, section 15.35

When average radiated emission measurements are specified, the limit on the peak level of the radio Frequency emission is 20dB above the maximum permitted average emission limit.

Transmitter Spurious Emissions 9KHz-30MHz			
	9-150KHz	150-490KHz	490KHz-30MHz
Resolution Bandwidth	200Hz	9KHz	9KHz
Video Bandwidth	2KHz	100KHz	100KHz
Detector	Peak	Peak	Peak
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep Time	Auto	Auto	Auto



### 5.3 Test Procedure

Measurement distance 3m

For the measurement range up to 30MHz in the following plots the field strength result from 3m Distance measurement are extrapolated to 300m and 30m distance respectively, by 40dB/decade, According to part 15.31(f)(2), per antenna factor scaling.

Measurements below 1000MHz are performed with a peak detector and compared to average limits, Measurements with an average detector are not required.

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.4 Test Result

PASS

For 9KHz-30MHz


Freq. (MHz)	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limits 3m (dBuV/m)	Margin (dBuV/m)
0.041	Peak	25.07	24.8	48.78	115.35	66.57
0.125	Peak	46.37	24.8	72.68	105.67	32.99
0.987	Peak	26.16	25.41	48.68	67.72	19.04
8.689	Peak	26.75	25.41	51.22	69.50	18.28



For 30MHz-1GHz

Please refer to following diagram for individual

Antenna polarity: V




Suspected List								
NO.	Freq. [MHz]	Result Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	69.770	28.37	-18.15	40.00	11.63	100	51	Vertical
2	143.975	32.38	-19.34	43.50	11.12	100	241	Vertical
3	216.240	19.94	-14.93	46.50	26.56	100	135	Vertical
4	269.590	21.98	-13.45	46.50	24.52	100	209	Vertical
5	412.665	27.59	-9.79	46.50	18.91	100	296	Vertical
6	551.375	23.48	-6.79	46.50	23.02	100	8	Vertical

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level





Antenna polarity: H



Suspected List								
NO.	Freq. [MHz]	Result Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	62.980	14.91	-16.41	40.00	25.09	300	208	Horizontal
2	95.475	21.54	-16.75	43.50	21.96	300	183	Horizontal
3	144.460	22.6	-19.31	43.50	20.90	300	95	Horizontal
4	268.135	26.44	-13.48	46.50	20.06	100	4	Horizontal
5	380.170	24.64	-10.59	46.50	21.86	100	205	Horizontal
6	463.105	25.85	-8.79	46.50	20.65	100	177	Horizontal

Remark: Transd = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

## 6 ANTENNA REQUIREMENT

### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


### Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### Antenna Connected Construction



The antenna used in this product is a Coil Antenna, The directional gains of antenna used for transmitting is 1dBi.

### ANTENNA



## 7. PHOTOGRAPH OF TEST

### 7.1 Radiated Emission





## 7.2 Conducted Emission



### 8. PHOTOGRAPH OF EUT

#### External Photos

















### Internal Photos







※※※※THE END※※※※