

ISED CABid: ES1909

Test Report No:  
 NIE: 64670RRF.005

## Partial Test Report

### USA FCC Part 15.247, 15.209

### CANADA RSS-247, RSS-Gen

(*) Identification of item tested	Smart Cooking Sensor
(*) Trademark	Safera
(*) Model and /or type reference	Sense Pro (Model code: IFU10B-PRO)
Other identification of the product	HW Version: B SW Version: 1.0.25 FCC ID: 2AT88-2000021194
(*) Features	Bluetooth LE, 802.15.4 (ZigBee-type), Wi-Fi 802.11 b/g/n (HT20)
Manufacturer	SAFERA OY Tekniikantie 4 B, FI-02150 Espoo, Finland.
Test method requested, standard	USA FCC Part 15.247 (10-1-20 Edition): Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-20 Edition): Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 amendment 1 (March 2019). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Approved by (name / position & signature)	Rafael López EMC Consumer & RF Lab. Manager
Date of issue	2021-12-23
Report template No	FDT08_23 (*) "Data provided by the client"



## Index

---

INDEX .....	2
COMPETENCES AND GUARANTEES .....	3
GENERAL CONDITIONS .....	3
UNCERTAINTY .....	3
DATA PROVIDED BY THE CLIENT .....	3
USAGE OF SAMPLES .....	4
TEST SAMPLE DESCRIPTION .....	5
IDENTIFICATION OF THE CLIENT .....	6
TESTING PERIOD AND PLACE .....	6
DOCUMENT HISTORY .....	6
ENVIRONMENTAL CONDITIONS .....	6
REMARKS AND COMMENTS .....	7
TESTING VERDICTS .....	8
SUMMARY .....	8
<b>APPENDIX A: TEST RESULTS. BLUETOOTH 5.0 (1 &amp; 2 MBPS):</b> .....	9
INDEX .....	10
TEST CONDITIONS .....	11
TEST CASES DETAILS .....	12
<i>RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power</i> .....	12

## Competences and guarantees

---

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that covers the performed tests in this report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory, CABid: ES1909, with the appropriate scope of accreditation that covers the performed tests in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

## General conditions

---

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

## Uncertainty

---

Uncertainty (factor  $k=2$ ) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

## Data provided by the client

---

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample Safera Sense is a Smart Cooking Sensor with the following main features:  
Sensors for monitoring the stove area and detecting cooking processes, as well as estimating indoor air quality. Processor and algorithms for detecting stove overheating, which will result in an audible alarm. Support for Bluetooth communication to smartphones and iOS / Android application in order to visualize data. Support for proprietary 802.15.4 based radio protocol for controlling some Safera Accessories (for example Power Control Unit for Stove). Support for Wi-Fi for connection to Safera Cloud or other Internet of Things -services.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Usage of samples

---

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
64670/029	Smart Cooking Sensor	Sense Pro	1727644012	2020-11-20

Sample S/01 has undergone the following test(s): The CONDUCTED tests indicated in Appendix A.

## Test sample description

Ports..... :	Port name and description		Cable				
			Specified length [m]	Attached during test	Shielded		
	N/A			<input type="checkbox"/>	<input type="checkbox"/>		
Rated power supply .....	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	DC:	For the final product: 3 x AA Alkaline batteries as power supply. Operational voltage from 3.0 V to 5.0 V. For testing purposes, power is wired externally to some sample units. This is done to make it possible to use an external power supply. When using an external power supply, allowed voltages are 3.0 VDC to 5.0 VDC.					
Rated Power .....	Normal operating mode: approx. 0.1 mA average Max. short term current consumption 150 mA Max. very short peak current consumption approx. 400 mA (ms level)						
Clock frequencies..... :	64 MHz main processor clock (nRF52840) 80-160 MHz auxiliary network processor clock (ESP8285) 32.768 kHz RTC auxiliary clock						
Other parameters .....	Not provided data						
Software version .....	1.0.25						
Hardware version .....	B						
Dimensions in mm (W x H x D) ...:	Not provided data						
Mounting position .....	<input type="checkbox"/>	Table top equipment					
	<input checked="" type="checkbox"/>	Wall/Ceiling mounted equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input type="checkbox"/>	Hand-held equipment					
	<input type="checkbox"/>	Other:					
Modules/parts..... :	Module/parts of test item		Type	Manufacturer			
	Sensor Unit			Safera			
Accessories (not part of the test item) .....	Description		Type	Manufacturer			
	Power supply						
	Batteries						
Documents as provided by the applicant..... :	Description		File name	Issue date			
	User Manual						

<sup>(3)</sup> Only for Medical Equipment

## Identification of the client

SAFERA OY

Tekniikantie 4 B, FI-02150 Espoo, Finland.

## Testing period and place

<b>Test Location</b>	DEKRA Testing and Certification S.A.U.
<b>Date (start)</b>	2020-12-18
<b>Date (finish)</b>	2020-12-18

## Document history

<b>Report number</b>	<b>Date</b>	<b>Description</b>
64670RRF.005	2021-12-23	First release.

## Environmental conditions

In the chamber for conducted measurements, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %

## Remarks and comments

---

The tests have been performed by the technical personnel: Javier Miguel Nadales.

Used instrumentation:

### Conducted Measurements

		Last Calibration	Due Calibration
1.	Shielded Room ETS LINDGREN S101	N/A	N/A
2.	Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2021/02	2023/02
3.	Analog Power Supply DC 40V/40A NGPE 40/40 Rohde and Schwarz	N/A	N/A
4.	Digital multimeter FLUKE 179	2021/06	2022/06

## Testing verdicts

Fail	F
Not applicable	N/A
Not measured	N/M
Pass	P

## Summary

### Bluetooth 5.0 (1 & 2 Mbps):

Requirement – Test case	FCC PART 15 PARAGRAPH / RSS-247	Verdict	Remark
RSS-247 5.2 (a) / FCC 15.247 (a) (2) 6 dB Bandwidth		N/M	(1)
RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power		Pass	
RSS-247 5.2 (b) / FCC 15.247 (e) Power Spectral Density		N/M	(1)
RSS-247 5.5 / FCC 15.247 (d) Band-edge emissions compliance (Transmitter)		N/M	(1)
RSS-247 5.5 / FCC 15.247 (d) Emission limitations radiated (Transmitter)		N/M	(1)
99dBw Occupied Channel Bandwidth 99%		N/M	(1)
<u>Supplementary information and remarks:</u>			
1) Test not requested			



## Appendix A: Test results. Bluetooth 5.0 (1 & 2 Mbps):

## INDEX

---

TEST CONDITIONS .....	11
TEST CASES DETAILS .....	12
<i>RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power</i> .....	12

## TEST CONDITIONS

---

(\*): Data provided by the client.

### POWER SUPPLY (\*):

Vnominal:	4.5 V DC
Type of Power Supply:	External power supply

### ANTENNA (\*):

Type of Antenna:	Integral
Maximum Declared Antenna Gain:	1.5 dBi

### TEST FREQUENCIES (\*):

Low Channel:	2402 MHz
Middle Channel:	2440 MHz
High Channel:	2480 MHz

### CONDUCTED MEASUREMENTS:

The equipment under test was set up in a shielded room and it is connected to the TS8997 using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



## TEST CASES DETAILS

### RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power

#### Limits

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).

The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

#### Results

The maximum peak conducted output power level in the fundamental emission was measured using the method according to point 11.9.1.1 "RBW  $\geq$  DTS bandwidth" of ANSI C.63.10-2013.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Maximum Declared Antenna Gain: 1.5 dBi

Modulation: Bluetooth 5.0 (1 & 2 Mbps):

Operation Band (MHz)	Equipment	Freq (MHz)	Max Conducted Power (dBm)	Max E.I.R.P (dBm)
[2400, 2483.5]	BLE 1Mbps	2402.00	-0.37	1.13
[2400, 2483.5]	BLE 1Mbps	2440.00	-1.12	0.38
[2400, 2483.5]	BLE 1Mbps	2480.00	-2.16	-0.66

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Operation Band (MHz)	Equipment	Freq (MHz)	Max Conducted Power (dBm)	Max E.I.R.P (dBm)
[2400, 2483.5]	BLE 2Mbps	2402.00	-0.36	1.14
[2400, 2483.5]	BLE 2Mbps	2440.00	-1.13	0.37
[2400, 2483.5]	BLE 2Mbps	2480.00	-2.15	-0.65

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.


#### Verdict

Pass


Uncertainty 0.99dB

**BLE 1Mbps:**


-Low Channel:



-Middle Channel:




-High Channel:




**BLE 2Mbps:**

-Low Channel:



-Middle Channel:



-High Channel:

