



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04

Report Template Revision Date: 2018-07-06

# TEST REPORT

**Report No. :** CQASZ20201200047EX-01

**Applicant:** Wenzhou Morning Electronics Co.,LTD

**Address of Applicant:** NO.238, Wei 11 Road, Yueqing Economic Development Zone, Yueqing, Zhejiang, China

**Equipment Under Test (EUT):**

**Product:** Smart Switch

**All Model No.:** WS-EU3-RF, SYT-A01, SYT-B01, SYT-C01, SYT-ZB01, WS-EU1-RF, WS-US1-RF, WS-EU1-L, WS-US1-L, WS-EUB1-WR, ZS-EUB1, ZTS-EU1, ZTS-EU1-WR, ZTS-US1, ZTS-US1-WR, WS-EUR-C, WS-USR-C, WS-EUR-2C, WS-USR-2C, WS-EUR-F, WS-USR-F, WS-EUR-FL, WS-USR-FL, WS-EUR-D, WS-USR-D, ZTS-EUR-C, ZTS-USR-C, ZTS-EUR-2C, ZTS-USR-2C, ZTS-EUR-F, ZTS-USR-F, ZTS-EUR-FL, ZTS-USR-FL, ZTS-EUR-D, ZTS-USR-D, SR-WS1, SR-ZS1, BS-EU BS-US BS-EUB

**Test Model No.:** WS-EU3-RF

**Brand Name:** N/A

**FCC ID:** 2AT8P-WSEUNX

**Standards:** 47 CFR FCC Part 15 Subpart C 15.247

**Date of Test:** Dec. 18, 2020 to Jan. 04, 2021

**Date of Issue:** Jan. 04, 2021

**Test Result :** PASS

**Tested By:** Jun Li  
( Jun Li )

**Reviewed By:** Ares Liu  
( Ares Liu )

**Approved By:** Sheek Luo  
( Sheek Luo )



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested.

Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History of Report

Report No.	Version	Description	Issue Date
CQASZ20201200047EX-01	Rev.01	Initial report	Jan. 04, 2021

## 2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

### 3 Contents

	Page
1 VERSION.....	2
2 TEST SUMMARY .....	3
3 CONTENTS.....	4
4 GENERAL INFORMATION .....	5
4.1 CLIENT INFORMATION .....	5
4.2 GENERAL DESCRIPTION OF EUT .....	5
4.3 DESCRIPTION OF SUPPORT UNITS .....	7
4.4 TEST LOCATION .....	7
4.5 TEST FACILITY .....	7
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	8
4.7 DEVIATION FROM STANDARDS .....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	8
4.10 EQUIPMENT LIST.....	9
5 TEST RESULTS AND MEASUREMENT DATA.....	10
5.1 ANTENNA REQUIREMENT.....	10
5.2 CONDUCTED EMISSIONS .....	11
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER .....	15
5.4 6DB OCCUPY BANDWIDTH .....	16
5.5 POWER SPECTRAL DENSITY .....	21
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	26
5.7 RF CONDUCTED SPURIOUS EMISSIONS .....	31
5.8 RADIATED SPURIOUS EMISSIONS.....	45
5.8.1 Radiated emission below 1GHz.....	48
5.8.2 Transmitter emission above 1GHz .....	50
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY .....	52
6 PHOTOGRAPHS - EUT TEST SETUP.....	58
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	60

## 4 General Information

### 4.1 Client Information

Applicant:	Wenzhou Morning Electronics Co.,LTD
Address of Applicant:	NO.238, Wei 11 Road, Yueqing Economic Development Zone, Yueqing, Zhejiang, China
Manufacturer:	Wenzhou Morning Electronics Co.,LTD
Address of Manufacturer:	NO.238, Wei 11 Road, Yueqing Economic Development Zone, Yueqing, Zhejiang, China

### 4.2 General Description of EUT

Product Name:	Smart Switch
Model No.:	WS-EU3-RF
All Model No.:	WS-EU3-RF, SYT-A01, SYT-B01, SYT-C01, SYT-ZB01, WS-EU1-RF, WS-US1-RF, WS-EU1-L, WS-US1-L, WS-EUB1-WR, ZS-EUB1, ZTS-EU1, ZTS-EU1-WR, ZTS-US1, ZTS-US1-WR, WS-EUR-C, WS-USR-C, WS-EUR-2C, WS-USR-2C, WS-EUR-F, WS-USR-F, WS-EUR-FL, WS-USR-FL, WS-EUR-D, WS-USR-D, ZTS-EUR-C, ZTS-USR-C, ZTS-EUR-2C, ZTS-USR-2C, ZTS-EUR-F, ZTS-USR-F, ZTS-EUR-FL, ZTS-USR-FL, ZTS-EUR-D, ZTS-USR-D, SR-WS1, SR-ZS1, BS-EU, BS-US, BS-EUB
Trade Mark:	N/A
Hardware version:	V1.0
Software version:	V2.5.8
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422 MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n(HT40): 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DBPSK) IEEE for 802.11 g/n(HT20)/n(HT40) : OFDM
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare )
Antenna Type	PCB Antenna
Antenna Gain	0dBi
Power Supply:	AC 120V 50/60Hz
Adapter Information:	/

Note: Please refer to the instruction manual for details.

There are many models here, but only tested: WS-EU3-RF, Their electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20)		For 802.11n (HT40)	
Channel	Frequency	Channel	Frequency
The Lowest channel	2412MHz	The Lowest channel	2422MHz
The Middle channel	2437MHz	The Middle channel	2437MHz
The Highest channel	2462MHz	The Highest channel	2452MHz

Note: Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

### 4.4 Test Location

All tests were performed at:

**Shenzhen Huaxia Testing Technology Co., Ltd.,**

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **ISED Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

#### 4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	$3 \times 10^{-8}$	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8°C	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

#### 4.7 Deviation from Standards

None.

#### 4.8 Abnormalities from Standard Conditions

None.

#### 4.9 Other Information Requested by the Customer

None.



#### 4.10 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/9/22	2021/9/21
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/24	2021/10/23
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2020/9/22	2021/9/21
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2020/10/28	2021/10/27
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2020/10/24	2021/10/23
Bilog Antenna	R&S	HL562	CQA-011	2020/9/22	2021/9/21
Horn Antenna	R&S	HF906	CQA-012	2020/9/22	2021/9/21
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2020/9/22	2021/9/21
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2020/9/22	2021/9/21
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2020/9/22	2021/9/21
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/22	2021/9/21
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/22	2021/9/21
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2020/9/22	2021/9/21
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2020/9/22	2021/9/21
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/22	2021/9/21
EMI Test Receiver	R&S	ESPI3	CQA-013	2020/9/22	2021/9/21
LISN	R&S	ENV216	CQA-003	2020/11/1	2021/10/30
Coaxial cable	CQA	N/A	CQA-C009	2020/9/22	2021/9/21

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 5 Test results and Measurement Data

### 5.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement:  An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:  The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
<p>EUT  Antenna:</p>	<p>Antenna</p> 
<p>The antenna is PCB antenna. The best case gain of the antenna is 0dBi.</p>	


## 5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	<ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>		

<p>Test Setup:</p>	<p>The diagram illustrates the test setup within a shielding room. It features a table with a height of 80cm. On this table, the Equipment Under Test (EUT) and the Antenna (AE) are positioned. To the right, a Test Receiver is placed on a separate table. Two Line Impedance Stabilization Networks (LISN1 and LISN2) are used to interface with the AC Mains. LISN1 is connected to the AC Mains and the EUT, with a specified distance of 80cm. LISN2 is connected to the AE and the AC Mains. A Ground Reference Plane is indicated at the base of the setup.</p>
<p>Exploratory Test Mode:</p>	<p>Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.</p>
<p>Final Test Mode:</p>	<p>All modes of 802.11b/g/n20/n40 were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below</p>
<p>Test Voltage:</p>	<p>AC120V/60Hz</p>
<p>Test Results:</p>	<p>Pass</p>

Measurement Data

Live Line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	60.71	-0.13	60.58	65.36	-4.78	QP	
2		0.1620	43.61	-0.13	43.48	55.36	-11.88	AVG	
3		0.2380	40.51	-0.11	40.40	52.16	-11.76	AVG	
4		0.2620	56.72	-0.11	56.61	61.36	-4.75	QP	
5	*	0.4380	52.44	-0.02	52.42	57.10	-4.68	QP	
6		0.4780	36.34	-0.03	36.31	46.37	-10.06	AVG	
7		0.7820	47.12	-0.07	47.05	56.00	-8.95	QP	
8		0.7980	33.81	-0.07	33.74	46.00	-12.26	AVG	
9		0.9620	32.49	-0.11	32.38	46.00	-13.62	AVG	
10		1.0220	42.70	-0.12	42.58	56.00	-13.42	QP	
11		12.1140	21.17	-0.14	21.03	50.00	-28.97	AVG	
12		12.6860	38.27	-0.14	38.13	60.00	-21.87	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1580	60.62	-0.13	60.49	65.56	-5.07	QP	
2		0.1580	43.40	-0.13	43.27	55.56	-12.29	AVG	
3		0.2020	59.35	-0.13	59.22	63.52	-4.30	QP	
4		0.2020	42.21	-0.13	42.08	53.52	-11.44	AVG	
5		0.2420	58.37	-0.11	58.26	62.02	-3.76	QP	
6		0.2420	40.18	-0.11	40.07	52.02	-11.95	AVG	
7	*	0.4260	54.43	-0.02	54.41	57.33	-2.92	QP	
8		0.4260	36.08	-0.02	36.06	47.33	-11.27	AVG	
9		0.6500	33.40	-0.05	33.35	46.00	-12.65	AVG	
10		0.6580	50.20	-0.05	50.15	56.00	-5.85	QP	
11		0.9340	32.34	-0.11	32.23	46.00	-13.77	AVG	
12		0.9540	46.65	-0.11	46.54	56.00	-9.46	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

### 5.3 Conducted Peak & Average Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20)/n(HT40); Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

#### WIFI

Type	Test channel	Peak Output Power (dBm)	Average Output Power dBm)	Limit (dBm)	Result
802.11b	Lowest	14.63	10.89	30.00	Pass
	Middle	13.47	9.73		
	Highest	12.97	9.07		
802.11g	Lowest	13.97	8.35	30.00	Pass
	Middle	13.57	7.15		
	Highest	11.35	4.70		
802.11n(HT20)	Lowest	13.08	8.11	30.00	Pass
	Middle	12.78	7.76		
	Highest	11.54	6.41		
802.11n(HT40)	Lowest	12.53	7.56	30.00	Pass
	Middle	12.10	6.03		
	Highest	11.01	6.08		

Note: 1.The test results including the cable lose.

## 5.4 6dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20)/n(HT40); Only the worst case is recorded in the report.
Limit:	$\geq 500$ kHz
Test Results:	Pass




### Measurement Data




Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	Lowest	11.342	$\geq 500$	Pass
	Middle	8.804		
	Highest	8.833		
802.11g	Lowest	15.74	$\geq 500$	Pass
	Middle	15.77		
	Highest	15.34		
802.11n(HT20)	Lowest	12.60	$\geq 500$	Pass
	Middle	12.55		
	Highest	11.31		
802.11n(HT40)	Lowest	33.01	$\geq 500$	Pass
	Middle	32.95		
	Highest	32.96		



Test plot as follows:




<p>11G/LCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.41200000 GHz</p> <p>Center Freq: 2.41200000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.412 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 17.351 MHz</p> <p>Total Power 14.8 dBm</p> <p>Transmit Freq Error -472.38 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 15.74 MHz</p> <p>x dB -6.00 dB</p> <p>Frequency 2.41200000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/MCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.43700000 GHz</p> <p>Center Freq: 2.43700000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.437 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 17.499 MHz</p> <p>Total Power 13.7 dBm</p> <p>Transmit Freq Error -562.54 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 15.77 MHz</p> <p>x dB -6.00 dB</p> <p>Frequency 2.43700000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/HCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.46200000 GHz</p> <p>Center Freq: 2.46200000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.462 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 16.664 MHz</p> <p>Total Power 11.3 dBm</p> <p>Transmit Freq Error -138.02 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 15.34 MHz</p> <p>x dB -6.00 dB</p> <p>Frequency 2.46200000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>

<p>11N20/LCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.41200000 GHz</p> <p>Center Freq: 2.41200000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.412 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 17.871 MHz</p> <p>Total Power 14.8 dBm</p> <p>Transmit Freq Error -509.67 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 12.60 MHz</p> <p>x dB -6.00 dB</p> <p>MSG STATUS</p>
<p>11N20/MCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.43700000 GHz</p> <p>Center Freq: 2.43700000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.437 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 16.998 MHz</p> <p>Total Power 11.4 dBm</p> <p>Transmit Freq Error -211.29 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 12.55 MHz</p> <p>x dB -6.00 dB</p> <p>MSG STATUS</p>
<p>11N20/HCH</p>	 <p>Keysight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.46200000 GHz</p> <p>Center Freq: 2.46200000 GHz</p> <p>Trig: Free Run</p> <p>Avg/Hold: 100/100</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm</p> <p>Center 2.462 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 3.867 ms</p> <p>Occupied Bandwidth 16.830 MHz</p> <p>Total Power 8.85 dBm</p> <p>Transmit Freq Error -120.60 kHz</p> <p>% of OBW Power 99.00 %</p> <p>x dB Bandwidth 11.31 MHz</p> <p>x dB -6.00 dB</p> <p>MSG STATUS</p>

<p>11N40/LCH</p>	<p>Keysight Spectrum Analyzer - Occupied BW          Center Freq: 2.42200000 GHz          Center Freq: 2.42200000 GHz          Trig: Free Run          Avg/Hold: 100/100          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm          Log          Center 2.422 GHz          #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms</p> <p><b>Occupied Bandwidth 35.974 MHz</b>          Total Power 12.9 dBm</p> <p>Transmit Freq Error -304.15 kHz % of OBW Power 99.00 %          x dB Bandwidth 33.01 MHz x dB -6.00 dB</p> <p>Frequency          Center Freq 2.42200000 GHz          CF Step 8.000000 MHz Man          Freq Offset 0 Hz</p>	
<p>11N40/MCH</p>	<p>Keysight Spectrum Analyzer - Occupied BW          Center Freq: 2.43700000 GHz          Center Freq: 2.43700000 GHz          Trig: Free Run          Avg/Hold: 100/100          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm          Log          Center 2.437 GHz          #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms</p> <p><b>Occupied Bandwidth 36.105 MHz</b>          Total Power 12.6 dBm</p> <p>Transmit Freq Error -401.46 kHz % of OBW Power 99.00 %          x dB Bandwidth 32.95 MHz x dB -6.00 dB</p> <p>Frequency          Center Freq 2.43700000 GHz          CF Step 8.000000 MHz Man          Freq Offset 0 Hz</p>	
<p>11N40/HCH</p>	<p>Keysight Spectrum Analyzer - Occupied BW          Center Freq: 2.45200000 GHz          Center Freq: 2.45200000 GHz          Trig: Free Run          Avg/Hold: 100/100          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 10.00 dBm          Log          Center 2.452 GHz          #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms</p> <p><b>Occupied Bandwidth 36.225 MHz</b>          Total Power 11.4 dBm</p> <p>Transmit Freq Error -355.64 kHz % of OBW Power 99.00 %          x dB Bandwidth 32.96 MHz x dB -6.00 dB</p> <p>Frequency          Center Freq 2.45200000 GHz          CF Step 8.000000 MHz Man          Freq Offset 0 Hz</p>	


## 5.5 Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20)/n(HT40); Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass




### Measurement Data

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	Lowest	-15.403	8	Pass
	Middle	-16.668		
	Highest	-17.124		
802.11g	Lowest	-18.995	8	Pass
	Middle	-20.389		
	Highest	-22.577		
802.11n(HT20)	Lowest	-15.621	8	Pass
	Middle	-19.984		
	Highest	-21.229		
802.11n(HT40)	Lowest	-24.292	8	Pass
	Middle	-24.673		
	Highest	-26.508		




Test plot as follows:




<p>11G/LCH</p>	 <p>KeySight Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz Mkr1 2.414 45 GHz -18.995 dBm Center Freq 2.41200000 GHz Start Freq 2.400198000 GHz Stop Freq 2.423802000 GHz CF Step 2.360400 MHz Sweep 2.504 s (501 pts)</p>
<p>11G/MCH</p>	 <p>KeySight Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz Mkr1 2.439 46 GHz -20.389 dBm Center Freq 2.43700000 GHz Start Freq 2.425174000 GHz Stop Freq 2.448826000 GHz CF Step 2.365200 MHz Sweep 2.510 s (501 pts)</p>
<p>11G/HCH</p>	 <p>KeySight Spectrum Analyzer - Swept SA Center Freq 2.46200000 GHz Mkr1 2.464 44 GHz -22.577 dBm Center Freq 2.46200000 GHz Start Freq 2.450493500 GHz Stop Freq 2.473506500 GHz CF Step 2.301300 MHz Sweep 2.442 s (501 pts)</p>

<p>11N20/LCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz Mkr1 2.411 659 8 GHz -15.621 dBm Center 2.412000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 18.90 MHz Sweep 2.005 s (501 pts)</p>
<p>11N20/MCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz Mkr1 2.436 70 GHz -19.984 dBm Center 2.437000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 18.82 MHz Sweep 1.997 s (501 pts)</p>
<p>11N20/HCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.46200000 GHz Mkr1 2.462 61 GHz -21.229 dBm Center 2.462000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 16.96 MHz Sweep 1.800 s (501 pts)</p>




<p>11N40/LCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.42200000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Sweep 5.253 s (501 pts)</p> <p>Mkr1 2.414 47 GHz -24.292 dBm</p> <p>Frequency Auto Tune Center Freq 2.42200000 GHz Start Freq 2.397244750 GHz Stop Freq 2.446755250 GHz CF Step 4.951050 MHz Freq Offset 0 Hz Scale Type Log</p>
<p>11N40/MCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Sweep 5.243 s (501 pts)</p> <p>Mkr1 2.429 49 GHz -24.673 dBm</p> <p>Frequency Auto Tune Center Freq 2.43700000 GHz Start Freq 2.412291250 GHz Stop Freq 2.461708750 GHz CF Step 4.941750 MHz Freq Offset 0 Hz Scale Type Log</p>
<p>11N40/HCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.45200000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Sweep 5.246 s (501 pts)</p> <p>Mkr1 2.444 48 GHz -26.508 dBm</p> <p>Frequency Auto Tune Center Freq 2.45200000 GHz Start Freq 2.427277750 GHz Stop Freq 2.476722250 GHz CF Step 4.944450 MHz Freq Offset 0 Hz Scale Type Log</p>


## 5.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20)/n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test plot as follows:




<p>11G/LCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.37600000 GHz Start 2.31000 GHz, Stop 2.44200 GHz Mkr2 2.400 000 GHz, -26.303 dBm Mkr1 2.390 000 GHz, -41.491 dBm Mkr3 2.408 208 GHz, -1.683 dBm</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.390 000 GHz</td> <td>-41.491 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.400 000 GHz</td> <td>-26.303 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.408 208 GHz</td> <td>-1.683 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.390 000 GHz	-41.491 dBm				2	N	1	f	2.400 000 GHz	-26.303 dBm				3									4	N	1	f	2.408 208 GHz	-1.683 dBm				<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.376000000 GHz</p> <p>Start Freq 2.310000000 GHz</p> <p>Stop Freq 2.442000000 GHz</p> <p>CF Step 13.200000 MHz Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																							
1	N	1	f	2.390 000 GHz	-41.491 dBm																																										
2	N	1	f	2.400 000 GHz	-26.303 dBm																																										
3																																															
4	N	1	f	2.408 208 GHz	-1.683 dBm																																										
<p>11G/HCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.466000000 GHz Start 2.43200 GHz, Stop 2.50000 GHz Mkr2 2.500 000 GHz, -57.747 dBm Mkr1 2.483 500 GHz, -50.230 dBm Mkr3 2.463 246 GHz, -5.583 dBm</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 500 GHz</td> <td>-50.230 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.500 000 GHz</td> <td>-57.747 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.463 246 GHz</td> <td>-5.583 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.483 500 GHz	-50.230 dBm				2	N	1	f	2.500 000 GHz	-57.747 dBm				3									4	N	1	f	2.463 246 GHz	-5.583 dBm				<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.466000000 GHz</p> <p>Start Freq 2.432000000 GHz</p> <p>Stop Freq 2.500000000 GHz</p> <p>CF Step 6.800000 MHz Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																							
1	N	1	f	2.483 500 GHz	-50.230 dBm																																										
2	N	1	f	2.500 000 GHz	-57.747 dBm																																										
3																																															
4	N	1	f	2.463 246 GHz	-5.583 dBm																																										


<p>11N20/LCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.37600000 GHz Start 2.31000 GHz, Stop 2.44200 GHz Mkr2 2.400 000 GHz, -25.970 dBm</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.390 000 GHz</td> <td>-41.939 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.400 000 GHz</td> <td>-25.970 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.413 224 GHz</td> <td>-1.118 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.390 000 GHz	-41.939 dBm				2	N	1	f	2.400 000 GHz	-25.970 dBm				3									4	N	1	f	2.413 224 GHz	-1.118 dBm				<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.376000000 GHz</p> <p>Start Freq 2.310000000 GHz</p> <p>Stop Freq 2.442000000 GHz</p> <p>CF Step 13.200000 MHz Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																							
1	N	1	f	2.390 000 GHz	-41.939 dBm																																										
2	N	1	f	2.400 000 GHz	-25.970 dBm																																										
3																																															
4	N	1	f	2.413 224 GHz	-1.118 dBm																																										
<p>11N20/HCH</p>	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.46600000 GHz Start 2.43200 GHz, Stop 2.50000 GHz Mkr2 2.500 000 GHz, -59.318 dBm</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 500 GHz</td> <td>-55.709 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.500 000 GHz</td> <td>-59.318 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.459 506 GHz</td> <td>-7.885 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.483 500 GHz	-55.709 dBm				2	N	1	f	2.500 000 GHz	-59.318 dBm				3									4	N	1	f	2.459 506 GHz	-7.885 dBm				<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.466000000 GHz</p> <p>Start Freq 2.432000000 GHz</p> <p>Stop Freq 2.500000000 GHz</p> <p>CF Step 6.800000 MHz Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																							
1	N	1	f	2.483 500 GHz	-55.709 dBm																																										
2	N	1	f	2.500 000 GHz	-59.318 dBm																																										
3																																															
4	N	1	f	2.459 506 GHz	-7.885 dBm																																										



## 5.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20)/n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test plot as follows:






11B\_MCH\_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz




11B\_HCH\_Graphs


Reference





30MHz-10GHz



10GHz-26.5GHz









11G\_HCH\_Graphs


Reference





30MHz-10GHz




10GHz-26.5GHz























Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

## 5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>					




**Test Procedure:**

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
 Note: For the radiated emission test above 1GHz:  
 Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the

	<p>ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>h. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates. Transmitting mode, Charge + Transmitting mode.</p>
Final Test Mode:	<p>Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case Through Pre-scan, find the11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); For below 1GHz, through Pre-scan, find the 11Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.</p>
Test Results:	Pass

### 5.8.1 Radiated emission below 1GHz

30MHz~1GHz		
Test mode:	Charge +Transmitting	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	31.3992	38.73	-6.06	32.67	40.00	-7.32	QP	
2	X	37.0248	41.58	-10.69	30.89	40.00	-9.11	QP	
3	!	65.8031	57.37	-18.76	38.61	40.00	-1.39	QP	

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.



Test mode:	Charge +Transmitting	Horizontal
------------	----------------------	------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	30.9618	35.92	-4.33	31.59	40.00	-8.41	QP			
2		35.3750	38.09	-8.09	30.00	40.00	-10.00	QP			
3		42.7496	42.57	-13.76	28.81	40.00	-11.19	QP			
4		103.0799	45.25	-14.94	30.31	43.50	-13.19	QP			

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

### 5.8.2 Transmitter emission above 1GHz

Test mode:		802.11b(11Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	59.95	-4.26	55.69	74	-18.31	PK	H
4824.000	41.53	-4.26	37.27	54	-16.73	AV	H
7236.000	61.11	1.18	62.29	74	-11.71	PK	H
7236.000	39.35	1.18	40.53	54	-13.47	AV	H
4824.000	59.66	-4.26	55.40	74	-18.60	PK	V
4824.000	42.41	-4.26	38.15	54	-15.85	AV	V
7236.000	61.56	1.18	62.74	74	-11.26	PK	V
7236.000	39.35	1.18	40.53	54	-13.47	AV	V

Test mode:		802.11b(11Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	59.19	-4.12	55.07	74	-18.93	PK	H
4874.000	40.51	-4.12	36.39	54	-17.61	AV	H
7311.000	61.31	1.46	62.77	74	-11.23	PK	H
7311.000	40.84	1.46	42.30	54	-11.70	AV	H
4874.000	58.94	-4.12	54.82	74	-19.18	PK	V
4874.000	42.27	-4.12	38.15	54	-15.85	AV	V
7311.000	61.22	1.46	62.68	74	-11.32	PK	V
7311.000	38.48	1.46	39.94	54	-14.06	AV	V

Test mode:		802.11b(11Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	59.50	-4.03	55.47	74	-18.53	PK	H
4924.000	40.08	-4.03	36.05	54	-17.95	AV	H
7386.000	60.16	1.66	61.82	74	-12.18	PK	H
7386.000	40.05	1.66	41.71	54	-12.29	AV	H
4924.000	58.85	-4.03	54.82	74	-19.18	PK	V
4924.000	40.66	-4.03	36.63	54	-17.37	AV	V
7386.000	61.87	1.66	63.53	74	-10.47	PK	V
7386.000	40.45	1.66	42.11	54	-11.89	AV	V

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

### 5.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
  - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

	<p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</p> <p>g. Test the EUT in the lowest channel , the Highest channel</p> <p>h. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates.</p> <p>Transmitting mode.</p>
Final Test Mode:	<p>Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case</p> <p>Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20);</p> <p>Only the worst case is recorded in the report.</p>
Test Results:	<p>Pass</p>

Test data:

Worse case mode:		802.11b(11Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2390.000	55.88	-9.2	46.68	74	-27.32	PK	H
2390.000	37.61	-9.2	28.41	54	-25.59	AV	H
2400.000	57.48	-9.39	48.09	74	-25.91	PK	H
2400.000	36.28	-9.39	26.89	54	-27.11	AV	H
2390.000	56.49	-9.2	47.29	74	-26.71	PK	V
2390.000	37.35	-9.2	28.15	54	-25.85	AV	V
2400.000	58.02	-9.39	48.63	74	-25.37	PK	V
2400.000	35.72	-9.39	26.33	54	-27.67	AV	V

Worse case mode:		802.11b(11Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2483.500	56.59	-9.29	47.30	74	-26.70	PK	H
2483.500	37.83	-9.29	28.54	54	-25.46	AV	H
2483.500	56.52	-9.29	47.23	74	-26.77	PK	V
2483.500	37.31	-9.29	28.02	54	-25.98	AV	V

Worse case mode:		802.11g(54Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2390.000	58.12	-9.2	48.92	74	-25.08	PK	H
2390.000	35.94	-9.2	26.74	54	-27.26	AV	H
2400.000	55.68	-9.39	46.29	74	-27.71	PK	H
2400.000	35.53	-9.39	26.14	54	-27.86	AV	H
2390.000	56.34	-9.2	47.14	74	-26.86	PK	V
2390.000	37.75	-9.2	28.55	54	-25.45	AV	V
2400.000	57.29	-9.39	47.90	74	-26.10	PK	V
2400.000	36.21	-9.39	26.82	54	-27.18	AV	V

Worse case mode:		802.11g(54Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2483.500	56.31	-9.29	47.02	74	-26.98	PK	H
2483.500	37.76	-9.29	28.47	54	-25.53	AV	H
2483.500	56.52	-9.29	47.23	74	-26.77	PK	V
2483.500	36.18	-9.29	26.89	54	-27.11	AV	V

Worse case mode:		802.11n(HT20)(MCS7)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2390.000	57.14	-9.29	47.85	74	-26.15	PK	H
2390.000	37.08	-9.29	27.79	54	-26.21	AV	H
2400.000	57.61	-9.29	48.32	74	-25.68	PK	H
2400.000	38.03	-9.29	28.74	54	-25.26	AV	H
2390.000	56.80	-9.29	47.51	74	-26.49	PK	V
2390.000	35.82	-9.29	26.53	54	-27.47	AV	V
2400.000	55.56	-9.29	46.27	74	-27.73	PK	V
2400.000	36.53	-9.29	27.24	54	-26.76	AV	V

Worse case mode:		802.11n(HT20)(MCS7)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2483.500	55.74	-9.29	46.45	74	-27.55	PK	H
2483.500	37.87	-9.29	28.58	54	-25.42	AV	H
2483.500	55.74	-9.29	46.45	74	-27.55	PK	V
2483.500	37.62	-9.29	28.33	54	-25.67	AV	V



Worse case mode:		802.11n(HT40)(MCS7)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2390.000	58.24	-9.29	48.95	74	-25.05	PK	H
2390.000	36.79	-9.29	27.50	54	-26.50	AV	H
2400.000	55.55	-9.29	46.26	74	-27.74	PK	H
2400.000	35.15	-9.29	25.86	54	-28.14	AV	H
2390.000	57.70	-9.29	48.41	74	-25.59	PK	V
2390.000	37.11	-9.29	27.82	54	-26.18	AV	V
2400.000	55.58	-9.29	46.29	74	-27.71	PK	V
2400.000	36.78	-9.29	27.49	54	-26.51	AV	V

Worse case mode:		802.11n(HT40)(MCS7)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
2483.500	56.49	-9.29	47.20	74	-26.80	PK	H
2483.500	36.62	-9.29	27.33	54	-26.67	AV	H
2483.500	56.99	-9.29	47.70	74	-26.30	PK	V
2483.500	36.51	-9.29	27.22	54	-26.78	AV	V

**Note:**


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

*Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor*

## 6 Photographs - EUT Test Setup

Please refer to the test setup file

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:

