

# Appendix 5

## RF Exposure Information

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2410	90.10	0.3070
2442	92.70	0.5586
2473	91.40	0.4141

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.3070/5) \cdot \sqrt{2.410} = 0.095 < 3.0$$

$$(0.5586/5) \cdot \sqrt{2.442} = 0.175 < 3.0$$

$$(0.4141/5) \cdot \sqrt{2.473} = 0.130 < 3.0$$

**Conclusion:**

No SAR is required.