



Report No.: EA2001244F 01001

1 of 74

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Bluetooth Speaker

Model No.:PTUV-02

Trademark: N/A

FCC ID:2AT96PTUV-02

Report No.: EA2001244F 01001

Issue Date: March 02, 2020

Prepared for

**Xiamen Helios Technology Co.,Ltd
13th Floor, 512 Dongyili, Canghu, Haicang District, Xiamen City, China**

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

**1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech
Industrial Development Zone, Dongguan City, evelopment Zone,
Dongguan City, Guangdong Pr., China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Electronic Technology Co., Ltd.**



VERIFICATION OF COMPLIANCE

Applicant:	Xiamen Helios Technology Co.,Ltd 13th Floor, 512 Dongyili, Canghu, Haicang District, Xiamen City, China
Manufacturer:	Xiamen Helios Technology Co.,Ltd 13th Floor, 512 Dongyili, Canghu, Haicang District, Xiamen City, China
Product Description:	Bluetooth Speaker
Trade Mark:	N/A
Model Number:	PTUV-02

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2019).

Date of Test : February 21, 2020 to February 29, 2020

Prepared by : Tomas Yang/Supervisor

Reviewer & Authorized Signer : Alan He/Manager



Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	EA2001244F 01001



Table of Contents

- 1. GENERAL INFORMATION..... 6**
 - 1.1 PRODUCT DESCRIPTION..... 6
 - 1.2 TEST METHODOLOGY.....6
 - 1.3 TEST FACILITY..... 7
- 2. SYSTEM TEST CONFIGURATION..... 8**
 - 2.1EUT CONFIGURATION.....8
 - 2.2 EUT EXERCISE.....8
 - 2.3 TEST PROCEDURE.....8
 - 2.4CONFIGURATION OF TESTED SYSTEM..... 9
- 3. SUMMARY OF TEST RESULTS..... 10**
- 4. DESCRIPTION OF TEST MODES..... 11**
- 5. TEST SYSTEM UNCERTAINTY..... 12**
- 6. CONDUCTED EMISSIONS TEST.....13**
 - 6.1MEASUREMENT PROCEDURE:..... 13
 - 6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 13
 - 6.3MEASUREMENT EQUIPMENT USED:..... 13
 - 6.4 MEASUREMENT RESULT:..... 14
 - 6.5 CONDUCTED MEASUREMENT PHOTOS:..... 17
- 7. RADIATED EMISSION TEST..... 18**
 - 7.1MEASUREMENT PROCEDURE..... 18
 - 7.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 20
 - 7.3 MEASUREMENT EQUIPMENT USED:..... 21
 - 7.4 RADIATED EMISSION LIMIT..... 22
 - 7.5 MEASUREMENT RESULT..... 23
 - 7.5 RADIATED MEASUREMENT PHOTOS:..... 31
- 8. CHANNEL SEPARATION TEST.....32**
 - 8.1MEASUREMENT PROCEDURE..... 32
 - 8.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 32
 - 8.3 MEASUREMENT EQUIPMENT USED:..... 32
 - 8.4MEASUREMENT RESULTS:..... 32
- 9. 20DB BANDWIDTH TEST..... 39**
 - 9.1MEASUREMENT PROCEDURE..... 39
 - 9.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 39
 - 9.3 MEASUREMENT EQUIPMENT USED:..... 39
 - 9.4 MEASUREMENT RESULTS:..... 39
- 10. QUANTITY OF HOPPING CHANNEL TEST..... 46**



- 10.1 MEASUREMENT PROCEDURE..... 46
- 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....46
- 10.3 MEASUREMENT EQUIPMENT USED:..... 46
- 10.4 MEASUREMENT RESULTS:.....46
- 11. TIME OF OCCUPANCY (DWELL TIME) TEST..... 47**
 - 11.1 TEST DESCRIPTION.....47
 - 11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....47
 - 11.3 MEASUREMENT EQUIPMENT USED:..... 47
 - 11.4 TEST REQUIREMENTS / LIMITS.....47
 - 11.5 TEST RESULT.....48
- 12. MAXIMUM PEAK OUTPUT POWER TEST.....50**
 - 12.1 MEASUREMENT PROCEDURE..... 50
 - 12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....50
 - 12.3 MEASUREMENT EQUIPMENT USED:..... 50
 - 12.4 MEASUREMENT RESULTS:..... 51
- 13. BAND EDGE TEST..... 57**
 - 13.1 MEASUREMENT PROCEDURE..... 57
 - 13.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....58
 - 13.3 MEASUREMENT EQUIPMENT USED:..... 58
 - 13.4 MEASUREMENT RESULTS:..... 59
- 14. ANTENNA APPLICATION..... 74**
 - 14.1 ANTENNA REQUIREMENT..... 74
 - 14.2 RESULT..... 74
- 15. PHOTOS OF EUT..... 74**

1. GENERAL INFORMATION

1.1 Product Description

Characteristics	Description
Product Name	Bluetooth Speaker
Model number	PTUV-02
Input rating	AC 100V-240, 50/60Hz for adapter
Power Supply	AC 120V/60Hz and AC 240V/50Hz for adapter
Kind of Device	Bluetooth Ver.4.2+EDR
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range	2402-2480MHz
Number of Channels	79
Transmit Power Max(PK)	1.86dBm(0.001535W)
Antenna Type	Internal PCB antenna
Antenna Gain	0dBi
Product Software Version	V3.0
Product Hardware version	V3.0
Radio Software Version	V1.0
Radio Hardware version	V1.0

1.2 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2013. Radiated testing was performed at an antenna to EUT distance 3 meters.



1.3 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2017.06.26
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L0468.

Accredited by A2LA, 2018.03.15
The Certificate Number is 4422.01.

Name of Firm : Dong Guan Anci Electronic Technology Co., Ltd.
Site Location : 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, evelopment Zone, Dongguan City, Guangdong Pr., China.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of EUT was fixed in a particular direction according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Bluetooth Speaker	N/A	PTUV-02	2AT96PTUV-02	<i>EUT</i>
2	Adapter	Innov	Model : IVP1200-1200 Input: AC 100-240V, 50/60Hz Output: DC 12V,1200mA	N/A	<i>Support Equipment</i>

Note:

- (1) Unless otherwise denoted as EUT in 『 Remark 』 column , device(s) used in tested system is a support equipment.



3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.203	Antenna Requirement	Compliant

4. Description of test modes

The EUT has been tested under its typical operating condition for EUT tested alone. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition. This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK, $\pi/4$ -DQPSK, 8DPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
1	2402
40	2441
79	2480



5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Remark: The coverage Factor ($k=2$), and measurement Uncertainty for a level of Confidence of 95%

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2020-05-19
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2020-05-19
RF Cable	N/A	N/A	2#	2020-05-19
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2020-05-19




6.4 Measurement Result:

Operation Mode:	TX	Test Date :	February 24, 2020
Frequency Range:	0.15MHz~30MHz	Temperature :	24°C
Test Result:	PASS	Humidity :	58 %
Test By:	Best		

Pass.

Conducted emission at both 120V & 240V, and emission at 240V represents the worst case. All the modulation modes were tested the data of the worst mode (GFSK TX 2480MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following data.



Site:	843.3	Phase:	N	Temperature(C):	26(C)
Limit:	FCC Part 15 C Conduction(QP)	Test Time:	2020-02-24	Humidity(%):	60%
EUT:	Bluetooth Speaker	Power Rating:	AC 240V/50Hz		
M/N.:	PTUV-02	Test Engineer:	Bast		
Mode:	TX2480				
Note:					

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.2180	33.84	9.91	43.75	62.89	-19.14	QP	
2	0.2180	21.09	9.91	31.00	52.89	-21.89	AVG	
3	0.3500	32.05	9.89	41.94	58.96	-17.02	QP	
4	0.3500	15.73	9.89	25.62	48.96	-23.34	AVG	
5	0.3780	32.54	9.90	42.44	58.32	-15.88	QP	
6	0.3780	13.01	9.90	22.91	48.32	-25.41	AVG	
7	0.5740	33.02	9.92	42.94	56.00	-13.06	QP	
8	0.5740	12.69	9.92	22.61	46.00	-23.39	AVG	
9 *	0.8820	34.24	9.92	44.16	56.00	-11.84	QP	
10	0.8820	17.96	9.92	27.88	46.00	-18.12	AVG	
11	1.1860	33.85	9.90	43.75	56.00	-12.25	QP	
12	1.1860	18.30	9.90	28.20	46.00	-17.80	AVG	

*:Maximum data x:Over limit !:over margin



Site:	843.3	Phase:L1	Temperature(C):26(C)
Limit:	FCC Part 15 C Conduction(QP)		Humidity(%):60%
EUT:	Bluetooth Speaker	Test Time:	2020-02-24
M/N.:	PTUV-02	Power Rating:	AC 240V/50Hz
Mode:	TX2480	Test Engineer:	Bast
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1980	33.11	9.88	42.99	63.69	-20.70	QP	
2	0.1980	18.98	9.88	28.86	53.69	-24.83	AVG	
3	0.4380	34.13	9.91	44.04	57.10	-13.06	QP	
4	0.4380	17.18	9.91	27.09	47.10	-20.01	AVG	
5	0.5500	33.51	9.91	43.42	56.00	-12.58	QP	
6	0.5500	15.15	9.91	25.06	46.00	-20.94	AVG	
7	0.7420	35.45	9.95	45.40	56.00	-10.60	QP	
8	0.7420	19.12	9.95	29.07	46.00	-16.93	AVG	
9 *	1.1780	35.75	9.92	45.67	56.00	-10.33	QP	
10	1.1780	16.96	9.92	26.88	46.00	-19.12	AVG	
11	1.8580	31.16	9.89	41.05	56.00	-14.95	QP	
12	1.8580	14.35	9.89	24.24	46.00	-21.76	AVG	

*:Maximum data x:Over limit !:over margin

6.5 Conducted Measurement Photos:



7. Radiated Emission Test

7.1 Measurement Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Average
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2020-11-28
2.	Pre-Amplifier	HP	8447D	2727A06172	2020-05-19
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2020-05-19
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2020-01-04
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
6.	Low noise Amplifiers	A-INFO	LA1018N4009	J101313052400 1	2020-05-19
7.	Horn antenna	A-INFO	LB-10180-SF	J203109061212 3	2020-05-19
8.	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX10 0KHz-40GHz	J101313052400 1	2020-03-12
9.	DRG Horn Antenna	A.H.SYSTEMS	SAS-574	J203109061212 3	2020-03-12
10.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-2m	N/A	2020-03-12
11.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-0.3m	N/A	2020-03-12
12.	RF Cable	N/A	N/A	6#	2020-05-19
13.	RF Cable	N/A	N/A	1-1#	2020-05-19
14.	RF Cable	N/A	N/A	1-2#	2020-05-19
15.	RF Cable	N/A	N/A	7#	2020-05-19
16.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2020-05-19
17.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	Ⓢ

- Remark 1. Emission level in dBuV/m=20 log (uV/m)
- :
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.



7.5 Measurement Result

Operation Mode:	TX	Test Date :	February 24, 2020
Test By:	Best	Temperature :	25°C
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m		

Below 30MHz:

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

All the modulation modes were tested the data of the worst mode (GFSK TX 2480MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site:	LAB	Antenna::	Horizontal	Temperature(C):	26(C)
Limit:	FCC Part 15 C 3m Radiation			Humidity(%):	60%
EUT:	Bluetooth Speaker	Test Time:	2020-02-24		
M/N.:	PTUV-02	Power Rating:	AC 120V/60Hz		
Mode:	TX2480	Test Engineer:	Dyson		
Note:					

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1 *	42.6000	28.37	-13.19	15.18	40.00	-24.82	QP			
2	100.5806	30.39	-12.49	17.90	43.50	-25.60	QP			
3	106.9461	31.40	-12.95	18.45	43.50	-25.05	QP			
4	139.1172	30.90	-15.21	15.69	43.50	-27.81	QP			
5	199.2855	28.69	-13.95	14.74	43.50	-28.76	QP			
6	211.8977	31.27	-13.35	17.92	43.50	-25.58	QP			

*:Maximum data x:Over limit !:over margin



Site:	LAB	Antenna::	Vertical	Temperature(C):	26(C)
Limit:	FCC Part 15 C 3m Radiation	Test Time:	2020-02-24	Humidity(%):	60%
EUT:	Bluetooth Speaker	Power Rating:	AC 120V/60Hz	Test Engineer:	Dyson
M/N.:	PTUV-02				
Mode:	TX2480				
Note:					

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	38.0115	38.48	-13.72	24.76	40.00	-15.24	QP			
2	40.0644	40.51	-13.19	27.32	40.00	-12.68	QP			
3 *	42.9750	41.06	-13.20	27.86	40.00	-12.14	QP			
4	106.9461	29.71	-12.95	16.76	43.50	-26.74	QP			
5	133.1511	34.62	-14.79	19.83	43.50	-23.67	QP			
6	139.1172	33.93	-15.21	18.72	43.50	-24.78	QP			

*:Maximum data x:Over limit !:over margin

**Above 1000MHz~10th Harmonics:**

Please refer to the following data.

Operation Mode: GFSK (CH1: 2402MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	95.97	76.15	-32.3	63.67	43.85	74	54	-10.33	-10.15
7206	V	98.48	78.7	-37.25	61.23	41.45	74	54	-12.77	-12.55
9608	V	99.36	80.03	-39.8	59.56	40.23	74	54	-14.44	-13.77
12010	V	96.84	77.84	-40.5	56.34	37.34	74	54	-17.66	-16.66
14412	V	95.93	77.37	-41.7	54.23	35.67	74	54	-19.77	-18.33
16814	V	94.65	75.13	-40	54.65	35.13	74	54	-19.35	-18.87
4804	H	95.38	74.95	-31.4	63.98	43.55	74	54	-10.02	-10.45
7206	H	95.93	75.82	-35.5	60.43	40.32	74	54	-13.57	-13.68
9608	H	96.17	76.32	-38.3	57.87	38.02	74	54	-16.13	-15.98
12010	H	95.13	76.45	-39	56.13	37.45	74	54	-17.87	-16.55
14412	H	96.23	77.65	-42	54.23	35.65	74	54	-19.77	-18.35
16814	H	94.08	74.84	-39.3	54.78	35.54	74	54	-19.22	-18.46

Operation Mode: GFSK (CH40: 2441MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	96.42	77.17	-32.3	64.12	44.87	74	54	-9.88	-9.13
7323	V	98.65	78.75	-37.2	61.45	41.55	74	54	-12.55	-12.45
9764	V	99.05	80.14	-39.6	59.45	40.54	74	54	-14.55	-13.46
12205	V	98.16	77.66	-40.5	57.66	37.16	74	54	-16.34	-16.84
14646	V	96.23	77.65	-41	55.23	36.65	74	54	-18.77	-17.35
17087	V	95.23	76.77	-41.1	54.13	35.67	74	54	-19.87	-18.33
4882	H	95.16	75.36	-31.6	63.56	43.76	74	54	-10.44	-10.24
7323	H	95.04	76.04	-35.7	59.34	40.34	74	54	-14.66	-13.66
9764	H	96.64	78.05	-38.3	58.34	39.75	74	54	-15.66	-14.25
12205	H	95.76	76.34	-39	56.76	37.34	74	54	-17.24	-16.66
14646	H	96.76	76.76	-42	54.76	34.76	74	54	-19.24	-19.24
17087	H	96.52	77.39	-41.5	55.02	35.89	74	54	-18.98	-18.11



Operation Mode: GFSK (CH79: 2480MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	V	96.86	77.5	-32.3	64.56	45.2	74	54	-9.44	-8.8
7440	V	99.22	79.65	-37.2	62.02	42.45	74	54	-11.98	-11.55
9920	V	97.93	79.04	-39.6	58.33	39.44	74	54	-15.67	-14.56
12400	V	98.03	78.85	-40.7	57.33	38.15	74	54	-16.67	-15.85
14880	V	96.32	77.76	-41	55.32	36.76	74	54	-18.68	-17.24
17360	V	95.35	75.66	-41.1	54.25	34.56	74	54	-19.75	-19.44
4960	H	96.18	75.96	-31.6	64.58	44.36	74	54	-9.42	-9.64
7440	H	97.35	77.58	-35.7	61.65	41.88	74	54	-12.35	-12.12
9920	H	96.55	77.55	-38.1	58.45	39.45	74	54	-15.55	-14.55
12400	H	96.23	77.16	-39	57.23	38.16	74	54	-16.77	-15.84
14880	H	97.34	78.54	-42	55.34	36.54	74	54	-18.66	-17.46
17360	H	96.17	76.53	-41.5	54.67	35.03	74	54	-19.33	-18.97

Operation Mode: Pi/4-DQPSK (CH1: 2402MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	94.75	75.31	-32.3	62.45	43.01	74	54	-11.55	-10.99
7206	V	96.63	77.43	-37.2	59.43	40.23	74	54	-14.57	-13.77
9608	V	97.14	77.94	-39.8	57.34	38.14	74	54	-16.66	-15.86
12010	V	95.93	77.48	-40.5	55.43	36.98	74	54	-18.57	-17.02
14412	V	96.13	77.84	-41.7	54.43	36.14	74	54	-19.57	-17.86
16814	V	94.78	75.56	-40	54.78	35.56	74	54	-19.22	-18.44
4804	H	93.39	74.33	-31.6	61.79	42.73	74	54	-12.21	-11.27
7206	H	94.95	76.06	-35.5	59.45	40.56	74	54	-14.55	-13.44
9608	H	95.63	76.48	-38.3	57.33	38.18	74	54	-16.67	-15.82
12010	H	96.27	76.65	-39.4	56.87	37.25	74	54	-17.13	-16.75
14412	H	96.13	77.23	-42	54.13	35.23	74	54	-19.87	-18.77
16814	H	95.06	75.73	-39.3	55.76	36.43	74	54	-18.24	-17.57



Operation Mode: Pi/4-DQPSK (CH40: 2441MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	95.64	76.06	-32.3	63.34	43.76	74	54	-10.66	-10.24
7323	V	97.53	78.54	-37.2	60.33	41.34	74	54	-13.67	-12.66
9764	V	98.13	79.07	-39.8	58.33	39.27	74	54	-15.67	-14.73
12205	V	96.64	78.08	-40.5	56.14	37.58	74	54	-17.86	-16.42
14646	V	96.33	77.32	-41	55.33	36.32	74	54	-18.67	-17.68
17087	V	95.29	76.53	-41.1	54.19	35.43	74	54	-19.81	-18.57
4882	H	94.49	74.72	-31.6	62.89	43.12	74	54	-11.11	-10.88
7323	H	94.95	76.08	-35.5	59.45	40.58	74	54	-14.55	-13.42
9764	H	96.53	76.62	-38.3	58.23	38.32	74	54	-15.77	-15.68
12205	H	95.15	76.34	-39	56.15	37.34	74	54	-17.85	-16.66
14646	H	97.23	78.45	-42	55.23	36.45	74	54	-18.77	-17.55
17087	H	95.52	76.52	-41.4	54.12	35.12	74	54	-19.88	-18.88

Operation Mode: Pi/4-DQPSK (CH79: 2480MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	V	95.75	76.44	-32.3	63.45	44.14	74	54	-10.55	-9.86
7440	V	97.54	78.54	-37.2	60.34	41.34	74	54	-13.66	-12.66
9920	V	99.43	79.93	-39.8	59.63	40.13	74	54	-14.37	-13.87
12400	V	97.6	78.62	-40.5	57.1	38.12	74	54	-16.9	-15.88
14880	V	95.76	76.14	-41	54.76	35.14	74	54	-19.24	-18.86
17360	V	95.86	76.75	-41.1	54.76	35.65	74	54	-19.24	-18.35
4960	H	94.76	75.25	-31.6	63.16	43.65	74	54	-10.84	-10.35
7440	H	96.75	77.06	-35.5	61.25	41.56	74	54	-12.75	-12.44
9920	H	97.53	78.5	-38.3	59.23	40.2	74	54	-14.77	-13.8
12400	H	96.48	77.58	-39	57.48	38.58	74	54	-16.52	-15.42
14880	H	97.23	78.23	-42	55.23	36.23	74	54	-18.77	-17.77
17360	H	95.64	76.64	-41.5	54.14	35.14	74	54	-19.86	-18.86



Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	93.84	74.64	-32.3	61.54	42.34	74	54	-12.46	-11.7
7206	V	96.65	77.65	-37.2	59.45	40.45	74	54	-14.55	-13.6
9608	V	98.03	79.45	-39.8	58.23	39.65	74	54	-15.77	-14.4
12010	V	97.06	77.84	-40.5	56.56	37.34	74	54	-17.44	-16.7
14412	V	96.15	76.86	-41.7	54.45	35.16	74	54	-19.55	-18.8
16814	V	94.65	75.54	-40	54.65	35.54	74	54	-19.35	-18.5
4804	H	93.4	73.71	-31.6	61.8	42.11	74	54	-12.2	-11.9
7206	H	94.84	75.83	-35.5	59.34	40.33	74	54	-14.66	-13.7
9608	H	95.63	76.64	-38.3	57.33	38.34	74	54	-16.67	-15.7
12010	H	96.13	77.12	-39	57.13	38.12	74	54	-16.87	-15.9
14412	H	96.76	77.65	-42	54.76	35.65	74	54	-19.24	-18.4
16814	H	94.31	75.08	-39.3	55.01	35.78	74	54	-18.99	-18.2

Operation Mode: 8DPSK (CH40: 2441MHz) Test Date : February 24, 2020

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	94.62	74.85	-32.3	62.32	42.55	74	54	-11.68	-11.45
7323	V	97.53	78.43	-37.2	60.33	41.23	74	54	-13.67	-12.77
9764	V	98.12	79.44	-39.8	58.32	39.64	74	54	-15.68	-14.36
12205	V	96.61	77.62	-40.5	56.11	37.12	74	54	-17.89	-16.88
14646	V	95.54	76.77	-41	54.54	35.77	74	54	-19.46	-18.23
17087	V	96.07	76.75	-41.1	54.97	35.65	74	54	-19.03	-18.35
4882	H	94.26	74.36	-31.6	62.66	42.76	74	54	-11.34	-11.24
7323	H	95.81	76.95	-35.5	60.31	41.45	74	54	-13.69	-12.55
9764	H	96.76	77.74	-38.3	58.46	39.44	74	54	-15.54	-14.56
12205	H	95.87	76.14	-39	56.87	37.14	74	54	-17.13	-16.86
14646	H	96.43	77.56	-42	54.43	35.56	74	54	-19.57	-18.44
17087	H	96.23	76.62	-41.5	54.73	35.12	74	54	-19.27	-18.88



Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	V	94.86	74.75	-32.3	62.56	42.45	74	54	-11.44	-11.55
7440	V	97.43	78.76	-37.2	60.23	41.56	74	54	-13.77	-12.44
9920	V	98.1	79.14	-39.8	58.3	39.34	74	54	-15.7	-14.66
12400	V	97.84	78.67	-40.5	57.34	38.17	74	54	-16.66	-15.83
14880	V	96.32	77.14	-41	55.32	36.14	74	54	-18.68	-17.86
17360	V	95.76	76.76	-41.1	54.66	35.66	74	54	-19.34	-18.34
4960	H	93.76	74.42	-31.6	62.16	42.82	74	54	-11.84	-11.18
7440	H	95.65	76.97	-35.5	60.15	41.47	74	54	-13.85	-12.53
9920	H	96.63	77.06	-38.3	58.33	38.76	74	54	-15.67	-15.24
12400	H	95.32	76.03	-39	56.32	37.03	74	54	-17.68	-16.97
14880	H	98.87	79.12	-42	56.87	37.12	74	54	-17.13	-16.88
17360	H	95.73	77.05	-41.5	54.23	35.55	74	54	-19.77	-18.45

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.

7.5 Radiated Measurement Photos:




8. Channel Separation test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>732
40	2441	1003	>729
79	2480	1003	>735






Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	Π/4-DQPSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>915
40	2441	1003	>912
79	2480	1003	>912






Report No.: EA2001244F 01001



37 of 74

Spectrum Detector: PK
 Test By: Best
 Test Result: PASS
 Modulation: 8DPSK

Test Date : February 25, 2020
 Temperature : 24°C
 Humidity : 53 %

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>912
40	2441	1003	>912
79	2480	1003	>912






9. 20dB Bandwidth test

9.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28



Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		


Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1098
40	2441	1094
79	2480	1103







Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	Π/4-DQPSK		


Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1372
40	2441	1368
79	2480	1368







Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	8DPSK		

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1368
40	2441	1368
79	2480	1368






10. Quantity of Hopping Channel Test

10.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Results:

Refer to attached data chart.

Worst Test Mode	GFSK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	> 15



11. Time of Occupancy (Dwell Time) test

11.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:


$$\text{Dwell time} = \text{time slot length} * \text{hop rate} / \text{number of hopping channels} * 31.6\text{s}$$

with:

- hop rate = $1600 * 1/\text{s}$ for DH1 packets = 1600 s^{-1}
- hop rate = $1600/3 * 1/\text{s}$ for DH3 packets = 533.33 s^{-1}
- number of hopping channels = 79
- $31.6 \text{ s} = 0.4 \text{ seconds multiplied by the number of hopping channels} = 0.4 \text{ s} * 79$

The highest value of the dwell time is reported.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

11.4 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart.


Modulation:	GFSK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %

11.5 Test result


Mode	Number of transmission in a 31.6(79 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	$1600/(2*79) \times 31.6 = 320$	0.411	131.52	400
DH3	$1600/(4*79) \times 31.6 = 160$	1.665	266.40	400
DH5	$1600/(6*79) \times 31.6 = 106.67$	2.913	310.73	400

Remark: The results of worst cased was recorded.


DH1:



DH3:



DH5:




12. MAXIMUM PEAK OUTPUT POWER TEST

12.1 Measurement Procedure

- a. Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

12.2 Test SET-UP (Block Diagram of Configuration)



12.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



12.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-2.02	0.628	125	PASS
40	2441	0.99	1.256	125	PASS
79	2480	1.86	1.535	125	PASS





Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %
Modulation:	Π/4-DQPSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-3.95	0.403	125	PASS
40	2441	-0.26	0.942	125	PASS
79	2480	0.96	1.247	125	PASS






Report No.: EA2001244F 01001



55 of 74

Spectrum Detector: PK
 Test By: Best
 Test Result: PASS
 Modulation: 8DPSK

Test Date : February 24, 2020
 Temperature : 24 °C
 Humidity : 53 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-5.56	0.278	125	PASS
40	2441	-1.7	0.676	125	PASS
79	2480	-0.27	0.940	125	PASS





13. Band EDGE test

13.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

13.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



13.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2020-11-28
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2020-11-28

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Signal Analyzer	Rohde & Schwarz	FSV40	US40240623	2020-11-28
2	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX100KHz-40G Hz	J1013130524 001	2020-03-12
3	DRG Horn Antenna	A.H.SYSTEMS	SAS-574	J2031090612 123	2020-03-12
4	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-2m	N/A	2020-03-12
5	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-0.3m	N/A	2020-03-12

13.4 Measurement Results:

Refer to attached data chart.


Spectrum Detector:	PK	Test Date :	February 25, 2020
Test By:	Best	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %


1. Conducted Test

For Non-Hopping Mode:


Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.16	GFSK	-2.08	51.55	>20dBc
2399.54	pi/4-DQPSK	-5.66	48.56	>20dBc
2399.78	8DPSK	-5.52	47.40	>20dBc
2484	GFSK	1.95	60.99	>20dBc
2484.04	pi/4-DQPSK	-0.23	58.42	>20dBc
2484.43	8DPSK	-0.14	57.44	>20dBc


Test plots of GFSK







Test plots of pi/4-DQPSK





Test plots of 8DPSK









For Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.19	GFSK	-0.73	53.45	>20dBc
2399.86	pi/4-DQPSK	-4.08	41.62	>20dBc
2399.78	8DPSK	-3.96	48.96	>20dBc
2485.83	GFSK	1.82	59.29	>20dBc
2484	pi/4-DQPSK	-0.25	57.36	>20dBc
2483.95	8DPSK	-0.25	58.16	>20dBc


Test plots of GFSK




Test plots of pi/4-DQPSK



Test plots of 8DPSK






Site: LAB Polarization: **Vertical** Temperature: 26.5
 Limit: FCC Part 15 C 3m Above1G(Peak) Power: AC 120V/60Hz Humidity: 60.6 %
 Mode: TX2480
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		2483.500	58.94	-4.00	54.94	74.00	-19.06			peak
2	*	2483.500	44.18	-4.00	40.18	54.00	-13.82			AVG
3		2492.281	52.90	-3.95	48.95	74.00	-25.05			peak
4		2494.835	53.27	-3.92	49.35	74.00	-24.65			peak

*:Maximum data x:Over limit !:over margin

<Reference Only

For Hopping Mode:



Site: LAB Polarization: **Vertical** Temperature: 26.5
 Limit: FCC Part 15 C 3m Above1G(Peak) Power: AC 120V/60Hz Humidity: 60.6 %
 Mode: Hopping
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree	Comment
1		2386.416	56.35	-4.74	51.61	74.00	-22.39			peak
2		2390.000	61.43	-4.71	56.72	74.00	-17.28			peak
3		2390.000	45.00	-4.71	40.29	54.00	-13.71			AVG
4		2400.000	71.45	-4.63	66.82	74.00	-7.18			peak
5	*	2400.000	53.69	-4.63	49.06	54.00	-4.94			AVG

*:Maximum data x:Over limit !:over margin

⟨Reference Only



14. Antenna Application

14.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

14.2 Result

The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0 dBi and meets the requirement.

15. Photos of EUT

Please refer to external photos.pdf and internal photos.pdf.