



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

Maximum Permissible Exposure Evaluation

FCC ID: 2AT9W-YS600

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

| | |
|----------------------------|--|
| EUT | Robotic Vacuum Cleaner |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz/2.422GHz~2.452 GHz <input type="checkbox"/> WCDMA Band II, Band IV, Band V <input type="checkbox"/> LTE FDD Band 2, Band 4, Band 5, Band 12 <input type="checkbox"/> Others |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | WIFI: 11.29dBm |
| Antenna gain (Max) | 2.5dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|---|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $Pd=(Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

| Operating Mode | Channel Frequency (MHz) | Max. Measured Power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 20cm (mW/cm ²) | Power density Limits (mW/cm ²) |
|----------------|-------------------------|---------------------------|-------------------------|--------------------------|--------------------|---|--|
| 802.11b | CH11 | 11.29 | 11.29±1 | 12.29 | 2.5 | 0.0060 | 1 |
| 802.11g | CH06 | 9.24 | 9.24±1 | 10.24 | 2.5 | 0.0037 | 1 |
| 802.11n (HT20) | CH06 | 8.68 | 8.68±1 | 9.68 | 2.5 | 0.0033 | 1 |
| 802.11n (HT40) | CH03 | 7.96 | 7.96±1 | 8.96 | 2.5 | 0.0028 | 1 |

Note

For a more detailed features description, please refer to the RF Test Report.

*****THE END*****