
INTERTEK TESTING SERVICES

RF Exposure Report

The Equipment Under Test (EUT) is a Echelon Reflect, Echelon Reflect Touch with BT5.0 (dual-mode) operating in 2402-2480MHz, 2.4G Wi-Fi function operating at 2412-2462MHz and 5G Wi-Fi function operating in 5180-5240&5747-5825MHz. The EUT is powered by A.C. 120V, 60Hz. Bluetooth and WIFI transmitters are share one antenna and can transmit simultaneously, but 2.4G WIFI and 5G WIFI cannot transmit simultaneously. User cannot access USB/LAN/SD card ports in normal use. For more detailed features description, please refer to the user's manual.

Bluetooth Version: 5.0 EDR

Antenna Type: Internal antenna

Antenna Gain: 3dBi.

Modulation Type: GFSK, $\pi/4$ -DQPSK and 8-DPSK

The normal radiated output power (e.i.r.p) is: -6 dBm (tolerance: ± 5 dB).

The normal conducted output power is: -9 dBm (tolerance: ± 5 dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 93.3dB μ V/m at 3m in the frequency 2402MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -1.93 dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 91.5 dB μ V/m at 3m in the frequency 2480MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -3.73dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting device is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The maximum radiated power = -1dBm = 0.794mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 0.794\text{mW} / 4\pi R^2$$

$$= 0.0002 \text{ mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the

INTERTEK TESTING SERVICES

MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

Bluetooth Version: 5.0 BLE

Antenna Type: Internal antenna

Antenna Gain: 3dBi.

Modulation Type: GFSK

The normal radiated output power (e.i.r.p) is: -7 dBm (tolerance: ± 4.5 dB).

The normal conducted output power is: -10 dBm (tolerance: ± 4.5 dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 93.6dB μ V/m at 3m in the frequency 2402MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -1.63 dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 93.4 dB μ V/m at 3m in the frequency 2480MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -1.83 dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting device is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The maximum radiated power = -2.5dBm = 0.562mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:

$$= 0.562\text{mW} / 4\pi R^2$$

$$= 0.0001 \text{ mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

INTERTEK TESTING SERVICES

2.4G WIFI Function:

Modulation Type: CCK, BPSK, QPSK, 16QAM, 64QAM, DQPSK, DBPSK

Antenna Type: Internal antenna

Antenna Gain: 3 dBi

The nominal conducted output power specified: 19dBm (Tolerance: ± 2 dB)

The nominal radiation output power specified: 22dBm (Tolerance: ± 2 dB)

The maximum conducted output power for the EUT is 20.9 dBm in the frequency 2.412GHz 802.11n-HT20 mode (Simultaneous transmission) which is within the production variation.

The minimum conducted output power for the EUT is 17.0 dBm in the frequency 2.462GHz 802.11b mode (Standalone transmission) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

For Maximum Permissible Exposure (MPE) evaluation of the product, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65.

The maximum E.I.R.P = 19dBm+2dB+3dBi=24dBm=251.2mW

The source-based time averaged maximum radiated power = 251.2mW x Duty Cycle = 251.2mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$= 251.2\text{mW} / 4\pi R^2$$

$$= 0.05 \text{ mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the Wi-Fi frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 1.

INTERTEK TESTING SERVICES

5G WIFI Function:

Modulation Type: BPSK, QPSK, 16QAM, 64QAM and OFDM.

Antenna Type: Internal antenna

Antenna Gain: 2 dBi

The nominal conducted output power specified: 14dBm (Tolerance: ± 3 dB)

The nominal radiation output power specified: 16dBm (Tolerance: ± 3 dB)

The maximum conducted output power for the EUT is 16.92 dBm in the frequency 5.755GHz 802.11ac-HT40 mode (Standalone transmission) which is within the production variation.

The minimum conducted output power for the EUT is 11.66 dBm in the frequency 5.825GHz 802.11a mode (Standalone transmission) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

For Maximum Permissible Exposure (MPE) evaluation of the product, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65.

The maximum E.I.R.P = 14dBm+3dB+2dBi=19dBm=79.43mW

The source-based time averaged maximum radiated power = 125.9 x Duty Cycle = 125.9mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$= 79.43\text{mW} / 4\pi R^2$$

$$= 0.0158 \text{ mW/cm}^2$$

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the Wi-Fi frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 1.

INTERTEK TESTING SERVICES

Simultaneous Transmission Evaluation

For Simultaneous transmitting of 2.4GHz WiFi and Bluetooth transmitters, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.0002/1 + 0.05/1 = 0.0502 < 1$

For Simultaneous transmitting of 5GHz WiFi and Bluetooth transmitters, According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.0002/1 + 0.0158/1 = 0.0160 < 1$

Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”