

# **RF Exposure Evaluation**

**Test report  
On Behalf of  
Dong Guan Hiper Song Electronic Technology Co.,Ltd  
For**

**Sound bar wireless Speaker  
Model No.: HS-BT167, HS-BT168, 90054PI**

**FCC ID: 2ATAT-HSBTX**

**Prepared for :** Dong Guan Hiper Song Electronic Technology Co.,Ltd  
3F 17# Xihe Road, Xihe Village, Shijie Town, Dongguan, Guangdong, China

**Prepared By :** Shenzhen HUAK Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

**Date of Test:** Nov. 14, 2019 ~ Nov. 22, 2019

**Date of Report:** Nov. 22, 2019

## 1 General Description of EUT

Product Name:	Sound bar wireless Speaker
Model/Type reference:	HS-BT167
Serial Model:	HS-BT168, 90054PI
Model Difference	All models have the same functionality, software and electronics, only the color, front frame shape and model names may differ. Test sample model: HS-BT167
Trade Mark	N/A
FCC ID	2ATAT-HSBTX
Hardware Version:	HA-569-C-2-1
Software Version:	V1.5
Version:	Supported EDR
Modulation:	GFSK, $\pi/4$ DQPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79CH
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	0 dBi
Power supply:	DC 3.7V from Battery

## 2 RF Exposure Compliance Requirement

### 2.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

#### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 2.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 3 EUT RF Exposure

GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.895	1±1	2	1.585	0.491	3.0
Middle (2441MHz)	1.723	1±1	2	1.585	0.495	
Highest (2480MHz)	1.643	1±1	2	1.585	0.499	
Conclusion: the calculated value $\leq 3.0$ , SAR is exempted.						

$\pi/4$ DQPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.332	2±1	3	1.995	0.618	3.0
Middle (2441MHz)	2.184	2±1	3	1.995	0.623	
Highest (2480MHz)	2.189	2±1	3	1.995	0.628	
Conclusion: the calculated value $\leq 3.0$ , SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: HK1911182927-E