

RF Exposure Evaluation

Standard(s): FCC Guidelines for Human Exposure IEEE C95.1 & FCC Title 47 Part 2.1091,

KDB 447498 D01 General RF Exposure Guidance v06

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0	614	1.63	*(100)	6		
3.0–30	1842/f	4.89/f	*(900/f ²)	6		
30–300	61.4	0.163	1.0	6		
300–1500			f/300	6		
1500-100,000			5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f ²)	30		
30–300	27.5	0.073	0.2	30		
300–1500			f/1500	30		
1500-100,000			1.0	30		

f = frequency in MHz

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Table for Filed Antenna

For 2.4GWiFi

Antenna ga	Antenna Type		
Ant1: 4.39dBi	Ant2: 2.75dBi	Internal antenna	

For 5GWiFi

Antenna ga	Antenna Type		
Ant1: 3.62dBi	Ant2: 4.67dBi	Internal antenna	



Test Result of RF Exposure Evaluation

Worst case as below

Operating Mode	Freq.	Maximum conducted output power	Max. positive tolerance according manufacturer	Directional Antenna Gain	Calculated EII	maximum RP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mW/cm ²)	
2.4G Wifi	2412-2462	19.10	1	6.66	26.76	474.24	1	0.0943
5G Wifi	5180-5825	19.59	1	7.19	27.78	599.79	1	0.1193

Note: 1. The calculated distance is 20 cm.

2. The 2.4G Wifi function can transmit at the same time with the 5G Wifi function

Simultaneous transmitting consideration

The ratio= MPE_{2.4G Wif}/limit+MPE_{5G Wif}/limit=0.0943/1+0.1193/1=0.2136<1.0

Result: Complies

(END OF REPORT)