

INTERTEK TESTING SERVICES

The Equipment Under Test (EUT) is a 2.4GHz Frequency Hopping GFSK Module Transmitter. It operates in frequency range of 2402MHz to 2478MHz with 2MHz channel spacing. There are total 23 hopping channels in normal operation. It is intended to be used as short range radio communication for embedded application inside a host. The EUT is powered by the host (3.3VDC).

The antenna used in the EUT is integral Monopole Antenna (1.5dBi), and the test sample is a prototype.

Antenna Type: Internal, Integral
Antenna Gain: 1.5 dBi
Nominal Conducted Peak Power: 10 dBm
Production Tolerance: +/- 3 dB

For Maximum Permissible Exposure (MPE) evaluation of the unit, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498.

For the unit, the measured powers among all the measured channels were within its production tolerance. The antenna gain is 1.5 dBi = 1.41 (num gain) and its maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\begin{aligned}\text{The EIRP Power} &= (13 + 1.5) = 14.5 \text{ dBm} \\ &= 28 \text{ mW}\end{aligned}$$

$$\begin{aligned}\text{The EIRP source-based time-averaging output power} &= (28 * 1) \text{ mW} \\ &= 28 \text{ mW}\end{aligned}$$

$$\begin{aligned}\text{The power density at 20cm} &= 28 / 4\pi R^2 \\ &= 0.0056 \text{ mW cm}^{-2}\end{aligned}$$

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm⁻² for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons.

The following RF exposure statement is proposed to be included in the user manual:

“ FCC RF Radiation Exposure Statement

Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the unit at least 20cm from nearby persons.”